



Catalogue

SHENGJIU CABINETS LOCK CO.,LTD.

ADD.: 10-1,Huahong International Centre, No.717,
Zhongxing Road, Ningbo, 315040 China
Tel: 0086-574-87845333 ext. 8002
Fax: 0086-574-87872762 E-mail: sj@shengjiu.com
Http: //www.shengjiu.com



ISO9001/ISO14001

**SHENGJIU
CABINETS LOCK**

**2016-2017
CATALOGUE**



Shengjiu Introduction

Shengjiu Cabinets Lock Co., Ltd is a comprehensive cabinet locks and hardware manufacturing enterprise integrating R&D, industry and trading. It was established in 1984.

Shengjiu has cultivated a professional and dedicated R&D team. We dedicate in developing three main principle products, such as cabinet locks, hinges and handles. We design products base on daring ideas and acquire the up-to-date information locally and abroad keenly. The company possesses more than 40 products of its own producing and selling right.

The company has a complete system in tracing, monitoring and inspecting starting from R&D, molding making, die-casting, punching, surface treatment and assembling.

After 30 years development, Shengjiu has already established its own quality systems and products standards. The company established the management standard after advanced equipment of mold and testing center was set up. We get ISO9001:2000 in 2001. At the same time we were beginning to pay more attention to environmental protection and got ISO14001:2004 in 2006.

Shengjiu regards quality as lifeline. We always concentrate on "Service first, quality first" to get more benefit for customer. We also provides different solutions to satisfy the customer's requirement. Meanwhile, We improves the company's internal competition, and provides the outstanding products to customer on time. Eventually achieve a win-win target.



Testing center

The testing center of Shengjiu was established in December 2006. It was divided into three sections: weather resisting test, mechanical property test and physically & chemically analytical test. According to the requirement of JB/T10382-2002 "the General Qualification for Mechanical Locks of Electrical Equipments" and the Shengjiu's standard for products quality, a full set of testing equipment was designed and set up. Counting or science, fair and accurate as its aim of work, Shengjiu gives a guarantee to the quality of its products and also lengthens its products' service life.

The tests include:

1. Weather resisting test
Salt spray test, ultraviolet light resisting test, dustproof test temperature and moisture/heat alternating test

2. Mechanical property test and equipments
Tensile test: for examining the tensile strength of the products and materials.
Impact load test: for examining the impact strength of the products and materials.
Image measuring instrument: for drawing products precisely and for analyzing the materials' whole image.
Intelligent electrochemical thickness gauge, hardness gauge, instrument for testing spring's pulling and pressing force, torsion stress testing instrument, vibration testing instrument, instrument for life test.

3. Physically & chemically analytical tests
Atomic absorption spectrophotometer: for analyzing components of materials; for measuring content of hazardous metal according to RoHS application.
Ultraviolet-visible spectrophotometer: for measuring content of hexavalent chromium.





Testing center equipment introduction



➤ Salt spray tester

Application: Test corrosion resistance of the protecting coating on product's surface



➤ Image measurement instrument

Application: Measure high precision, irregularly shaped product and draw the outline. Such as angle, radian, radius and hologram generates CAD and so on



➤ Ultraviolet light and climate resistance adjustable testing box

Application: Test the influence to the color of product's surface and mechanical property under harsh ultraviolet radiation or at temperature 50°C to 70°C



➤ Dust test chamber

Application: Test the influence to product's mechanical property in harsh sand and dust environment. Confirm whether the sand or dust will get into the inside of cabinets through cabinet locks. Survey the IP degree of cabinet locks



➤ High-low temperature-humidity test chamber

Application: Test the influence to product's mechanical and physical property in environment of different temperature and humidities



➤ Impact testing machine

Application: Test the impact resistance of different materials




➤ Pressure tester

Application: Test high pressure performance of electronic products. The main purpose of the pressure test is by testing circuit and housing leakage current value to check the ability of insulation withstand voltage.



➤ Electrical parameters measuring instrument

Application: Test electronic products, voltage, current, power factor.



➤ X Fluorescent direct reading spectrometer

Application: Test the percentage content of each element in the test sample or the ROHS test



➤ Lock insertion and removal rotation testing machine

Application: Test the usage counter of cylinder in the key plug, pull, turn bolt driven. Test machine shows the key inserted, pull force, torque value of rotation.



➤ Universal electronic spring pull and press tester

Application: 1. Test the physical property of different materials, such as the tensile strength, the yield stress and the point of elastic deformation
2. Test the bearing capacity of the cam, the magnitude of tensile resistance and the stress of the whole cabinet lock. Test the product's bearable load according to the testing graph
3. Test the magnitude of hinge's widthways and lengthways bearing capacity. Test the product's bearable load according to the testing graph




➤ Vickers hardness tester

Application: Measure the hardness of product after the heat treatment or the hardness of some big products with great hardness. All the products tested by electric hardness tester can also be tested by vickers microhardness tester. Electric hardness tester measures more fast. Vickers microhardness tester measures slowly and complexly



➤ High speed carbon-sulfur analyzer

Application: Test the percentage of carbon and sulfur in different materials



➤ Atomic absorption spectrophotometer

Application: Test the percentage of Ni, Pb, Cu, Zn, Fe, Al, Hg, Mn, Li, Mo and so on in different materials



➤ Waterproof test

Application: Test product waterproof level. Test product features in the water environment whether can normal operation. Test whether in-outside of product is sealed and impermeable



Design&Mould



Shengjiu focuses on every detail and humanization design of its' products. We try to attain the most simple operation method with the most reasonable structure on the premise of our products' quality.

Moulding tool, as the most important link of carrying out an idea into reality, is the key for guarantee factor to the product quality. Our CNC processing center, CNC engraving machine, electric impulse machine and experienced world designer, make the whole process to be more efficient and reliable.



CONCEPT OF NANOMETER SPRAY PAINTING

Nanotechnology is one of development from science-and-technology in the area of physics. Nanometer spray painting is which nanotechnology is used in manufacture. It forms compact nanometer painting on the surface of products which include exceptional hardness and high corrosion resistance materials. It can provide many kinds of colors and luster. This is one of the surface treatment which is environment friendly, lower cost, and durable. Nanometer spray painting is not eroded itself to protect the inside metal, the material can be eroded if the surface coating is destroyed, but it's excellent physical capability could replace electroplating treatment in a certain extent.



1	Highest temperature	150°C-180°C
2	Lowest temperature	-40°C
3	Hardness	GB/T6739-96 CHUNG HWA pencil 5-6H
4	Impact	GB/T1732-93 no rift, no fall-off (50kg.cm)
5	Resistance to Boid	Keep normal under 100°C water for 1 hour
6	Resistance to Acid	Keep normal under 5% HCl for 200 hours
7	Resistance to Alkali	Keep normal under 5% NaOH for 200 hours
8	Salt corrosive-resistance	GB/T1025-1997 under 5% NaCl 500hours in PH=7
9	RoHS compliance	Accordance with RoHS application
10	Color-resistance	Keep the normal color under drying in 180°C for 1 hour
11	Weather-resistance	GB/T4522-93 E<2 (ASTMG-53) QUV200 hours
12	Bend	GB11185-89 3MM Keep normal
13	Thickness	GB1764-79 40-60um



Vacuum Chrome Plated Nickel Plating Technology

Industrial manufacturing has brought severe damage to earth's ecosystem, and human living environment becomes worse and worse, so providing a better living environment is responsibility and obligation of every enterprise. Shengjiu is devoting to research environmental products and processes. Lasted five years Shengjiu research and explore the Vacuum Chrome-plating environmental finish process, and come true non-polluting &environmental processing, and processing parts in accordance with the standard of EU environmental protection.

Vacuum coating technology is the use of physical and chemical method, solid surface is coated with a layer of special performance, so that the solid surface with wear-resistant, high temperature resistance, corrosion resistance superior performance, antioxidation, anti radiation, conductive, magnetic, insulation and decoration and many other than solid material itself, to improve product quality, extend product life, save energy and achieve significant technical and economic benefit. Working principle: under the condition of vacuum, the metal, alloy or compound (evaporation or sputtering deposition), the cooling in the painted object film-forming process; vacuum coating is a new coating technology, coating preparation process is carried out under vacuum conditions, it with the existing liquid penetration the resulting coating has the following characteristics:

Preparation of thin film, the vacuum environment clean, film is not easy to be contaminated, can obtain good compactness, high purity, uniform coating film.

The film material and substrate material has a wide range of selectivity, thickness of the film can be controlled to produce various functional chrome film.


The film and substrate adhesion strength is good, the film is firm.

It does not produce waste, can avoid the pollution of the environment.


The coating structure is generally divided into: vacuum coating material, vacuum coating, primer, topcoat.



» Processing equipment showing



» Hardness test



» Adhesion test

Vacuum Chrome Plated Nickel Plating Technology

Compared to common plating, vacuum plating can meet the all general performance of common electroplating, its special character more suitable for all kinds of harsh environment, and the coating in line with the EU ROHS related law Requirements. The following is a vacuum chrome of the performance indicators:

Test Items	Technical data	
	Vacuum Chrome Plating	Usual plating
Impact strength	GB/T1793-1993 50kg·cm The surface is OK	/
Boling water resistance	120°C 1hour	/
Hardness	According GB/T6739-2006 more than 2H	/
Adhesive	GB/T 5270-2005 no obscession	GB/T 5270-2005 no obscession
Thickness	40-60um	8-12um
Corrosion resistance	GB/T10125-1997 more than 96H NSS	GB/T10125-1997 more than 48H NSS
Environmental protection	No waste water, so won't produce the products with environmental safety risk	Produce too much heavy metal waste water, not RoHS, so the products also have risk for environmental.

Product picture effect comparison (the appearance effect without any difference)



Vacuum chrome plated



Common electroplated



A STRONG SALES NETWORK

With the continued business expansion, Shengjiu has **7** companies which located in city of Beijing, Shanghai, Shenzhen, Wuhan, Qingdao, Ningbo and UAE. It's excellent quality high reputation, prompt service have won trust and favorable comments from a number of clients, and thus build up a reliable brand of Shengjiu(SJ). We own **26** distributors in domestic and **9** distributors in singapore, Japan, Korea, India, Sweden, Germany, Spain, South Africa, and Italy. That make Shengjiu a strong sales network to service for our valuable clients.


List of contents

Characteristic explain	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket	Index
Accessories ➤													
Electronic lock ➤													
Handle lock ➤													
Cylinder lock ➤													
Plane lock ➤													
Rod control lock ➤													
Panel lock ➤													
Toggle and hook ➤													
Handles ➤													
Door stop ➤													
Hinge ➤													
Seal gasket ➤													

► Explanation of pictograms

	Outside the gasketing		Inside the gasketing		Hinge exposed		Hinge concealed		Hinge half-concealed
IP40	IP-rating IP40	IP50	IP-rating IP50	IP54	IP-rating IP54	IP64	IP-rating IP64	IP65	IP-rating IP65
	Tighten	RL	Door RH and LH-version	R	Door RH-version	L	Door LH-version		RoHS Application
	Two-point latching		Three-point latching		Alternative point latching		Multipoint latching		Stainless steel



► Explanation of LH and RH version





► Abbreviation

Lock: MS	Nut: NT	Right-hand:RH	Brass: Br
Toggle: DK	Vibration proof screw: SW	Anticlockwise rotation: ACW	Zinc die-casting: ZDC
Handle: LS	key: K	Clockwise rotation: CW	Aluminum: ALU
Door stop: TX	Gasket: G	Stroke: Dm	Polyamide: PA
Hinge: CL	Pin: P	Rotation angle: Ra	Polypropylene: PP
Rod: LG	Latch: MB	Powder coated finish: CS	Acrylonitrile Butadiene
Rod accessories: RG	Thickness: Ts	Plated finish: CP	Styrene: ABS
Handle pull: HP	Adjustable distance: Ha	Max-Torque: Tmax	Polycarbonate: PC
Waterproof cap: WP	Stop height: H	Max-load: Fmax	Rubber: RB
Dustproof cap: DP	Groundwork height: GH	Cold rolled steel: CRS	
Profile Insert: TC	Bend height: BH	Spring steel: Fst	
Cam: S	Left-hand: LH	Stainless steel: SUS	

► H and GH specification



GH: the distance A from the abutted surface between lock body and door to the abutted surface between cam and lock body changes when Ts changes.



GH: the distance A from abutted surface between housing and door to the abutted surface between cam and housing is invariable when Ts changes. GH is measured from inboard door. The product is separable structure in common case. H=GH+BH




► IP-rating

The IP protection category is characterised by two numerals for protection against contact, foreign objects and water. As defined in IEC60529, the description is following:

1st numeral	Description	2nd numeral	Description
0	Non-protected	0	Non-protected
1	Protected against solid foreign objects with a diameter of 50mm and greater (such as hand)	1	Protected vertically falling water drops (such as condensation water)
2	Protected against solid foreign objects with a diameter of 12.5mm and greater (such as fingers)	2	Protected vertically falling water drops when the enclosure is tilted up to 15°
3	Protected against solid foreign objects with a diameter of 2.5mm and greater (such as tools or thick wires)	3	Protected against splashing water
4	Protected against solid foreign objects with a diameter of 1mm and greater (such as most wires or screws)	4	Protected against splashing water
5	Dust-protected	5	Protected against water jets
6	Dust-tight	6	Protected against powerful water jets
		7	Protected against the effects of temporary immersion in water
		8	Protected against the effects of continuous immersion in water

Accessories



S1B Series



Remark: Default thickness 3mm, please specify on request of other material, center distance and thickness. Code prefixed with D stands for cam with stopper.

Cam code	BH TS=3	ERP
S1B45N02	-2	S1B45N02019
S1B4500	0	S1B45Y00002
S1B4502	2	S1B45Y02002
S1B4504	4	S1B45Y04002
S1B4506	6	S1B45Y06004
S1B4507	7	S1B45Y07002
S1B4508	8	S1B45Y08002
S1B4510	10	S1B45Y10002
S1B4512	12	S1B45Y12002
S1B4514	14	S1B45Y14002
S1B4516	16	S1B45Y16002
S1B4518	18	S1B45Y18004
S1B4520	20	S1B45Y20002



AS3B Series



Remark: Default thickness 3mm, please specify on request of other material, center distance and thickness. Code prefixed with D stands for cam with stopper.



Cam code	BH	ERP
AS3B45N02	-2	2882452023
AS3B4500	0	2882450015
AS3B4502	2	2882452024
AS3B4504	4	2882452025
AS3B4506	6	2882452026
AS3B4507	7	2882452027
AS3B4508	8	2882452028
AS3B4510	10	2882452029
AS3B4512	12	2882451226
AS3B4514	14	2882452030
AS3B4516	16	2882452031
AS3B4518	18	2882452032
AS3B4520	20	2882452022

S3B Series





Cam code	BH	ERP
S3B4500	0	2882450029
S3B4504	4	2882450418
S3B4508	8	2882450822
S3B4510	10	2882451020
S3B4512	12	2882451218
S3B4514	14	2882451415
S3B4516	16	2882451611
S3B4520	20	2882452013
S3B4522	22	2882452212

S1B2836H





Cam code	Rotation Radius	ERP
S1B2836H	28	S1B28Y36002

S1BK Series





Cam code	BH	L	ERP
S1B33N4K	-4	33	S1B33N04001
S1A7200	0	72	S1A72Y00001

S1A Series





Cam code	BH	L	ERP
S1A3500	0	35	S1A35Y00005
S1A3900	0	39	S1A39Y00001
S1A7200	0	72	S1A72Y00001

S1B2328H





Cam code	Rotation Radius	ERP
S1B2328H	23	S1B23Y28002

S1B1179D



Cam code	BH	Material	ERP
S1B1179D	11	SUS	S1B11Y79003


S1C Series



Cam code	BH	L	ERP
S1C4000	0	40	S1C40Y00001
S1C6300	0	63	S1C63Y00002
S1C7200	0	72	S1C72Y00002

Accessories


S1K4513



Electronic lock
Handle lock
Cylinder lock
Plane lock

Cam code	BH	L	ERP
S1K4513	-13	45	S1K45N13003


S1K3500



Rod control lock
Panel lock

Cam code	BH	L	ERP
S1L3500	0	35	S1K35Y00002


S1G Series



Toggle and hook
Handles

Cam code	BH	L	ERP
S1G2300	0	23	S1G23Y00002
S1G2304	4	23	S1G23Y04002
S1G2308	8	23	S1G23Y08002
S1G2312	12	23	S1G23Y12002
S1G2316	16	23	S1G23Y16002
S1G2320	20	23	S1G23Y20002
S1G2304	-4	23	S1G23N04001
S1G2308	-8	23	S1G23N08005
S1G2312	-12	23	S1G23N12001
S1G2316	-16	23	S1G23N16001
S1G2320	-23	23	S1G23N20005


S1H Series



Door stop

Cam code	BH	L	ERP
S1H4819	19	48	S1H48Y19001


S1D Series(Left)



Hinge

Cam code	BH	L	ERP
S1D5600Z	0	56	S1D56Y00006
S1D5608Z	8	56	S1D56Y08002
S1D5612Z	12	56	S1D56Y12002
S1D5618Z	18	56	S1D56Y18002
S1D5628Z	28	56	S1D56Y28001


S1C3700D



Panel lock

Cam code	BH	L	ERP
S1C3700D	0	36.5	S1C37Y00002


S1K3606



Toggle and hook

Cam code	BH	L	ERP
S1K36N06	-6	36	S1K36N06001


S1M3300



Handles

Cam code	BH	L	ERP
S1M3300	0	33	S1M33Y00002


S3H6028



Door stop

Cam code	BH	L	ERP
S3H6028	13.5/18.5/23.5/28.5	60	S3H60Y28001


S1D Series(Right)



Hinge

Cam code	BH	L	ERP
S1D5600Y	0	56	S1D56Y00002
S1D5608Y	8	56	S1D56Y08005
S1D5612Y	12	56	S1D56Y12005
S1D5618Y	18	56	S1D56Y18005
S1D5628Y	28	56	S1D56Y28005

S1C3621D




Seal gasket


Cam code	BH	L	ERP
S1C3621D	21	36	S1C36Y21002

Accessories

S2C2100




Cylinder lock | Handle lock | Electronic lock




Cam code	ERP
S2C2100	S2C21Y00002

S2B1800




Plane lock | Cylinder lock | Handle lock




Cam code	ERP
S2B1800	S2B18Y00005

S3B6500




Cylinder lock | Handle lock | Electronic lock




Cam code	ERP
S3B6500	S3B65Y00002

S3B6800A




Plane lock | Cylinder lock | Handle lock




Cam code	BH	L	ERP
S3B6800A	0	68	S3B68Y00002

S3C Series




Handle lock | Cylinder lock | Electronic lock




Cam code	BH	L	ERP
S3C8600	0	86	S3C86Y00002
S3C6527	27	65	S3C65Y27002
S3C4851	51	48	S3C48Y51002

S3C7200




Plane lock | Rod control lock




Cam code	BH	L	ERP
S3C7200	0	72	S3C72Y00002

S2C2400




Panel lock | Handles | Toggle and hook




Cam code	ERP
S2C2400	S2C24Y00002

S2C Series




Hinges | Door stop | Handles




Cam code	L	ERP
S2C2000	0	S2C20Y00002
S2C2500	25	S2C25Y00002

S3B6300A




Handles | Panel lock | Door stop




Cam code	BH	L	ERP
S3B6300A	0	63	S3B63Y00002

S3B6000A




Handles | Panel lock | Door stop




Cam code	BH	L	ERP
S3B6000A	0	60	S3B60Y00002

S3C Series




Handles | Panel lock | Door stop




Cam code	BH	L	ERP
S3C5000	0	50	S3C50Y00003
S3C7000	0	70	S3C70Y00002
S3C8800	0	88	S3C88Y00002

S3C6200




Hinge | Seal gasket




Cam code	BH	L	ERP
S3C6200	0	62	S3C62Y00003

Accessories

S3C4413 Series





S3C4413Y (right cam)





Cam code	BH	L	ERP
S3C4413Y	13	44	2883441307
S3C4413Z	13	44	2883441308

S1A1403X




Cam code	ERP
S1A1403X	S1A14Y03001

S1B3011D




Cam code	L	ERP
S1B3011D	30	S1B30Y11002

PN0011
PN0012





Part code	H	Remark
PN0011	H=4	Suitable cam thickness 3mm
PN0012	H=5	Suitable cam thickness 4mm

PN0015
PN0016



Part code	H	Remark
PN0015	H=4	Suitable cam thickness 3mm
PN0016	H=5	Suitable cam thickness 4mm

A1001



Change cam cut out 8mm to 7mm

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod lock

Panel lock

Toggle and hook



Handles

Door stop

Hinge



Seal gasket

S1B3502A





Cam code	BH	L	ERP
S1B3502A	0	35	S1B35Y02001

S1B2402X




Cam code	BH	L	ERP
S1B2402X	2	24	S1B24Y02001

S1B6800X



Cam code	L	ERP
S1B6800X	68	28768000001

Cam code specification



S:Cam tag

1-point cam
2-points cam
3-points cam

Hole code
A:Ø7x7
B:Ø8x8
C:Ø10x10
D:Special cam
G:Ø6x4.8 Waist hole
H:Ø16x10 Waist hole
K:Ø 8x6.5 Waist hole
M:Ø 10x8 Waist hole

(Length)L




Remark:H=GH+BH

If you can't find a suitable single point cam in our catalog, please refer to our S1B series cam, the default thickness is 3mm. Hole size (), bend height(BH) and center length(L), can be tailor-made, MOQ 1000pcs.

Accessories

Example of rod-latch application



Calculate the length of the rod

Calculation method of coincident length of door center and center line of rotation part

$$L1=F/2-A+(Dm-2)$$

$$L2=F/2-B+(Dm-2)$$

Calculation method of coincident length of door center and center line of lock

$$L1=F/2-[A+(D/2-C)]+(Dm-2)$$


$$L2=F/2-[B-(D/2-C)]+(Dm-2)$$

Remark: the effective length of connecting piece should be deducted if a connecting piece is needed for fitting. This calculation method is applicable for those rods with seals fitted inside. Be aware of the actual installation conditions when using the above methods.

Dm: the code of driving distance

F:door frame height

Cabinet structural sketch



LG001-1




Zinc-plated steel, cone-round rod

ERP

LG001F3D000003

Please specify the rod length "L" purchase

LG001-2




Zinc-plated steel, match with PA roller round rod

ERP

LG001F3D000004

Please specify the rod length "L" purchase

LG001-3



Zinc-plated steel, bend, round rod

ERP

LG001F3D000005

Please specify the rod length "L" purchase

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles


Door stop

Hinge

Seal gasket

Accessories

RG001-1



Electronic lock

Handle lock


Cylinder lock

Plane lock

Rod control lock

Panel lock


RG001-2



Black PA guide, fix with M6*16~20 weld screw, connect strap can be removed

ERP	Material
1110000001	Black PA


RG001-3



Black PA guide, zinc-plated nut, fix with M6*16~20 weld screw

ERP	Material
1110000003	Black PA


RG001-9



PC guide

ERP	Material
1110010009	PC(White)


RG010



PA guide

ERP	Material
1110100001	Black PA

RG001-4



Toggle and hook


Handles

Door stop

Hinge


Seal gasket

RG001-5



ERP	Material
1110010001	Black PA


RG001-8



Black PA guide, fix with M6*16~20 weld screw


ERP	Material
1110000006	Black PA

RG001-11



ERP	A	B	Welding screw specification
1110020001	32	24	M6x16
1110020002	38	30	M6x20
1110020003	42	34	M6x20


RG002



Black PA guide, nut inside

ERP	A	B	Welding screw specification
1110021102	32	24	M6x16
1110021103	38	30	M6x20



RG002-A



ERP	A	B	Welding screw specification
1110021102	32	24	M6x16
1110021103	38	30	M6x20

Accessories



RG003-1



Black ZDC catcher, match with the rod white rivet

ERP	Material
1110030001	ZDC



RG003-2



Black ZDC clip catcher, PA pin ,fit with 2MM door

ERP	Material
1110030002	ZDC



RG003-3



Zinc plated ZDC catcher,Zinc plated steel pin, fixed with M6 screw.

ERP	Material
1110030003	ZDC



RG003-7



Zinc plated ZDC catcher, fixed with M6 countersunk head screw.

ERP	Material
1110030007	ZDC



RG003-8



Zinc plated ZDC cassette catcher, fixed with M6 countersunk head screw.

ERP	Material
1110030008	ZDC

RG003-9





Zinc plated ZDC Cassette fixed buckle, fixed with M6countersunk head screw.

ERP	Material
1110030009	ZDC

Panel lock



RG003-4



Zinc plated ZDC catcher,stainless steel pin, fixed with M6 screw.

ERP	Material
1110030004	ZDC



RG003-5



Zinc plated ZDC catcher, fixed with M6 countersunk head screw, match with the rod with roller.

ERP	Material
1110030005	ZDC



RG003-6



Zinc plated ZDC catcher, fixed with M6 countersunk head screw, match with locking pin flat rod.

ERP	Material
1110030006	ZDC



RG003-10



Zinc plated ZDC Cassette fixed buckle, fixed with M6 countersunk head screw.

ERP	Material
1110030010	ZDC



RG003-11



Zinc plated ZDC catcher, fixed with M6 countersunk head screw, match with locking pin flat rod.

ERP	Material
1110030012	ZDC

RG003-14




Cam catcher; L and R available

ERP	Material
	ZDC

Accessories


RG003-15



Plane lock | Cylinder lock | Handle lock | Electronic lock

ERP	Material
2240030001	ZDC


RG004-1



Rod control lock

ERP	Material
1110040001	Black PA


RG004-2



PA guider

ERP	Material
1110040002	White ABS


RG005-3



Cam catcher,match with S1A1403.

ERP	Material
1110050003	ZDC


RG006-1



Zinc plated ZDC,connect accessories,Zinc plated steel,M6 set screw.

ERP	Material
1110061001	ZDC


RG006-2



ERP	Material
1110060002	Black PA

Accessories

RG004-3




Panel lock

Hinge	Handles	Toggle and hook
Door stop		

Black ABS guider

ERP	Material
1110040003	Black ABS

RG005-1




Door stop

Door stop	Handles	Toggle and hook
Hinge		

ZDC fix catcher,match with LG002-1/2.

ERP	Material
1110050001	ZDC

RG005-2




Handles

Door stop	Handles	Toggle and hook
Hinge		

Cam fix fastener,match with S1A1403.

ERP	Material
1110050002	ZDC

RG007




Door stop	Handles	Toggle and hook
Hinge		

ZDC connect cover,nylon rolle,match with LG001-1 and LG003.

ERP	Material
1110070001	ZDC/PA

RG008




Door stop	Handles	Toggle and hook
Hinge		

Nylon guide,match with Ø8 mm round rod.

ERP	Material
1110080001	Black PA

RG011



Hinge	Handles	Toggle and hook
Door stop		

ZDC Guide

ERP	Material
2130110001	ZDC

Accessories

Accessories	RG015	RG015-2	WP001	WP002	WP003	Accessories																				
Electronic lock						Electronic lock																				
Cylinder lock						Handle lock																				
Plane lock						Cylinder lock																				
PA guide,match with 3X14 flat rod.	PA guide,match with 3X14 flat rod.	PA guide,match with 3X14 flat rod.	Black PA water-proof cap	Black PA water-proof cap	Black PA water-proof cap	Plane lock																				
Rod control lock	<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1110150001</td><td>Black PA</td></tr> </table>	ERP	Material	1110150001	Black PA	<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1110150002</td><td>Black PA</td></tr> </table>	ERP	Material	1110150002	Black PA	<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1150010001</td><td>Black PA</td></tr> </table>	ERP	Material	1150010001	Black PA	<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1150020001</td><td>Black PA</td></tr> </table>	ERP	Material	1150020001	Black PA	<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1150030001</td><td>Black PA</td></tr> </table>	ERP	Material	1150030001	Black PA	Rod control lock
ERP	Material																									
1110150001	Black PA																									
ERP	Material																									
1110150002	Black PA																									
ERP	Material																									
1150010001	Black PA																									
ERP	Material																									
1150020001	Black PA																									
ERP	Material																									
1150030001	Black PA																									



Accessories for rods

Rod guide code	Rod code
RG001-1	LG004、LG005、LG006、LG010
RG001-2	LG004、LG005、LG006、LG010
RG001-3	LG004、LG005、LG006、LG010
RG002	LG001-1、LG001-2、LG001-3、LG003、LG007-A
RG002-A	LG001-1、LG001-2、LG001-3、LG003、LG007-A、LG007-B
RG004-1	LG001-1、LG001-2、LG001-3、LG003、LG007-A
RG004-2	LG001-1、LG001-2、LG001-3、LG003、LG007-A
RG004-3	LG001-1、LG001-2、LG001-3、LG003、LG007-A
RG006-2	LG002-1、LG002-2
RG006-2A	LG001-1、LG001-2、LG001-3、LG003、LG007-A、LG007-B
Rod guide code	Rod code
RG003-1	LG004、LG005、LG010
RG003-2	
RG003-3	
RG005-1	LG002-1、LG002-2
RG005-2	LG002-1、LG002-2
RG006-1	LG001-1、LG001-2

Black PA water-proof cap	Black PE water proof with handle pull	Chrome plated zdc water-tight cap,sus bracket												
<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1150040001</td><td>Black PA</td></tr> </table>	ERP	Material	1150040001	Black PA	<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1150070001</td><td>BlackPE</td></tr> </table>	ERP	Material	1150070001	BlackPE	<table border="1"> <tr> <th>ERP</th><th>Material</th></tr> <tr> <td>1150010002</td><td>Zinc plated ZDC/SUS</td></tr> </table>	ERP	Material	1150010002	Zinc plated ZDC/SUS
ERP	Material													
1150040001	Black PA													
ERP	Material													
1150070001	BlackPE													
ERP	Material													
1150010002	Zinc plated ZDC/SUS													

Accessories



HP001



Black PA handle pull

ERP	Material
1150010003	Black PA



HP002



Black rubber handle pull

ERP	Material
1150020002	RB




HP003



Black PP handle pull

ERP	Material
1150030002	Black PP

Locking screw



Washer screw size	H
M6 x 8	8
M6 x 10	10
M6 x 27	27
M6 x 55	55



Washer screw size	H
M4 x 8	8

Washer screw size	H
M6 x 5	5
M6 x 8	8
M6 x 10	10
M6 x 12	12

Washer screw size	H
M8 x 12	12

Panel lock


A3001



Cannula

ERP	Material
1153001001	SUS
1153001002	Packed black powder Q235


A3002




Zinc plated steel seating, applicable for locks similar to MS705

ERP	Material
1110040001	Zinc plated Q235


Cylinder insert




Chrome plated ZDC insert default Key K140,Automatic reset lock tongue.




Chrome plated ZDC insert default Key K140,Automatic reset lock tongue.




Brass Anti-thief insert on request of safety and special circumstance.




Brass Anti-thief insert on request of safety and special circumstance.




Chrome plated insert,default K140, automatic reset.




Chrome plated insert, with button, automatic reset.



Chrome plated ZDC insert,with stainless steel safety cover and stainless steel screw. default key K140,automatic reset.




Chrome plated ZDC insert,match with padlock,default key K290,automatic reset.




Chrome plated ZDC insert,match with padlock,default key K290,automatic reset.

Model	A	B
TC06-2	17	Ø12
TC06-3	26.5	Ø14
TC06-4	12	Ø8x11



Chrome plated ZDC insert, auto-resile striking plate, see P061 for insert sets.








	Specification	Code	Key Code
Insert insert	Double bit 4mm	TC02-1	K15-1/K15-1F/K15-1A
	Double bit 3mm	TC02-1A	K15-1/K15-1F/K15-1A
	Hooked	TC02-2	K15-1
	Triangular 8mm	TC02-3	K15-3/K15-3F
	Square 8mm	TC02-4	K15-4/K15-4F
	Square 8mm with slot	TC02-4A	K15-4/K15-4F
	Square 6mm	TC02-5	K15-5/K15-5F/K15-5A
	Square 7mm	TC02-6	K15-6/K15-6F
	Socket Hexagon	TC02-7	K15-7/K15-7F
	Slot	TC02-8	
	Hexagon	TC02-9	K15-9/K15-9F
	Thron	TC02-10	K15-10
TC08	Oblate-type	TC02-11	K15-11
	Triangular 7mm	TC02-12	K15-3/K15-3F



Insert list on P061

	Specification	Code	Key Code
Insert insert	Anti-thief insert	TC08-A1	K14/K19
	Double bit 4mm	TC08-B1	K15-1/K15-1F/K15-1A
	Double bit 3mm	TC08-B1A	K15-1/K15-1F/K15-1A
	Hooked	TC08-B2	K15-1
	Triangular 8mm	TC08-B3	K15-3/K15-3F
	Square 8mm	TC08-B4	K15-4/K15-4F
	Square 8mm with slot	TC08-B4A	K15-4/K15-4F
	Square 6mm	TC08-B5	K15-5/K15-5F/K15-5A
	Square 7mm	TC08-B6	K15-6/K15-6F
	Socket Hexagon	TC08-B7	K15-7/K15-7F
	Slot	TC08-B8	
	Hexagon	TC08-B9	K15-9/K15-9F
Door stop	Thron	TC08-B10	K15-10
	Oblate-type	TC08-B11	K15-11
	Triangular 7mm	TC08-B12	K15-3/K15-3F

Key series



Key different list

Key code	Applicable products model	Key different ifferentiaty	Remark
K72-2	MS829	10 Sets	Rod control lock
	MS819, MS828, MS831	200 Sets	
	MS712, MS712-Q, MS713, MS727	200 Sets	Panel lock
K72-3	TC01, TC04, TC05, TC05-2		Cylinder
	MS301, MS304, MS305, MS306, MS307, MS310, MS317		Handle lock
	MS762, MS705-3E	500 Sets	Insert lock
	MS737		Panel lock
	MS820-4,MS830, MS830-8, MS832, MS833,MS835		Rod control lock

ELECTRONIC LOCK SERIES

Active electronic lock series



Cylinder lock

Passive electronic lock series(New product)






These locks above can be chosen to use electronic lock cylinder, the installation hole size refer to the mechanical lock, please consult the technical department before ordering.

DS864-8-7A Control System Principle

Single Control Mode



Network Control Mode



ERP	Specification
DS864Z2E723004	Mechanical insert, switch control, without padlock
DS864Z2E723005	Mechanical insert, switch control, with padlock
DS864Z2E723006	Mechanical insert, DO control, without padlock
DS864Z2EE06001	Electronic insert, DO control, without padlock

Remark: Default cam is S3C5800



RL IP65 RoHS

Main material and finish : Black painted (high salt mist resistant) ZDC housing, handle, stainless steel cam. Plastic electronic boxplastic box.

Application : Active electronic lock.

Rated voltage: DC 12V

Rated current: ≤0.3A

Consumption Power: ≤ 3.6W

Remark: Optional mechanical insert and electronic insert

This product is used for indoor.

Please read operating introduction in advance and operate according to introduction.

Performance Parameter

Handle load tension capability: ≤600N

Handle load torque capability: ≤30N.m

Working Environment

Temperature: -40 ~ +65°C

Humidity: 5 ~ 90%

Altitude: -60m~4000m




Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

DS899 Control System Principle

Single Control Mode



Network Control Mode



ERP

DS899Z2EE03001

Remark: Default cam is S3C5800

DS899



RL IP65 RoHS

Main material and finish : Black painted (high salt mist resistant) ZDC housing, handle, stainless steel cam. Plastic electronic boxplastic box.

Application : Active electronic lock.

Rated voltage: DC 12V

Rated current: ≤0.25A

Consumption Power: ≤ 3.6W

Remark : Default head face pin tumbler insert.

This product is used for indoor.

Please read operating introduction in advance and operate according to introduction.

Performance Parameter

Handle load tension capability: ≤600N
Handle load torque capability: ≤30N.m

Working Environment

Temperature: -40 ~ +65°C


Humidity: 5 ~ 90%

Altitude: -60m~4000m




Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

DS899-1A Control System Principle

Single Control Mode



Network Control Mode



DS899-1A



RL IP65 RoHS

Main material and finish : Black painted (high salt mist resistant) ZDC housing, handle, stainless steel cam. Plastic electronic boxplastic box.

Application : Active electronic lock.

Rated voltage: DC 12V

Rated current: ≤0.25A

Consumption Power: ≤ 3.6W

Remark : Default head face pin tumbler insert.

This product is used for indoor.

Please read operating introduction in advance and operate according to introduction.

Performance Parameter

Handle load tension capability: ≤600N

Handle load torque capability: ≤30N.m

Working Environment

Temperature: -40 ~ +65°C



Humidity: 5 ~ 90%

Altitude: -60m~4000m

ERP	Specification
DS899Z2E723001	Swiping Card Control
DS899Z2E723002	Bluetooth Control
DS899ZEE06001	Swiping Card Control + Electronic cylinder Control

Remark: Default cam is S3C5800

DS912、DS913 Control System Principle



ERP DS912Z2E723001

DS912	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

DS912

Accessories:

- Electronic lock
- Handle lock
- Cylinder lock
- Plane lock
- Rod control lock
- Panel lock
- Toggle and hook
- Handles
- Door stop
- Hinge
- Seal gasket

NEW

RL IP65 RoHS

Handling: High salt spray resistance
Application : Active electronic lock (idle)
Rated voltage: DC 12V
Rated current: Unlock condition≤0.25A
 Standby mode≤0.05A
Remark : This product is suitable used for outdoor.
 Read the operating instructions carefully before usage and operate according to the instructions.

Working Environment
Temperature: -40 ~ +65°C
Humidity: 5 ~ 90%
Altitude: -60m~4000m

DS913



NEW

IP65 RoHS

Handling: Zinc alloy housing, panel, plastic electronic box.

Handling: High salt spray resistance

Application: Active electronic lock

Rated voltage: DC 12V

Rated current: ≤0.25A

Consumption Power: ≤3W

Remark: This product is suitable used for outdoor.



Read the operating instructions carefully before usage,
operation according to the instructions.

Working Environment

Temperature: -40 ~ +65°C

Humidity: 5 ~ 90%

Altitude: -60m~4000m



Cut out

ERP DS913Z2E723001

Optional functions	Optional accessories
Rotation handle	Unlock tool keys
Mechanical cylinder	Bluetooth electronic key
Electronic cylinder	10 core cable(meter)
Insert controlled	Mobile APP Software
Built-in bluetooth	PC Management Platform
RS485 Protocol communication function	

The default basic functions: remote door opening and signal sensing (no rotating handle) matching function and accessories need to be noted in the order.

Remark: Default cam S3C5800

HANDLE LOCK SERIES



Cylinder lock

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Plane lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	------------	-------------	-----------------	-------------



RL

Main material and finish : Bright chrome-plated ZDC handle and housing, white zinc-plated steel cam, bright chrome plated button and white zinc plated shaft

Application : Quarter-turn opening or closing

Remark : Default Key K050

Default cam : S1H48Y19002

Performance parameter:

Maximum static load:220N



Recommended nut tightening torque:20N.m

Maximum input torque:15N.m


Specification	Model	ERP
With insert	MS301-1	MS301Z3A050008
Without insert	MS301-2	MS301Z3A000001
With button type	MS302-1	MS302Z3A000001
With padlock type	MS302-2	MS302Z3A000008

Remark : Default Cam S1H4819


Cam S1H4819 (Optional)



Remark: shadow parts shows mounting hole allocation between housing and door panel



ERP MS304Z3A050008
Remark : Default cam S1H4819



Remark: cut out size, RH, LH, and cam selection refer to MS301 on catalogue

Specification	Model	ERP
With insert	MS306-1	MS306Z3A050005
Without insert	MS306-2	MS306Z3A000007
With button type	MS306-3	MS306Z3A000002
With padlock type	MS306-4	MS306Z3A000006

Remark : Default Cam S1H4819



RL

Main material and finish : Bright chrome-plated ZDC handle and housing, white zinc-plated steel cam

Application : Quarter -turn opening or closing

Remark : Default Key K050

Default cam : S1H48Y19002

Performance parameter:

Maximum static load:220N

Recommended nut tightening torque:20N.m

Maximum input torque:15N.m



RL

Material and finish : Bright chrome-plated ZDC handle and housing, white zinc-plated steel cam, bright chrome plated steel button and shaft

Application : Quarter-turn opening or closing

Remark : Default key K050

Default cam : S1H48Y19002

Performance parameter:

Maximum static load:220N

Recommended nut tightening torque:20N.m

Maximum input torque:15N.m

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Plane lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	------------	-------------	-----------------	-------------

Accessories
Electronic lock
Handle lock

Cylinder lock
Plane lock

Rod control lock

Panel lock

Toggle and hook
Handles

Door stop
Hinge

Seal gasket

MS307



RL IP54

Main material and finish : Bright chrome-plated ZDC handle and housing, white zinc-plated steel cam

Remark : Default key K050



Default cam : S1H48Y19002

Performance parameter:

Maximum static load:220N

Recommended nut tightening torque:20N.m

Maximum input torque:15N.m



Remark : RH,LH, and cam selection please refer to MS301 on catalogue

ERP MS307Z3A050011

Remark : Default cam S1H4819

MS308-2



RL IP54

Main material and finish:

Bright chrome plated ZDC handle, housing and white zinc plated steel cam.

Application:Quarter-turn opening and closing.



Remark:No key,cut out size same as MS308

Performance parameter




Maximum static load:220N

Recommended nut tightening torque:20N.m

Maximum input torque:15N.m



ERP MS308Z3A000004



Feature Description	Product item	ERP
with cylinder,with padlock device,LH	MS315-4-Z	MS315Z3A280018
with cylinder,with padlock device,RH	MS315-4-Y	MS315Z3A280013

MS315-4



NEW

RL IP55

Main material and finish:Bright chrome-plated ZDC handle,housing,insert,color zinc plated carbon steel shaft,stainless steel lock panel.

Application:Quarter-turn opening and closing.

Remark:Default key K280

Performance parameter

Handle load tension capability:780N

Recommended nut tightening torque:5N.m

Maximum input torque:15N.m

Accessories
Electronic lock
Handle lock
Cylinder lock
Plane lock
Rod lock
Panel lock
Toggle and hook
Handles
Door stop
Hinge
Seal gasket

MS317



Seal gasket	Hinge	Door stop	Handles	Panel lock	Rod control lock	Toggle and hook	Toggle and hook	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	------------	------------------	-----------------	-----------------	------------	---------------	-------------	-----------------	-------------

RL IP54




Main material and finish : Bright chrome-plated ZDC handle, housing and insert, white zinc-plated steel cam, teeth washer
Application : 60 degree rotation opening or closing

Remark : Default key K050

Default cam : S1B45Y00002

Performance parameter:



Maximum static load:140N
 Recommended nut tightening torque:20N.m
Maximum input torque:15N.m



Opening from left rotation Opening from right rotation



ERP MS317Z3A050001

Remark : Default cam S1B4500



Remark : Change the location of keeper and cam installation position can be adjusted groundwork height GH

ERP MS317Z3A011001



ERP MS322Z2B000003

Remark : Default cam S1B5406 (square 8*8 cam optional)

MS317-1A



RL IP65

Main material and finish : Bright chrome plated ZDC handle, housing and dust cap.

Application : 60 degree rotation opening or closing.

Remark: Default key K110.

Performance parameter:

Maximum static load:220N
 Recommended nut tightening torque:20N.m
Maximum input torque:15N.m



L IP65 3PL ▶

Main material and finish : Nanometer painting ZDC handle and housing, white zinc-plated steel padlock and cam

Application : 90 degree rotation opening or closing, pad-lockable

Default cam : S1B54Y06001

Performance parameter:

Maximum static load:220N
 Recommended nut tightening torque:20N.m
Maximum input torque:15N.m



Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock
-------------	-----------------	-------------	---------------	------------	----------

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
------------	-----------------	---------	-----------	-------	-------------

--	--	--	--	--

Seal gasket	Hinge	Door stop	Handles	Panel lock	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	------------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------

MS320



Remark : applicable door thickness Ts=50

RL

Main material and finish : PA handle and housing, white zinc-plated steel shaft

Application : Quarter-turn opening or closing


Remark : Default key K160

Performance parameter


Handle load tension capability:91N

Maximum input torque:10N.m


Installation Method



Horizontal hole position
(housing)



Vertical hole position
(housing)



When housing is horizontal hole position,
handle should be counterclockwise rotation



When housing is vertical hole position,
handle should be clockwise rotation

ERP


MS320N00160004

	MS324-1 Black powder coating ZDC	MS324-1B Stainless steel
ERP	MS324Z1A140010	MS324S4B140007

Remark: Default cam S1B4507 (Square 8*8 cam optional)



Cut out



MS323



RL

Main material:PA6+30%GF black handle, and housing.

Application:90°rotation opening and closing.

Remark:L2D0143 cylinder components(with key), white zinc plated zinc alloy/K14 Blank key.

Performance parameter

Handle load tension capability:1750N

Maximum input torque:15N.m

MS324



RL

IP54

Main material and finish : ZDC handle and housing, steel cam

Application : Handle 90 degree rotation opening or closing

Remark : Default key K140



Default cam : S1B45Y07002

Performance parameter:

Maximum static load:230N

Recommended nut tightening torque:20N.m

Maximum input torque:20N.m



Cut out

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
------------	-----------------	---------	-----------	-------	-------------



RL **IP65** **3PL**

Main material and finish: Black powder coating ZDC housing and handle, white zinc plating steel cam

Application: 90 degree rotation opening or closing

Remark: Default key K140



Default cam : S1B45Y07020

Performance parameter:

Maximum static load: 270N


Recommended nut tightening torque: 20N.m

Maximum input torque: 20N.m



	MS324-2 With insert	MS324-2A Without insert
ERP	MS324Z1A140040	MS324Z1A000002

Remark: Default cam S1B4507 (square 8*8 cam optional)



Main material and finish: White zinc plated ZDC housing, shaft, and holder.

Anti-corrosive Spraying

Application: Handle 180° rotation opening or closing, stroke 25mm.

Performance parameter:

Handle load tension capability: 490N



L **IP65** **3PL**

Main material and finish: Black powder coating ZDC housing and handle, bright chrome plated lock cylinder components.



Application: Insert 180° rotation opening, handle bounces automatically and 360° rotation freely.

Remark: Default key K58-3


Performance parameter:

Maximum static load: 270N

Maximum input torque: 20N.m



Default key K58-3




Remark: default cam S1C7200


ERP **MS353Z3D000001**

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------


					MS807-1	
Seal gasket	Hinge	Door stop	Handles	Toggle and hook	R	
					L	
					IP54	
					Main material and finish :	Bright chrome plated ZDC handle,housing,insert and dust tight cap, white zinc-plated steel cam,teeth washer, and shaft
					Application :	Cam adjustable
					Remark:	Default key K050
					Default cam:	S1C45Y00003(Steel) S1C45Y00004(Stainless steel)
					Performance parameter:	
					Maximum static load:	242N
					Recommended nut tightening torque:	30N.m
					Maximum input torque:	23N.m



MS807-1




MS807-2




MS807-3


Default cam



Remark: Default cam drawing cut out is square 10mm, other cam selection refer to cam list



Cut out




Note : if it is used for 60 RH and LH, the door can be opened both right and left through housing 180 rotation assembling position, it is the dorsal view after lock is assembled on the door

Specification		MS807-1 Series			
		Bright chrome-plated ZDC housing, handle, cap		S.S housing, handle, cap	
		Model	ERP	Model	ERP
A=23 B=83 H=45~58	60° for RH and LH	MS807-1	MS807Z3A050029	MS807-1B	MS807S4A050010
	90° RH	MS807-1-Y	MS807Z3A050036		
	90° LH	MS807-1-Z	MS807Z3A050039		
A=40 B=103 H=52~75	60° for RH and LH	MS807-1-D1	MS807Z3A050002	MS807-1B-1	MS807S4A050011
	90° RH	MS807-1-Y1	MS807Z3A050005		
	90° LH	MS807-1-Z1	MS807Z3A050008		
A=63 B=103 H=75~80	60° for RH and LH	MS807-1-D2	MS807Z3A050003	MS807-1B-2	MS807S4A050012
	90° RH	MS807-1-Y2	MS807Z3A050006		
	90° LH	MS807-1-Z2	MS807Z3A050009		
Specification		MS807-2 Series			
		Bright chrome-plated ZDC housing, handle, cap		S.S housing, handle, cap	
		Model	ERP	Model	ERP
A=23 B=83 H=45~58	60° for RH and LH				
	90° RH	MS807-2-Y	MS807Z3A050011	MS807-2B-Y	MS807S4A050001
	90° LH	MS807-2-Z	MS807Z3A050010	MS807-2B-Z	MS807S4A050019
Specification		MS807-3 Series			
		Bright chrome-plated ZDC housing, handle, cap		S.S housing, handle, cap	
		Model	ERP	Model	ERP
	60° for RH and LH	MS807-3	MS807Z3A050017	MS807-3B	MS807S4A050003
	90° RH	MS807-3-Y	MS807Z3A050018	MS807-3B-Y	MS807S4A050024
	90° LH	MS807-3-Z	MS807Z3A050019	MS807-3B-Z	MS807S4A050025

MS842



Handle lock Electronic lock Accessories



Main material and finish : Black pocked coated ZDC handle and housing, white zinc-plated steel cam, stainless steel lock panel or whole stainless steel for selection

Application : Quarter-turn opening or closing, padlockable







Default cam : S1B45Y07002
S1B45Y07022

Performance parameter:


Maximum static load: 270N

Recommended nut tightening torque: 20N.m

Maximum input torque: 25N.m



Support (Accessory)



Specification	Model	ERP
ZDC	MS842	MS842Z1B000003
Stainless steel	MS842-1B	MS842S4B000001

Remark : Default cam S1B4507 (square 8*8 cam optional)

Specification	Model	ERP
Double bit	MS859-1-1	MS859Z1BT01001
Triangular 8mm	MS859-1-2	MS859Z1BT04001
Square 8x8mm	MS859-1-3	MS859Z1BT07001
Square 7x7mm	MS859-1-4	MS859Z1BT06001
Square 6x6mm	MS859-1-5	MS859Z1BT05001
Hexagon Female	MS859-1-6	MS859Z1BT09002
Slot	MS859-1-7	MS859Z1BT10001
Triangular 7mm	MS859-1-8	MS859Z1BT14001

Remark : ERP excludes cam (cut out square 8mm)

MS859



Accessories

Electronic lock

Handle lock



Main material and finish : PA handle, pocked black powder coated ZDC housing, bright chrome-plated ZDC insert, white zinc-plated steel shaft

Application : Quarter-turn opening or closing

Remark : Optional key K15 series

Default cam : S1B45Y00005(Ts=4)

Performance parameter:

Handle load tension capability: 105N

Maximum static load: 220N

Maximum input torque: 20N.m

Seal gasket

Door stop

Hinge



Panel lock

Rod control lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

MS868





Accessories
Electronic lock
Handle lock
Cylinder lock

RL **IP54** **3PL**

Main material and finish : Black powder coated ALU handle and lock panel,ZDC housing,white zinc plated steel cam
Application : Quarter-turn opening or closing, padlock available

Default cam : 2882450603

Performance parameter:
Maximum static load:270N
Maximum input torque:20N.m



ERP MS868Z1A000001

Remark : Default cam DS3B4506 (square 8*8 cam optional)

MS887-1




Door stop
Handles
Toggle and hook
Panel lock

Hinge
Seal gasket

Main material and finish : Black powder coated ZDC housing, handle, white zinc-plated steel cam


Application : Handle combines with latch

Performance parameter:
Handle load tension capability:100N



Remark : Lock driving part prepared by user

ERP MS887Z1A000001




MS887-2



Main material and finish : Blue gray (RAL7035) powder coated aluminum housing, handle, white zinc-plated steel cam

Application : Handle combines with latch

Performance parameter:
Handle load tension capability:100N



Remark : Lock driving part prepared by user



ERP MS887A1D000001

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------

MS887-3




Seal gasket	Hinge	Door stop	Handles	Panel lock	Toggle and hook	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	------------	-----------------	------------------	------------	---------------	-------------	-----------------	-------------



Main material and finish : Blue gray (RAL 7012) powder coated ZDC housing, handle and cylinder barrel
Application : Handle combines with latch, rod-latch system on sketch is just for reference, generally prepared by user


Remark : Optional K15-01C

Performance parameter:
Handle load tension capability: 1350N




ERP MS887Z1DT02001

Select K15 series as per various inserts




ERP 3290151001




ERP MS887Z1D000001

PA guider (Optional)



ERP 3438874001

Catcher (Optional)



ERP 3248874001

MS887-4




Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------

Main material and finish : Blue gray (RAL 7012) powder coated ZDC housing, and handle
Application : Handle combines with latch, rod-latch system on sketch is just for reference, generally prepared by user

Performance parameter:
Handle load tension capability: 1800N

CYLINDER LOCK SERIES





ERP MS330F3D000001

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
			MS330			MS704-2					



Main material and finish : Bright chrome-plated steel housing and insert
Application : 360 degree rotation opening or closing, with function of locking
Remark : Optional key K15-1



ERP MS704F3AT02004

MS704-1



MS704-1A



Main material and finish : Bright chrome-plated ZDC housing and steel insert






Application : 360 degree opening or closing, with function of locking

Remark : Optional key K15-1

Performance parameter:

Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m



Summary listing of instrumental lock insert for MS705 Series



Double bit 4mm pin



Double bit 3mm pin



Hooked 4mm



Triangular 8mm



Square 8mm



Square 8mm with slot



Square 6mm




Square 7mm




Socket Hexagon 10mm




Slot




Hexagon 11mm




Thorn




Flat Cylinder




Triangular 7mm




Triangular 9mm




Heptagon



Triangular 10mm with circle



Concave with slot



Hexagon female with pin

Specification	ZDC housing		Lead sealable housing		PA housing	
	Model	ERP	Model	ERP	Model	ERP
A=40 B=2.5 H=23	MS704-1/23	MS704Z3AT02001	MS704-1A/23	MS704Z3HT02004	MS704-1F/23	MS704N00T02001
A=46 B=7.5 H=28	MS704-1/28	MS704Z3AT02002	MS704-1A/28	MS704Z3HT02005	MS704-1F/28	MS704N00T02002
A=54 B=13.5 H=34	MS704-1/34	MS704Z3AT02003	MS704-1A/34	MS704Z3HT02006	MS704-1F/34	MS704N00T02003

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook


Handles

Door stop



Hinge

Seal gasket


Summary listing of instrumental lock insert for MS816-1/MS816-1A series




Remark: Hooked cam, Ra=360°, suit for push-pull type cabinet doors



Assembling sketch



Exploded view



MS705



RL IP54

Application : Insert 90 degree quarter-turn opening or closing.


**Default cam :S1B45Y07002 (ZDC)
S1B45Y07022 (SUS)**

Performance parameter:
Maximum static load:270N
Recommended nut tightening torque:20N.m
Maximum input torque:9N.m

Housing							
Accessories							
Electronic lock							
Handle lock							
Cylinder lock							
Plane lock							
Rod control lock							
Panel lock							
Toggle and hook							
Handles							
Door stop							
Hinge							
Knob							
		Housing GH=18					
Specification		ZDC housing and bright chrome insert		SUS housing and insert		Black PA housing and bright chrome ZDC insert	
		Model	ERP	Model	ERP	Model	ERP
Double bit 4mm	MS705-1	MS705Z3AT02032		MS705-1B	MS705S00T02008	MS705-1S	MS705N00T02008
Double bit 3mm	MS705-1A	MS705Z3AT01007		MS705-1AB	MS705S00T01017	MS705-1AS	MS705N00T01014
Hooked 4mm	MS705-2	MS705Z3AT03034		MS705-2B	MS705S00T03005	MS705-2S	MS705N00T03001
Triangular 8mm	MS705-3	MS705Z3AT04041		MS705-3B	MS705S00T04008	MS705-3S	MS705N00T04017
Square 8mm	MS705-4	MS705Z3AT07021		MS705-4B	MS705S00T07007	MS705-4S	MS705N00T07001
square 8mm with solt	MS705-4A	MS705Z3AT08001		MS705-4AB	MS705S00T08005	MS705-4AS	MS705N00T08001
Square 6mm	MS705-5	MS705Z3AT05008				MS705-5S	MS705N00T05007
Square 7mm	MS705-6	MS705Z3AT06010				MS705-6S	MS705N00T06002
10mm Hexagon famale	MS705-7	MS705Z3AT09025		MS705-7B	MS705S00T09003	MS705-7S	MS705N00T09001
Slot	MS705-8	MS705Z3AT10012				MS705-8S	MS705N00T10012
11mm Hexagon male	MS705-9	MS705Z3AT11008				MS705-9S	MS705N00T11002
Thorn	MS705-10	MS705Z3AT12001				MS705-10S	MS705N00T12001
Flat Cylinder	MS705-11	MS705Z3AT13001				MS705-11S	MS705N00T13001
Triangular 7mm	MS705-12	MS705Z3AT14014				MS705-12S	MS705N00T14001
Triangular 9mm	MS705-13	MS705Z3AT15009				MS705-13S	MS705N00T15001
Heptagon male	MS705-14	MS705Z3AT16001				MS705-14S	MS705N00T16001
Triangular 10mm	MS705-15	MS705Z3AT17017				MS705-15S	MS705N00T17002
Concave with solt	MS705-16	MS705Z3AT18005				MS705-16S	MS705N00T18002
Inside hexagon with pin	MS705-18	MS705Z3AT24001					
		Housing GH=28					
Specification		ZDC housing, bright chrome insert		ZDC housing, bright chrome insert		Black PA housing, bright chrome ZDC insert	
		Model	ERP	Model	ERP	Model	ERP
Double bit 4mm	MS705-2M-1	MS705Z3AT02088		MS705-3M-1	MS705Z3AT02077	MS705-3M-1S	MS705N00T03003
Double bit 3mm	MS705-2M-1A	MS705Z3AT01026		MS705-3M-1A	MS705Z3AT01027	MS705-3M-1AS	MS705N00T01003
Hooked 4mm	MS705-2M-2	MS705Z3AT03022		MS705-3M-2	MS705Z3AT03015	MS705-3M-2S	MS705N00T03005
Triangular 8mm	MS705-2M-3	MS705Z3AT04027		MS705-3M-3	MS705Z3AT04096	MS705-3M-3S	MS705N00T04018
Square 8mm	MS705-2M-4	MS705Z3AT07017		MS705-3M-4	MS705Z3AT07035	MS705-3M-4S	MS705N00T07003
square 8mm with solt	MS705-2M-4A	MS705Z3AT08002		MS705-3M-4A	MS705Z3AT08025	MS705-3M-4AS	MS705N00T08003
Square 6mm	MS705-2M-5	MS705Z3AT05011		MS705-3M-5	MS705Z3AT05003	MS705-3M-5S	MS705N00T05003
Square 7mm	MS705-2M-6	MS705Z3AT06009		MS705-3M-6	MS705Z3AT06015	MS705-3M-6S	MS705N00T06003
10mm Hexagon famale	MS705-2M-7	MS705Z3AT09026		MS705-3M-7	MS705Z3AT09027	MS705-3M-7S	MS705N00T09003
Slot	MS705-2M-8	MS705Z3AT10002		MS705-3M-8	MS705Z3AT10031	MS705-3M-8S	MS705N00T10003
11mm Hexagon male	MS705-2M-9	MS705Z3AT11010		MS705-3M-9	MS705Z3AT11003	MS705-3M-9S	MS705N00T11003
Thorn	MS705-2M-10	MS705Z3AT12002		MS705-3M-10	MS705Z3AT12003	MS705-3M-10S	MS705N00T12003
Flat Cylinder	MS705-2M-11	MS705Z3AT13002		MS705-3M-11	MS705Z3AT13003	MS705-3M-11S	MS705N00T13003
Triangular 7mm	MS705-2M-12	MS705Z3AT14002		MS705-3M-12	MS705Z3AT14003	MS705-3M-12S	MS705N00T14003
Triangular 9mm	MS705-2M-13	MS705Z3AT15002		MS705-3M-13	MS705Z3AT15003	MS705-3M-13S	MS705N00T15003
Heptagon male	MS705-2M-14	MS705Z3AT16002		MS705-3M-14	MS705Z3AT16003	MS705-3M-14S	MS705N00T16003
Triangular 10mm	MS705-2M-15	MS705Z3AT17002		MS705-3M-15	MS705Z3AT17003	MS705-3M-15S	MS705N00T17003

Housing GH=62				
Specification	ZDC housing and bright chrome insert		housing and bright chrome ZDC insert	
	Model	ERP	Model	ERP
Double bit 4mm	MS705-H62-1	MS705Z3AT02070	MS705-H62-1S	MS705N00T02004
Double bit 3mm	MS705-H62-1A	MS705Z3AT01004	MS705-H62-1AS	MS705N00T01004
Hooked 4mm	MS705-H62-2	MS705Z3AT03073	MS705-H62-2S	MS705N00T03004
Triangular 8mm	MS705-H62-3	MS705Z3AT04099	MS705-H62-3S	MS705N00T04004
Square 8mm	MS705-H62-4	MS705Z3AT07015	MS705-H62-4S	MS705N00T07004
square 8mm with solt	MS705-H62-4A	MS705Z3AT08054	MS705-H62-4AS	MS705N00T08004
Square 6mm	MS705-H62-5	MS705Z3AT05004	MS705-H62-5S	MS705N00T05004
Square 7mm	MS705-H62-6	MS705Z3AT06004	MS705-H62-6S	MS705N00T06004
10mm Hexagon famale	MS705-H62-7	MS705Z3AT09028	MS705-H62-7S	MS705N00T09004
Slot	MS705-H62-8	MS705Z3AT10032	MS705-H62-8S	MS705N00T10004
11mm Hexagon male	MS705-H62-9	MS705Z3AT11004	MS705-H62-9S	MS705N00T11004
Thorn	MS705-H62-10	MS705Z3AT12004	MS705-H62-10S	MS705N00T12004
Flat Cylinder	MS705-H62-11	MS705Z3AT13004	MS705-H62-11S	MS705N00T13004
Triangular 7mm	MS705-H62-12	MS705Z3AT14004	MS705-H62-12S	MS705N00T14004
Triangular 9mm	MS705-H62-13	MS705Z3AT15004	MS705-H62-13S	MS705N00T15004
Heptagon male	MS705-H62-14	MS705Z3AT16004	MS705-H62-14S	MS705N00T16004
Triangular 10mm	MS705-H62-15	MS705Z3AT17004	MS705-H62-15S	MS705N00T17004
Concave with solt	MS705-H62-16	MS705Z3AT18004	MS705-H62-16S	MS705N00T18004

Remark: For ERP no. above, default cam S1B4507 (cutout 8x8)



HP001 Handle pull (Optional)

Technical drawing of HP001 Handle pull showing a 3D view and two cross-sectional views. The top view shows a handle pull with a central hole and a flange. The side view shows dimensions: height 32, width 19, thickness 2, and a semi-circular cutout of radius R_{d_1} . The front view shows a stepped profile with a total width of 28, a shoulder height of 16, and a base width of 17.

WP002 Water-proof cap (Optional)

Technical drawing of WP002 Water-proof cap showing a 3D view and two cross-sectional views. The top view shows a cap with a flange and a central hole. The side view shows a stepped profile with a total width of 27.8, a shoulder width of 28.4, and a height of 7. The front view shows a stepped profile with a total width of 52, a shoulder width of 23, and a height of 15.

A3001 Stainless steel lock tube (Optional)

Technical drawing of A3001 Stainless steel lock tube showing a 3D view and two cross-sectional views. The top view shows a lock tube with a central hole. The side view shows a stepped profile with a total height of 16.5 and a shoulder height of 25. The front view shows a stepped profile with an outer diameter of 37.5, an inner hole diameter of 22.5, and a shoulder diameter of 20.1.

A3002 Carbon steel seat cover (Optional)

Technical drawing of A3002 Carbon steel seat cover showing a 3D view and two cross-sectional views. The top view shows a seat cover with a central hole. The side view shows a stepped profile with a total height of 32 and a shoulder height of 1.2. The front view shows a stepped profile with an outer diameter of 48, an inner hole diameter of 22.5, and a shoulder diameter of 35.3.

MS705-K01

MS705-K02

Cut out

Specification	Model	ERP
Handles	MS705-K01	MS705Z1F000015
Double bit	MS705-K02	MS705Z1FT01001

Remark: Default cam DS1B32N04, T=4

Handle

Cam

Insert

cam

handle

housing

insert

cam

Cut out

ERP

MS705Z2AT20003

MS705-K		Accessories
 RL	 IP54	Electronic lock
Main material and finish : Green powder coated ZDC handle,housing and insert,white zinc-plated steel cam Application: Quarter-turn opening or closing Remark : Optional key K15-01C		Cylinder lock
Default cam : S1B32N04002		Plane lock
Performance parameter: maximum static load: 210N recommended nut tightening torque: 20N.m maximum input torque: 15N.m		Rod control lock
MS705-Q		Panel lock
 RL	 IP54	Toggle and hook
Main material and finish : Black painted ZDC housing,Bright chrome plated insert,white zinc-plated cam and screw. Remark: Default key K15-1		Handles
Performance parameter: maximum static load: 270N recommended nut tightening torque: 20N.m maximum input torque: 9N.m		Door stop
		Hinge
		Seal gasket

MS705-1W-2D



R L

Main material and finish: Bright chrome ZDC housing, insert and cam

Application: Quarter turn opening or closing, auto locking function





Remark: Optional key K15 series

Performance parameter:

Maximum static load: 270N

Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m



	MS705-1W-2D Left hand cam	MS705-1W-2D Right hand cam
ERP	MS705Z3AT02020	MS705Z3AT02018

MS705-3C



RL

Main material and finish : Sand-spray, and bright chrome-plated ZDC housing, white zinc-plated steel cam

Application : Quarter-turn opening or closing





Default cam : S1B45Y02002

Performance parameter:

Maximum static load: 270N

Recommended nut tightening torque: 20N.m

Maximum input torque: 6N.m



Specification	Model	ERP
Slot	MS705-3C-1	MS705Z1B000002
Square 7x7	MS705-3C-2	MS705Z3HT06001

Remark: default cam S1B4502 (Cut out 8x8 cam)

ERP	Model	Insert range	Optional key
MS705Z3HT02009	MS705-3A-1	Double bit 4mm	K15-1/K15-1F/K15-1A
MS705Z3HT01008	MS705-3A-1A	Double bit 3mm	K15-1/K15-1F/K15-1A
MS705Z3HT03008	MS705-3A-2	Hooked 4mm	K15-1
MS705Z3HT04010	MS705-3A-3	Triangular 8mm	K15-3/K15-3F
MS705Z3HT07007	MS705-3A-4	Square 8mm	K15-4/K15-4F
MS705Z3HT08005	MS705-3A-4A	square 8mm with solt	K15-4/K15-4F
MS705Z3HT05005	MS705-3A-5	Square 6mm	K15-5/K15-5F/K15-5A
MS705Z3HT06005	MS705-3A-6	Square 7mm	K15-6/K15-6F
MS705Z3HT09001	MS705-3A-7	10mm Hexagon famale	K15-7/K15-7F
MS705Z3HT10007	MS705-3A-8	Slot	
MS705Z3HT11005	MS705-3A-9	11mm Hexagon male	K15-9/K15-9F
MS705Z3HT12005	MS705-3A-10	Thorn	K15-10
MS705Z3HT13005	MS705-3A-11	Flat Cylinder	K15-11
MS705Z3HT14007	MS705-3A-12	Triangular 7mm	K15-3/K15-3F
MS705Z3HT15005	MS705-3A-13	Triangular 9mm	
MS705Z3HT16005	MS705-3A-14	Heptagon male	
MS705Z3HT17005	MS705-3A-15	Triangular 10mm	
MS705Z3HT18005	MS705-3A-16	Concave with solt	

Remark: For ERP no. above, default cam S1B4507 (cut out 8x8)

MS705-3A



RL

Main material and finish : Sand-spray and bright chrome-plated ZDC housing, insert and dust-proof cap, white zinc-plated steel cam

Application : Quarter-turn opening or closing

Remark: Optional key K15 series

Default cam : S1B45Y07002

Performance parameter:

Maximum static load: 270N

Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket



RL

Main material and finish: Bright chrome ZDC housing, black powder coated handle
Application : Quarter-turn opening or closing






Default cam : S1V45Y08001

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:9N.m



ERP MS705Z3A000009

Remark : Default cam S1V4508

Specification	Model	ERP
ZDC housing,insert(RH-rotation)	MS705-3E	MS705Z1A140026
ZDC housing,insert(LH-rotation)	MS705-3E-2	MS705Z3A140011
PA housing,insert(RH-rotation)	MS705-3E-F	MS705N00140007

Default cam: S1B4507 T=4 (cut out 8x8)



RL

Main material and finish : Black powder coated ZDC housing, white zinc-plated steel cam

Application : Quarter-turn opening or closing

Remark: Default key K140

Performance parameter:

Maximum static load:220N

Recommended nut tightening torque:20N.m



RL IP54

Main material and and finish : Black powder coated ZDC housing and insert, white zinc-plated steel cam

Application : Quarter-turn opening or closing







Remark : Optional key K15-1A

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:9N.m



ERP	MS705-3J-1B	MS705-3J-2B	MS705-3J-3B
MS705S4AT09001	MS705S4AT32004	MS705S4AT32003	

Remark:Default cam S1B4507,T=4 (Optional cam8x8)



IP55

Main material and finish : Stainless steel housing,insert,nut,screw,cam.

Application:Quarter-turn opening or closing

Remark: Optional three types of insert.

ERP of Cam:S1B45Y07002

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:9N.m

Electronic lock

Handle lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Accessories

Cylinder lock

Plane lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

MS705-3U



RL **IP54**

Main material and finish : Black powder coated ZDC housing, or black PA housing, white zinc-plated steel cam
Application : Quarter-turn opening or closing


Default cam : S1B45Y07002

Performance parameter:

Maximum static load: 220N

Recommended nut tightening torque: 20N.m

Maximum input torque: 20N.m



Specification	ZDC housing and handle		PA housing, ZDC handle	
	Model	ERP	Model	ERP
GH=18	MS705-3U-1	MS705Z1A000028	MS705-3U-1F	MS705N00000009
GH=28	MS705-3U-2	MS705Z1A000047	MS705-3U-2F	MS705N00000008
GH=36	MS705-3U-3	MS705Z1A000048	MS705-3U-3F	MS705N00000007
GH=62	MS705-3U-4	MS705Z1A000049	MS705-3U-4F	MS705N00000010

Remark : Default cam S1B4507 (cut out 8x8)

MS705-8G



IP55

Material: ZDC housing, insert, nut and steel cam.

Finish: bright chrome housing and insert; white plated cam.

Construction: Quarter turn opening or closing


Default cam : S1B45Y00002

Performance parameter:

Maximum static load: 270N


Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m



ERP **MS705Z3AT10030**

Remark: Default cam S1B4500 (Cutout 8x8)



ERP **MS705Z2AT24005**

MS705-24G



IP54

Main material and finish : Black painted ZDC housing, insert, nut, black zinc plated steel cam

Application: Quarter-turn opening or closing, with damping.


Performance parameter:

Maximum static load: 270N

Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m

New product, Please consult technical department when ordering.



ERP **MS705S00T13001**

MS705-27



NEW

IP65

Main material and finish : Stainless steel 316 housing, insert, cam, screw. Cam electrolysis

Application: Quarter-turn opening or closing
Remark: Cam is optional.

Performance parameter:

Insert rotation torque: 0.5N.m-2.5N.m

Cam load capability: 300N.

Maximum input torque: 9N.m

Recommended nut tightening torque: 20N.m

Accessories	Electronic lock	Handle lock	Cylinder lock
Plane lock	Rod control lock	Plane lock	Rod lock

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
Plane lock	Rod control lock	Plane lock	Rod lock	Hinge	Seal gasket

MS706



Handle lock Electronic lock Accessories

Main material and finish: Bright chrome plated ZDC housing and insert, white zinc plated steel cam

Application: Cam 180 degree rotation to open or lock




Remark: Default key K130

Default cam : S1B33Y06002


Performance parameter:

Maximum static load: 100N

Recommended nut tightening torque: 20N.m



WP003



HP002





HP003





DP001

Model	ERP
MS706-1	MS706Z3A130001
MS706-2	MS706Z3A130012
MS706-3	MS706Z3A130004


Remark : Default cam S1B3306



MS714-1 Series



MS714-2 Series



Specification	Knob			
	black powder coated ZDC housing, PA handle		PA housing and handle	
Model	ERP	Model	ERP	
GH=18	MS714-1-1	MS714Z1A0000020	MS714-1A-1	MS714N00000001
GH=28	MS714-1-2	MS714Z1A000002	MS714-1A-2	MS714N00000002
GH=36	MS714-1-3	MS714Z1A000003	MS714-1A-3	MS714N00000003
GH=62	MS714-1-4	MS714Z1A000004	MS714-1A-4	MS714N00000004

Specification	Handle			
	black powder coated ZDC housing, PA handle		PA housing and handle	
Model	ERP	Model	ERP	
GH=18	MS714-2-1	MS714Z1A000040	MS714-2A-1	MS714N00000014
GH=28	MS714-2-2	MS714Z1A000053	MS714-2A-2	MS714N00000006
GH=36	MS714-2-3	MS714Z1A000054	MS714-2A-3	MS714N00000007
GH=62	MS714-2-4	MS714Z1A000008	MS714-2A-4	MS714N00000008

Remark: Default cam S1B4507 (cut out 8x8)

MS714-1



MS714-2



RL IP54

Main material and finish : Black powder coated ZDC housing or PA housing, PA handle, white zinc plated steel cam

Application : Quarter-turn opening or closing

MS714-2 Performance parameter:

Maximum static load: 220N

Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Handle lock Electronic lock Accessories

Hinge Handles Panel lock Toggle and hook Handles

Seal gasket

MS714-3



RL IP54

Main material and finish : Pocked black powder coated ZDC housing and handle, white zinc-plated steel cam

Application : Handle 90 degree quarter-turn opening or closing


Default cam : S1B45Y07005

Performance parameter:

Maximum static load:250N

Recommended nut tightening torque:20N.m

Maximum input torque:18N.m



ERP MS714Z1B000007

Remark: Default cam S1B4507, T=4 (cut out 8x8)

MS714-4



RL IP54

Main material and finish : Pocked black powder coated ZDC housing,PA handle, white zinc-plated steel cam

Application : Handle 90 degree quarter-turn opening or closing


Default cam : S1B45Y07005

Performance parameter:

Maximum static load:250N

Recommended nut tightening torque:20N.m



Maximum input torque:18N.m



ERP S1B30Y40001

Specification	ZDC housing, PA handle		PA housing and handle	
	Model	ERP	Model	ERP
GH=18	MS714-4-1	MS714Z1A000061	MS714-4A-1	MS714N00000009
GH=28	MS714-4-2	MS714Z1A000013	MS714-4A-2	MS714N00000010
GH=36	MS714-4-3	MS714Z1A000014	MS714-4A-3	MS714N00000011
GH=62	MS714-4-4	MS714Z1A000015	MS714-4A-4	MS714N00000012

Remark : Default cam S1B4507, T=4 (cut out 8x8)



Specification	ZDC housing, bright chrome handle	PA housing and ZDC handle
GH=18	MS715Z3A000001	MS715N00000001
GH=28	MS715Z3A000002	MS715N00000002
GH=36	MS715Z3A000003	MS715N00000003
GH=62	MS715Z3A000004	MS715N00000004

Remark: Default cam S1B4507, T=4 (cut out 8x8)

MS715



RL IP54

Main material and finish : Bright chrome-plated ZDC housing or PA housing, bright chrome plated ZDC handle, white zinc-plated steel cam

Application : Handle 90 degree quarter-turn opening or closing



Default cam : S1B45Y07002

Performance parameter:


Maximum static load:220N

Recommended nut tightening torque:20N.m

Maximum input torque:11N.m



HP001 Handle pull
(Optional)



WP002 Water-proof
cap (Optional)

MS721



Main material and finish: Bright chrome-plated ZDC housing and insert, steel cam

Application : Handle 120 degree quarter-turn opening or closing

Default cam : S1W51Y00001

Performance parameter:

Maximum static load:220N

Recommended nut tightening torque:20N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



MS722

RL **IP54**

Main material and finish: Bright chrome-plated ZDC housing, white zinc-plated steel cam and insert

Application : Quarter-turn opening or closing



Remark : Optional key K15-1

Default cam : S1B45Y07002

Performance parameter:





Maximum static load:220N

Recommended nut tightening torque:20N.m



ERP **MS722Z3AT01009**

Remark: Default cam S1B4507,T=4 (cut out 8x8)



ERP **MS733Z3A430009**

Remark : Default cam S1B3300

MS733

RL

Main material and finish: Bright chrome-plated ZDC housing and insert, white zinc-plated steel cam

Application: Quarter-turn opening or closing

Remark: Default key K430

Default cam : S1B33Y00005

Performance parameter:

Maximum static load:220N

Recommended nut tightening torque:20N.m



MS729-1 MS729-2 MS729-3

RL

Main material and finish: Bright chrome plated ZDC housing and insert, white zinc plated steel cam

Application: Quarter-turn opening or closing




Remark: Default key K420

Default cam : S1B40Y00001

Performance parameter:




Maximum static load:150N

Recommended nut tightening torque:20N.m



ERP **MS729Z3A420022** **MS729Z3A420002** **MS729Z3A420017**

Remark : Default cam S1B4000



ERP **MS734Z3AT12001**

Remark : Default cam S1B4500 (cut out 8x8)

MS734

RL

Main material and finish : Bright chrome-plated ZDC housing and insert, white zinc-plated steel cam

Application : Quarter-turn opening or closing, with function of locking

Remark : Optional key K15-10


Default cam : S1B45Y00002

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:8N.m




Accessories	Electronic lock	Handle lock	Cylinder lock

Plane lock	Rod control lock	Plane lock	Rod control lock

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket


--	--	--	--

	Door stop	Hinges	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
MS735											
 											
Main material and finish : White zinc-plated steel lock body.											
Application : Quarter-turn opening or closing, with function of locking											
Default cam : S1S35Y00001											
Performance parameter: Maximum static load: 160N Maximum input torque: 11N.m											
						ERP MS735F3D000002					
						Remark : Default cam S1S3500					




	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
MS735-4												
  												
Main material and finish: White zinc-plated steel lock body												
Application: Quarter-turn opening or closing, cam adjustable												
Default cam : S1S25Y11001												
Performance parameter: Maximum static load: 280N												

Example of assembling



	Door stop	Hinges	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
MS735-2											
 											
Main material and finish : Trivalent zinc-plated steel lock body.											
Application : Quarter-turn opening or closing											
Default cam : S1S25Y00001											
Performance parameter: Maximum static load: 160N Maximum input torque: 11N.m											
						ERP MS735F3E000001					
						Remark : Default cam S1S2500					



	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
MS735-4												
  												
Main material and finish: White zinc-plated steel lock body												
Application: Quarter-turn opening or closing, cam adjustable												
Default cam : S1S25Y11001												
Performance parameter: Maximum static load: 280N												

MS741



Handle lock Electronic lock Accessories

R

Main material and finish: Bright chrome-plated ZDC housing and insert, white zinc plated steel cam

Application: Quarter-turn opening or closing, with function of locking automatically




Remark: Default key K160

Default cam : S1C32Y04001

Performance parameter:

Maximum static load: 140N

Recommended nut tightening torque: 20N.m



ERP MS741Z3A160001

Remark : Default cam S1C3204

MS742



Panel lock

Toggle and hook

Handles

Door stop

R **L**

Main material and finish: White zinc-plated steel housing cam and shaft , PA cap



Application: Quarter-turn opening or closing

Default cam : S1K45Y00001


Performance parameter:

Maximum static load: 140N

Maximum input torque: 4N.m






Exploded view



Specification	Model	ERP
Close from left rotation	MS742-Z	MS742F3D000001
Close from right rotation	MS742-Y	MS742F3D000002

Remark : Default cam S1K4500



ERP MS743Z3A282001

Remark : Default cam S1B3000 (cut out 8x8)

MS743



IP40

Main material and finish: Bright chrome-plated ZDC housing, white zinc-plated steel cam

Application: Quarter-turn opening or closing




Remark: Default key K282

Default cam : S1B30Y00006

Performance parameter:

Maximum static load: 140N

Recommended nut tightening torque: 20N.m



ERP MS744Z3D160002

Remark : Default cam S1B2000 (cut out 8x8)

MS744



RL IP40

Main material and finish: White zinc-plated ZDC housing and steel cam

Application: Quarter-turn opening or closing

Remark: Default key K160

Default cam : S1B20Y00001

Performance parameter:

Maximum static load: 130N

Recommended nut tightening torque: 20N.m

MS744-3




IP54

Main material and finish: ZDC housing, insert, white zinc plated steel cam
Application: Quarter-turn opening or closing
Remark: Default key K28-5

Performance parameter:

Maximum static load: 140N

Recommended nut tightening torque: 20N.m



ERP

MS744Z3A280001

MS745-1



MS745-2

RL IP40

Main material and finish: Bright chrome-plated ZDC housing, white zinc-plated steel cam

Application: Quarter-turn opening or closing

Remark: Default key K080


Default cam : S1B33Y00005

Performance parameter:

Maximum static load: 160N




Recommended nut tightening torque: 20N.m

Maximum input torque: 40N.m(Rotation type)



Specification	Model	ERP
With insert	MS745-1	MS745Z3A080001
Knob	MS745-2	MS745Z3A000001

Remark : Default cam S1B3300



MS745-4



IP54



Main material and finish: PA housing and nut, Wire-drawing polishing stainless steel insert, check ring, screw
Application: Inner with positioning structure, 90° rotation, with damping.
Remark: Default key K170

Performance parameter:

Maximum static load : 100N

Recommended nut tightening torque: 20N.m

ERP	With insert	Without insert
	MS745N00T10001	MS745N00T10002



MS746-2



Material and finish: Pocked black powder coated ZDC housing and insert, white zinc plated steel cam

Remark: Default key K40

Performance parameter:

Maximum static load: 140N

Recommended nut tightening torque: 20N.m

ERP	MS746Z1B400001
-----	----------------

MS748



RL **IP54**

Main material and finish: Black powder-coated ZDC housing, handle and insert, white zinc plated steel cam

Application: Quarter-turn opening or closing

Remark: Default key K160




Default cam : S1B45Y07002

Performance parameter:

Maximum static load:270N



Recommended nut tightening torque:20N.m

Maximum input torque:30N.m



Black powder coated housing		Bright chrome-plated housing	
Model	ERP	Model	ERP
MS748-1	MS748Z1A040005	MS748-1	MS748Z3A160009
MS748-2	MS748Z1A160011	MS748-2	MS748Z3A160002

Remark : Default cam:S1B4500 (cut out 8x8)



ERP **MS748Z2C160001**

MS748-3B



Main material and finish:Pocked black powder coated ZDC housing, insert, handle, stainless steel cam(Passivation +electrophoresis paint).

Application:Quarter-turn opening or closing

Remark:Default insert L1C0160,Key K16

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:30N.m

MS748-3/3A



IP65

Main material and finish: Pocked black powder coated ZDC housing,PA handle,White zinc plated steel cam.

Application:quarter-turn opening or closing

Remark:Default key K190





Default cam : S1B45Y07019(Default)

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m



Maximum input torque:30N.m



MS748-3


MS748-3A

Remark:Default cam DS1B4507 T=4 (Optional cam 8x8)



MS748-4A

MS748-4



Cut out

MS748-4



Main material and finish:Black painted ZDC housing,handle,white zinc plated nut.

Application:Without insert,quarter-turn opening or closing.Automatic return after release.

Remark:Default key K190

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:30N.m

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Electronic lock
Accessories

Cylinder lock
Plane lock

Rod control lock

Panel lock
Toggle and hook

Handles
Door stop

Seal gasket
Hinge

Seal gasket


MS753



Cylinder lock

Main material and finish: Black PC housing, insert, shaft pipe and lock tongue
Application: Automatic locked push type
Remark: Default key K160


Performance parameter:
Maximum static load: 240N



ERP

MS753N00160001


Catcher (Optional)



ERP



3658250001

Handle pull (Optional)



ERP

1150050002



MS754




IP54

Main material and finish: Bright chrome-plated ZDC housing, white zinc-plated ZDC insert and steel cam
Application: Automatic locked quarter-turn to open or close
Remark: Optional key K15-12F

Default cam : S1B45Y02005

Performance parameter:
Maximum static load: 270N
Recommended nut tightening torque: 20N.m
Maximum input torque: 10N.m

Optional key



ERP

3290153005

Accessories	Electronic lock	Handle lock	Cylinder lock
Hinge	Handles	Door stop	Toggle and hook

MS755



Handle lock Electronic lock Accessories

Main material and finish: Pocked black powder coated ZDC handle,housing,Color-zinc plated steel cam


Application:Quarter-turn opening or closing

Performance parameter:

Maximum static load:200N

Recommended nut tightening torque:20N.m

Maximum input torque:9N.m



Item	H	L	Cam ERP	ERP
2	36	32	S1A32Y12001	MS755Z1BT01001
1	43	34	S1A34Y19001	MS755Z1BT01004

MS756



RL IP54

Main material and finish: Bright chrome plated ZDC housing,insert and cam

Application:Insert rotated 270° to open.


Remark:Optional key K15 series,Cam can be installed opposite.

Performance parameter:




Maximum static load:300N

Recommended nut tightening torque:20N.m

Maximum input torque:9N.m



Model	ERP
MS756-H40	MS756Z3AT06006
MS756-H50	MS756Z3AT06007



ERP MS758Z3AE04001

MS758



RL

Main material and finish: Bright chrome plated ZDC housing,cover plate,insert,nut and key Stainless steel marble,cam and screw.


Remark:Three types key,A,B,C

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:9N.m



ERP MS758Z3AT04001

MS758-2



RL

Main material and finish:Bright chrome plated ZDC housing,insert,cover plate,Passivated stainless steel cam

Application:Quarter-turn opening or closing

Remark:8mm triangle insert can fit tool type key

Performance parameter:

Maximum static load:270N

Recommended nut tightening torque:20N.m

Maximum input torque:9N.m

Seal gasket



MS760

Accessories
Electronic lock

Handle lock
Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge
Seal gasket

RL IP54

Main material and finish: Bright chrome-plated ZDC housing and insert, white zinc-plated steel cam

Application: Quarter-turn opening or closing





Remark: Default key K160

Default cam : S1V33N02001

Performance parameter:

Maximum static load:230N





Recommended nut tightening torque:20N.m



Change the fitting direction of position device to suit RH or LH application

ERP MS760Z3A160001

Remark : Default cam S1V33N02



MS762


Accessories
Electronic lock

Handle lock
Cylinder lock

Default cam : S1B45Y07002

Performance parameter:
Maximum static load:270N

MS761



RL

Main material and finish : Bright chrome-plated ZDC housing and steel insert, white zinc-plated steel cam

Application : Quarter-turn opening or closing, with function of locking

Remark : Optional key K15-04A







Default cam : S1B29Y00005

Performance parameter:

Maximum static load:92N

Recommended nut tightening torque:20N.m

Maximum input torque:6N.m



IP55

Material and finish: Plastic housing, insert and nut

Application: Quarter turn opening or closing

Performance parameter:
Maximum static load:80N

Accessories
Electronic lock

Handle lock
Cylinder lock

Plane lock
Rod lock

Panel lock
Toggle and hook

Handles

Door stop

Hinge
Seal gasket

MS769-1



Accessories
Electronic lock

MS769-2



Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook


Hinges

Door stop


Handles

Seal gasket


MS769-1




MS769-1



MS769-2



MS769-2






IP55

Material and finish: White zinc plated ZDC housing, cam and steel screw, stainless steel insert, ZDC plastic-covered handle

Default cam : S1B30Y00004

Performance parameter:
Maximum static load: 270N







Cam can be reversely installed,
and rotating angel exceeds 90°

ERP

MS769-1

MS769-2

Remarks: Default cam S1B3000



ERP

MS772Z1D000001

Remark: Default cam S1B4502 T=4 (cut out 8x8)

MS772



RL IP54



Main material and finish: Blue gray powder coated (RAL 7012) ZDC housing, PA handle, white zinc-plated steel cam
Application: 90 degree quarter-turn opening or closing

Default cam : S1B45Y02015

Performance parameter:

Maximum static load: 970N

Recommended nut tightening torque: 20N.m



ERP

MS773Z2AT01001

Remark : Default cam DS1B4504, T=4 (cut out 8x8)

MS773



RL IP55

Main material and finish: Bright chrome plated ZDC housing, dust-proof cap and insert; white zinc plated ZDC nuts, white zinc plated steel cam and screw.

Remark: Default key K15 double bit key

Default cam : S1B45Y04008

Performance parameter:

Maximum static load: 270N

Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

MS773-3



IP55

Main material and finish: Bright chrome plated ZDC housing cap and key; White zinc plated steel cam and insert.


Application: Press cap, rotated insert to open or close.

Performance parameter:

Maximum static load: 200N


Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m



ERP

MS773Z3AT07001



ERP

MS773Z3AT04002

MS773-4



IP55

Main material and finish: Bright chrome plated ZDC housing, insert and cap, white zinc plated ZDC nuts, White zinc plated steel cam.


Application: Press cap, rotated insert 90° to open or close.

Performance parameter:

Maximum static load: 270N


Recommended nut tightening torque: 20N.m

Maximum input torque: 9N.m



ERP

MS773Z3AT03001



ERP

MS775N00024001

Remark : Default cam S1B4000

MS773-5



NEW

Main material and finish: Bright chrome plated ZDC housing, white-zinc plated steel cam.

Application: Insert quarter-turn to open or close

Remark: Default key K15

Default cam: S1B45Y04027

Performance parameter:

Maximum static load: ≤270N

Recommended nut tightening torque: 20N.m

MS775-2



RL IP55

Main material and finish: Plastic housing and inset; white zinc plated ZDC nut, steel cam and screw; mirror polished stainless steel housing cap and inset cap

Remark: Default key K024

Default cam : S1B40Y00003

Performance Parameter:

Maximum static load: 180N



MS779



Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock



Toggle and hook

Handles


Door stop

Hinge

Seal gasket



Note: Only applies to wood, soft door plank.






Clockwise rotate 180°

ERP MS779Z3G501001

Remark: default cam S1A2500



Default key K50



Optional key

ERP MS786Z2A540002

K540



MS786



Main material and finish : White zinc-plated steel lock body, ABS plastic cover
Application : Quarter-turn opening or closing

Remark : Optional key K15-1

Default cam : S1B45Y17002

Performance parameter:
Maximum static load: 220N






Handle

Toggle and hook



Panel lock

Door stop



ERP MS784Z3D000002

Remarks: Default cam S1H4819



ERP MS801F3CT01003
 Remark : Default cam DS1B4517 (cut out 8x8)

MS801-1



Handle lock Electronic lock Accessories

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Performance parameter:

Maximum static load:139N

Recommended nut tightening torque:4N.m

Maximum input torque:7N.m



Main material and finish : White zinc-plated steel lock body, ABS plastic cover

Application : Insert quarter-turn rotation combines with cam and rod latch

Remark : Optional key K15-1

Default cam : S1B45Y23001

Performance parameter:

Maximum static load:270N

ERP

MS801F3DT02003

Remark : Default cam S1B4523 (cut out 8x8)

$\phi 8$

16.5mm

102

102

105.5

120

102

16.5mm

21.5

18

Door

Weld

Cam

Insert

25

18

Cam

Insert

Weld

Cam



MS804

		Handle lock	Electronic lock	Accessories
Cylinder lock				
Plane lock				
Rod control lock				

Main material and finish: Bright chrome-plated ZDC housing and insert, white zinc-plated steel cam

Application: Quarter-turn opening or closing




Remark: Default key K050

Default cam : S1B45Y02001 (Ts=2)

Performance parameter:




Maximum static load: 100N

Recommended nut tightening torque: 20N.m



ERP MS804Z3A050008

Remark : Default cam S1B4502 (cut out 8x8)



ERP MS806Z3A220011

Remark : Default cam S1G2900



MS806

Accessories	Electronic lock	Handle lock	Cylinder lock
Plane lock			
Rod lock			



MS809

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
Panel lock					
Toggle and hook					
Handles					



MS805

		Handles	Toggle and hook	Panel lock
Door stop				
Hinge				
Seal gasket				

RL

Main material and finish : Black powder coated ZDC housing and insert, white zinc-plated steel cam

Application : 180 degree rotation opening or closing

Remark : Default key K040




Default cam : S1B36Y02001

Performance parameter:

Maximum static load: 270N

Recommended nut tightening torque: 20N.m

Maximum input torque: 20N.m






HP001 Handle pull (Optional)



WP002 Water-proof cap (Optional)

ERP MS805Z2A040005

Remark : Default cam S1B3602, T=2 (Cut out 8x8)



ERP MS809Z3A230006

Remark : Default cam S1B4000



MS811-1

MS811-2

RL


Main material and finish : Bright chrome-plated steel housing and handle, white zinc-plated steel cam

Application : Quarter-turn opening or closing

Default cam : S1W19Y00002


Performance parameter:

Maximum static load: 140N




MS811-1

MS811-2



Cut out



	MS811-4-Z (Left)	MS811-4-Y (Right)
ERP	MS811Z3D000008	MS811Z3D000001

Remark : Default cam S1S2500



Tighten

R

L

Main material and finish : White zinc-plated ZDC housing, white zinc-plated steel cam and shaft

Application : Quarter-turn opening or closing, with function of locking

Default cam : S1S25Y00002

Performance parameter:

Maximum static load: 210N

Recommended nut tightening torque: 20N.m

Maximum input torque: 11N.m



RL IP54

Main material and finish : Bright chrome-plated ZDC housing and insert, white zinc-plated steel cam

Application : 70 degree rotation opening or closing

Remark : Key the same as MS812-2


Default cam : S3C86Y00002

Performance parameter:

Maximum static load: 110N

Recommended nut tightening torque: 20N.m

Maximum input torque: 11N.m



MS811-3



Tighten

R

L



Main material and finish : Trivalent zinc-plated steel housing, handle and cam

Application : Handle 360 degree rotation, with function of locking



Default cam : S1S13Y00001

Performance parameter:


Maximum static load: 180N



Cut out



Cut out



Remark : Housing rotate 180°for installing. the picture shows the product and panel after installing



MS812-2







RL **IP54**

Main material and finish: Bright chrome plated ZDC housing and cap, white zinc plated steel cam.

Application: Quarter turn opening or closing

Default cam : S1B72Y00001

Performance parameter:
Maximum static load: 240N



Remark: change direction device and cam to realize left or right opening

ERP MS812Z2B000003

Remark : Default cam S1B7200 (cut out 8x8)

MS813-4



RL **IP54**




Main material and finish: Yellow gray powder coated ZDC housing, bright chrome plated insert, white zinc plated steel cam.

Application: Quarter turn opening or closing

Remark: Optional key K15-1




Default cam : S1A44Y06001

Performance parameter:
Maximum static load: 580N



ERP MS813Z1ET01006

Remark : Default cam S1A4406



MS813



MS813-B



RL **IP54**

Main material and finish : Yellow-gray ZDC housing,bright chrome-plated ZDC insert, white zinc-plated ZDC cam

Application : Quarter-turn opening or closing

Remark : Optional key K15-1

Performance parameter:
Maximum static load: 580N

Specification	Model	ERP
ZDC	MS813	MS813Z1ET01003
Full S.S.	MS813-B	MS813S4AT01002



MS813-5B

RL **IP54**


Main material and finish: Mirror polishing stainless steel housing, insert, ZDC cam, screw and steel support

Remark: Optional key K15 series

Default cam : S1A44Y06001


Performance parameter:

Maximum static load: 580N



ERP MS813S4AT01001

Remark : Default cam S1A4406




MS815-2

IP54

Main material and finish: Black painted ZDC housing and handle, white zinc plated steel cam

Application: Quarter turn opening or closing

Remark: Default key K170



ERP MS815Z2A170002

Remark : Default cam S1V2400



MS815-1

IP54

Main material and finish: Black painted ZDC housing and handle, white zinc plated steel cam

Application: Quarter turn opening or closing


Remark: Default key K240

Default cam : S1B26Y00001

Performance parameter:


Maximum static load: 100N

Recommended nut tightening torque: 12N.m



ERP MS815Z2A240001

Remark : Default cam S1B2600 (cut out 8x8)



MS815-3A(Model A)

MS815-3B(Model B)

Specification	Model	ERP	
		Painted (mat black) housing	Bright chrome-plated housing
Model A	MS815-3A	MS815Z1A170003	MS815Z3A170003
Model B	MS815-3B	MS815Z1A170004	MS815Z3A170004

Remark: Cam cut out Ø 7*5.5



Main material and finish: ZDC housing, insert and steel cam

Application: Quarter-turn opening or closing

Remark: Default key K170

**Default cam : S1W20Y00001 (Model A)
S1W19Y00001 (Model B)**

Performance parameter:

Maximum static load: 250N

Recommended nut tightening torque: 20N.m

Accessories	Electronic lock	Handle lock	Cylinder lock
Plane lock	Rod control lock	Rod lock	Panel lock

Panel lock	Toggle and hook	Handles	Door stop
Hinge			Hinge

Seal gasket

MS816-2



Main material and finish : Blue-gray powder coated ZDC housing and insert, white zinc-plated steel cam, PA handle pull

Application: Cam quarter-turn to open or close, with function of locking

Remark: Optional key K15 series




Default cam : S1K35Y00002 (Ts=4)

Performance parameter:

Maximum static load: 360N

Recommended nut tightening torque: 20N.m

Maximum input torque: 11N.m



WP001 water-proof cap (Optional)






Remark : Inserts sketch refers to inserts list 2 on P058


ERP	Model	Insert	Optional key
MS816Z1DT25004	MS816-2-1	10mm Hexagon	K15-9、K15-9F
MS816Z1DT04004	MS816-2-2	8mm Triangle	K15-3、K15-3F
MS816Z1DT07004	MS816-2-3	8mm Square	K15-4、K15-4F
MS816Z1DT06004	MS816-2-4	7mm Square	K15-6、K15-6F
MS816Z1DT26004	MS816-2-5	9mm Square	
MS816Z1DT14004	MS816-2-6	7mm Triangle	K15-3、K15-3F

Remark : Default cam S1K3500 (cut out Ø8x6.5)



WP004(Optional)



Cam(Optional)



key(Optional)




Remark: Please refer to cam list on P009

Specification	Model	ERP	Optional key
Handle	MS816-3S-1	MS816Z2A000028	
6mm Square	MS816-3S-2	MS816Z2AT05001	K15-5A
Abnormal	MS816-3S-3	MS816Z1AT21002	K370
Slot	MS816-3S-4	MS816Z1AT18006	

Remark: Default cam S1G23N08 (Cutout Ø6x4.7)

MS816-3S-1



Main material and finish: Black painted ZDC housing, insert and handle, white zinc-plated steel cam, PA water-proof cap

Application: Cam Quarter-turn to open or close, with function of locking

Default cam : S1G23N08005

Performance parameter:

Maximum static load: 360N

Recommended nut tightening torque: 20N.m

Maximum input torque: 8N.m

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Seal gasket	Hinge	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Handle lock	Cylinder lock	Accessories
-------------	-------	---------	-----------------	------------	------------------	------------	-------------	---------------	-------------



R L IP54

Main material and finish : Stainless steel housing, insert and cam, white zinc-plated steel shaft

Application : Quarter-turn opening or closing, with function of locking

Remark : Optional key K15 series




Default cam : S1M44N06001

Performance parameter:

Maximum static load: 590N

Recommended nut tightening torque: 30N.m

Maximum input torque: 11N.m



ERP MS816S00T07009
Remark: Default cam S1M44N06 (cut out Ø10x8)

MS816-4D-4



Main material and finish : Chrome-plated ZDC housing, insert, white zinc-plated steel shaft, stainless steel gear ring, cam and nut

Application: Lock insert aligns with the indicator mark on housing when in lock position;

Lock insert twists 195°anti-clockwise when opening;




120°turn causes shaft to pull of 6.4mm, Then 75°turn causes cam to rotate to achieve lock opening.

Performance parameter:

Maximum static load: 300N

Recommended nut tightening torque: 20N.m



Maximum input torque: 11N.m





Square 8mm
MS816-4D-4

Square 7mm
MS816-4D-5



Model	MS816-4D-4	MS816-4D-5
ERP	MS816Z3AT07015	MS816Z3AT06004



Unadjustable type



Adjustable type



Remarks: Lock insert pic refers to diagram P058

Specification	Unadjustable		Adjustable		Optional key
	Model	ERP	Model	ERP	
8mm Triangle	MS817-1	MS817Z2AT04001	MS817-1A	MS817Z2AT04007	K15-3, K15-3F
S Hook	MS817-2	MS817Z2AT03001	MS817-2A	MS817Z2AT03002	K15-1
8mm Socket hexagon	MS817-3	MS817Z2AT24001	MS817-3A	MS817Z2AT24002	
10mm Hexagon	MS817-4	MS817Z2AT25003	MS817-4A	MS817Z2AT25002	K15-9, K15-9F
8mm Square	MS817-5	MS817Z2AT07001	MS817-5A	MS817Z2BT07002	K15-4, K15-4F
7mm Square	MS817-6	MS817Z2AT06001	MS817-6A	MS817Z2AT06003	K15-6, K15-6F
9mm Square	MS817-8	MS817Z2AT26001	MS817-8A	MS817Z2AT26002	
Slot	MS817-9	MS817Z2AT10001	MS817-9A	MS817Z2AT10002	
7mm Triangle	MS817-10	MS817Z2AT14001	MS817-10A	MS817Z2AT14002	K15-3, K15-3F
Abnormal	MS817-12	MS817Z2AT21001	MS817-12A	MS817Z2AT21002	K31

MS817



R L IP54

Main material and finish: Black powder coated ZDC housing and insert, white zinc plated steel cam

Application: Cam Quarter-turn to open or close, with function of locking

Remark: Optional key K15

Default cam : S1B45N07001(Unadjustable)
S1M33Y00002(Adjustable Ts=5)

Performance parameter:

Maximum static load: 190N

Recommended nut tightening torque: 20N.m

Maximum input torque: 6N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

MS823-1



Handle lock Electronic lock Accessories

MS823-1A



Cylinder lock

Plane lock

Rod control lock



Main material and finish: Bright chrome-plated ZDC housing and insert, white zinc plated steel cam

Application: Cam quarter-turn to open or lock , with function of locking

Remark : Optional key K15


Default cam : S1B45N070016(Unadjustable)
S1M33Y00002(Adjustable Ts=5)

Performance parameter:




Maximum static load: 100N

Recommended nut tightening torque:20N.m



Maximum input torque: 12N.m



Specification	Unadjustable		Adjustable		Optional key
	Model	ERP	Model	ERP	
8mm Triangle	MS823-1	MS823Z3AT04001	MS823-1A	MS823Z3AT04004	K15-3、K15-3F
S Hook	MS823-2	MS823Z3AT03007	MS823-2A	MS823Z3AT03014	K15-1
8mm Socket hexagon	MS823-3	MS823Z3AT24001	MS823-3A	MS823Z3AT24002	
10mm Hexagon	MS823-4	MS823Z3AT25001	MS823-4A	MS823Z3AT25002	K15-9、K15-9F
8mm Square	MS823-5	MS823Z3AT07001	MS823-5A	MS823Z3AT07002	K15-4、K15-4F
7mm Square	MS823-6	MS823Z3AT06001	MS823-6A	MS823Z3AT06002	K15-6、K15-6F
9mm Square	MS823-8	MS823Z3AT26001	MS823-8A	MS823Z3AT26002	
Slot	MS823-9	MS823Z3AT10001	MS823-9A	MS823Z3AT10002	
7mm Triangle	MS823-10	MS823Z3AT14001	MS823-10A	MS823Z3AT14002	K15-3、K15-3F
Abnormal	MS823-12	MS823Z3AT14001	MS823-12A	MS823Z3AT21002	K31



ERP MS822Z1A000001
Remark : ERP excludes cam (cut out Øx6.5)



ERP MS824Z3A000001
Remark : Default cam S1V2700

MS822



Main material and finish : Black powder coated ZDC housing and handle, white zinc-plated steel cam ,insert and shaft
Application : Quarter-turn opening or closing, adjustable, with function of locking

Default cam : S1K46Y07001

Performance parameter:
Maximum static load: 140N

MS824



Main material and finish: Bright chrome-plated ZDC housing, insert and white zinc-plated steel cam
Application: 180 degree rotation opening or closing

Default cam : S1V27Y00001

Performance parameter:
Maximum static load: 70N
Recommended nut tightening torque:20N.m
Maximum input torque: 5.Nm

	Handle lock	Electronic lock	Accessories
--	-------------	-----------------	-------------

MS825





Main material and finish: Bright chrome-plated ZDC housing, insert and lock bolt, white zinc-plated ZDC lock bolt

Application: Automatic reset locked

Remark: Default key K160

Performance parameter:




Maximum static load: 320N





ERP

MS825Z3A160001

Catcher (Optional)



ERP MS824-7D
MS826Z3A000008



MS826-7D



IP55

Main material and finish: bright chrome-plated housing and insert, white zinc plated insert and lock tongue

Application: Key alike and key different available, resilient automatically lock

Performance Parameter

Maximum static load: 340 N

	Rod control lock	Plane lock	
--	------------------	------------	--

MS826





Main material and finish: Bright chrome-plated ZDC housing, insert and lock-tongue, white zinc-plated ZDC lock tongue

Application: Automatic reset locked

Remark: Default key K160

Performance parameter:





Maximum static load: 340N



ERP

MS826Z3A160001

Catcher (Optional)



MS826-8D



IP55

Main material and finish: bright chrome+varnish brush ZDC housing and insert, white zinc-plated ZDC lock tongue, 120 hours salt spray test

Application: resilient automatically lock

Performance Parameter

Maximum static load: 340 N

Seal gasket	Hinge		
-------------	-------	--	--

Handle lock Electronic lock Accessories

MS844






Main material and finish : Bright chrome-plated ZDC housing and handle, white zinc-plated steel cam

Application : Quarter-turn opening or closing

Default cam : S1W16Y00001




Performance parameter:

Maximum static load: 180N



Specification	Model	ERP
Plate	MS844-1	MS844Z3A000001
Nut	MS844-2	MS844Z3A000002

Remark : Default cam S1W1600 (Cutout $\varnothing 6 \times 3.6$)



ERP MS845N00000001

Remark: Default cam S1V2400

MS845-5



RL

Main material and finish: ZDC housing and black PA handle, white zinc plated steel cam.

Remark: Fast-installed housing, cam DS1V serial optional

Default cam : S1V24Y00001

Performance parameter:
Maximum static load: 220N

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

MS845-1



MS845-3

RL IP54


Main material and finish : Black powder coated ZDC housing and insert, white zinc-plated steel cam

Application : Quarter-turn opening or closing

Default cam : S1V24Y00001




Performance parameter:

Maximum static load: 220N



Specification	Model	ERP
Square 6mm	MS845-1	MS845Z3AT05001
Slot	MS845-2	MS845Z1AT10007
Handle	MS845-3	MS845Z1A000013

Remark : Default cam S1V2400 (cut out 6x6)



ERP MS845S00T30001

MS845-7B




Main material and finish: stainless steel housing, insert, keeper and cam

Application: 90 degree rotation, positioned by keeper

Performance Parameter
Maximum static load: 270 N

PLANE LOCK SERIES



Specification	Model	ERP
Cam opening from left rotation	MS703-Z	MS703Z3A000001
Cam opening from right rotation	MS703-Y	MS703Z3A000003

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

MS703




Main material and finish: Bright chrome-plated ZDC lock body and white zinc-plated steel cam
Application: Quick-open, easy assembling, by adjusting the cam screw to change the H and L of cam

Performance parameter:

Handle load tension capability: ≤350N

Maximum static load: 350N

MS707




Main material and finish: Blast-spraying and nickle plated ZDC housing, handle, button and insert, white zinc-plated steel cam

Application: Quick-open, easy assembling, by adjusting the cam screw to change the H and L of cam

Performance parameter:

Handle load tension capability: ≤900N

Maximum static load: 350N



Specification	Model	ERP	
		Opening from left rotation	Opening from right rotation
With insert	MS707	MS707Z3I000001	MS707Z3I000002
With lead sealable button	JMS707	MS707Z3I000003	MS707Z3I000004

MS708




Main material and finish: Sand-blast ZDC housing, handle and button, zinc-plated steel screw

Application: Quick-open design, easy installation. Adjusting screw on cam meets the need of distance control

Performance parameter:

Handle load tension capability: ≤285N

Maximum static load: 200N



Remark: Default adjustable screw, others on request

Specification	Model	ERP
H=46.5	MS708-1	MS708Z3H000002
H=59.5	MS708-2	MS708Z3H000004
H=24	MS708-3	MS708Z3H000006

MS710



Main material and finish: Nanometer painted ZDC housing and handle, ZDC insert, white zinc plated steel support and cam

Application: Quick-open , easy assembling. One-point locking or three-point locking function will be achieved with different cam mounted on

Remark: Default key k010


Default cam: S3C62Y00004

Performance parameter:

Handle load tension capability: ≤ 220N

Handle load torque capability: ≤ 11 N.m

Maximum static load: 380 N




Optional cam S1C3700D Optional cam S1C3621D Optional cam S2C2100

Remark : Optional cam refer to drawings separately

ERP MS710Z2B010002

Remark: The default cam is S3C6200


MS712



Remark: Change the fitting position or angle of position device and cam to realize LH or RH application

Model	ERP	L1	L3	W1	W3	GH	A2	A3	Cam	Default key
MS712	MS712Z2B040001	149	139.5	38	29.5	30	22	22.5	S1C7200	K040
MS712-2A	MS712Z2B110001	132	124	33.5	27.5	30	22	17	S1C7200	K110
MS712-3A	MS712Z2B110002	92	84	33.5	27.5	30	22	17	S1C7200	K110
MS713	MS713Z2B090001	110	102	33.5	27	30	22	17	S1C6200	K090

MS713-Q



ERP MS713Z2B090010

Remark : The default cam is S1C7200

**MS712
MS713**



MS713-Q



RL **IP54**

Main material and finish: Nanometer painted ZDC housing and handle, ZDC insert, white zinc plated steel support and cam

Application: Quick-open,easy assembling. One-point locking or three-point locking function will be achieved with different cam mounted on

Remark: The default key of MS713-Q is K040

Default cam: S1C72Y00002

Performance parameter:

MS712

Handle load tension capability: ≤ 690N

Handle load torque capability: ≤ 42 N.m

MS713

Handle load tension capability: ≤ 510N

Handle load torque capability: ≤ 40 N.m

Maximum static load: 265 N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
MS717-1												
RL												
Main material and finish: Black painted ZDC housing and handle, white zinc plated steel support and cam Application: Quick-open, easy assembling, H variable												
Default cam: S1B73Y00001												
Performance parameter: Handle load tension capability: \leq 140N Handle load torque capability: \leq 17 N.m Maximum static load: 150 N												
		ERP	MS717Z2A000002									
		Remark: Default cam is S1B7300 (rhombic hole)										
MS717-2												
RL												
Main material and finish: Silk black powder ZDC housing and handle, white zinc plated steel support and cam Application: Quick-open, easy assembling, H variable												
Default cam: S1B73Y00001												
Performance parameter: Handle load tension capability: \leq 125N Handle load torque capability: \leq 17 N.m Maximum static load: 150 N												
		ERP	MS717Z2A000009									
		Remark: Default cam is S1B7300 (rhombic hole)										
MS718												
Tighten												
Main material and finish: Black powder coated ZDC housing, handle and button, ZDC insert, white zinc plated steel screw Application: Quick-open, easy assembling, by adjusting screw meets the need of distance control Remark: Default key K180												
Performance parameter: Handle load tension capability: \leq 750N Maximum static load: 200N												
MS718-2												
Tighten												
Main material and finish: silk black powder coated ZDC housing, handle, insert and button, white zinc-plated screw Application: Quick-open, easy assembling, by adjusting screw to meet the need of distance control Remark: default key K160												
Performance parameter: Handle load tension capability: \leq 540N Maximum static load: 200N												

		MS718-3
Accessories	Electronic lock	
	Handle lock	
Cylinder lock		Main material and finish: Black powder coated ZDC housing, handle, insert and button, white zinc plated steel screw Application: Quick-open, easy assembling, by adjusting screw meets the need of distance control Remark: Default key K160
Plane lock		Performance parameter: Handle load tension capability: ≤1500N Maximum static load: 290 N
Rod control lock	Panel lock	MS718-3C 
Toggle and hook	Handles	 
Door stop		Main material and finish: Bright chrome-plated ZDC housing, handle and button, white zinc-plated support, connection, screw Application: Quick open, easy assembling, adjust nut to fit different H Remark: Default K650 key
Hinge		Performance parameter: Handle load tension capability: ≤1300N Maximum static load: 290N
Seal gasket		

ERP

MS718Z3A650002

Remark: Default adjusting screw,
others on request

Specification	A=29		A=50	
	Model	ERP	Model	ERP
With insert	MS719-1	MS719Z1A020001	MS719-2	MS719Z1A020002
Without insert	MS719-1A	MS719Z1A000001	MS719-2A	MS719Z1A000002

MS718-4C

Tighten **IP65**

Main material and finish: Bright chrome-plated ZDC housing, handle and button, white zinc-plated foot, connector, support and screw.

Application: Quick-open, easy assembling, by adjusting screw meets the need of distance control

Remark: Default key K650

Performance parameter:

Handle load tension capability: ≤790N

Maximum static load: 290N

MS719

Tighten

Main material and finish: Black powder coated ZDC housing, handle, insert and button, white zinc plated steel screw

Application: Quick-open, easy assembling, by adjusting screw meets the need of distance control

Remark: Default key K020

Performance parameter:

Handle load tension capability: ≤345N

Maximum static load: 200N

Seal gasket							
-------------	--	--	--	--	--	--	--

MS719-1C



Main material and finish: Black painted ZDC housing, handle, insert and button, white zinc plated steel screw


Application: Quick-open, easy assembling, by adjusting screw meets the need of distance control

Remark: Default key K020

Performance parameter:

Handle load tension capability: ≤1200N

Maximum static load: 200N



Remark: Default adjusting screw, others on request

Specification	A=29		A=50	
	Model	ERP	Model	ERP
With insert	MS719-1C	MS748Z3A160009	MS719-2C	MS719Z1A020008
Without insert	MS719-1CA	MS748Z3A160002	MS719-2CA	MS719Z1A000005

MS719-1U




Main material and finish: Sand-blast black painted housing, handle, button, insert, white zinc-painted cam and support

Application: press button, and the handle bounce automatically, put up the handle to open

Performance parameter:


Handle load tension capability: ≤200N

Maximum static load: 200N



ERP

MS719Z2A400001



ERP
MS723Z2B080001
Remark: Default cam is S3B6500

MS723



RL

Main material and finish: Nanometer painted ZDC housing and handle, white zinc-plated steel cam

Application: Open the handle upward, quarter-turn opening

Remark: Default key K083


Default cam: S3B65Y00002

Performance parameter:

Handle load tension capability: ≤130N

Handle load torque capability: ≤ 18N.m

Maximum static load: 200N



Remark: Change the fitting position of position device and cam to adjust the height. Change the fitting direction to suit RH or LH application

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------

Seal gasket	Hinge	Door stop	Handles	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories



RL **IP54**

Main material and finish: Nanometer painted ZDC housing and handle

Application: Quarter-turn opening or closing, adjust cam direction to realize RH or LH application

Remark: Default key K082




Default cam: S3B65Y00002

Performance parameter:

Handle load tension capability:≤98N

Handle load torque capability:≤14N.m

Maximum static load: 200N




Default key





Specification	Model	ERP	
		Nanometer painted	Sand-blast chrome-painted
ZDC button, with insert	MS720-1	MS720Z2B000001	MS720Z3H000014
ZDC button, without insert	MS720-2	MS720Z2B000015	MS720Z3H000025
Plastic button, with insert	MS720-1H	MS720Z2B000002	MS720Z3H000002
Plastic button, without insert	MS720-2H	MS720Z2B000007	MS720Z3H000004

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
MS720-1					



180 degree cam rotation to realize LH or RH (only for cam without bend)



ERP	Black powder coated housing, handle	Bright chrome-plated housing, handle	Nanometer painted housing, handle
MS726Z1A000001	MS726Z3A000001	MS726Z2B000001	

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
MS720-1H	MS720-1										

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
MS726-1					

RL

Main material and finish: ZDC housing and handle, white zinc plated steel support and cam

Application: Quick-open, easy assembling. H variable by adjusting nut with the function of telescopic

Default cam: S1K45N13004

Performance parameter:
Handle load tension capability:≤420N
Maximum static load: 400N

MS726-1A



RL

Main material and finish: Sand-spraying and bright chrome-plated ZDC housing, handle and insert, white zinc plated steel support and cam


Application: Quick-open , easy assembling, H variable by adjusting nut with the function of telescopic

Default cam: S1K45N13004

Performance parameter:


Handle load tension capability:≤420N

Maximum static load: 400N



ERP

MS726Z3H000003



ERP

MS726Z2A000009

MS726-2



RL

Main material and finish: ZDC housing and handle. white zinc plated steel support and cam


Application: Quick-open, easy assembling. H variable by adjusting nut with the function of telescopic

Default cam: S1K36N06001

Performance parameter:

Handle load tension capability:≤280N


Maximum static load: 400N



ERP


Black powder coated housing, handle	Bright chrome-plated housing, handle	Nanometer painted housing, handle
MS726Z1A000013	MS726Z3A000002	MS726Z2B000004

Remark: The default cam S1K36N06(Cut size Ø8x6.5)



ERP

MS727Z1A020002



Default cam S1K4513

MS726-3



RL

Main material and finish: Black painted ZDC housing and handle, white zinc plated steel support and cam

Application: Quick-open , easy assembling, H variable by adjusting nut with the function of telescopic

Default cam: S1W21N09001

Performance parameter:

Handle load tension capability:≤245N

Maximum static load: 220N

MS727



RL

Main material and finish: Black powder coated ZDC housing and handle, ZDC insert, white zinc plated steel support and cam

Application: Quick-open , easy assembling, H variable by adjusting nut with the function of telescopic

Remark: Default key K020

Default cam: S1K45N13004

Performance parameter:

Handle load tension capability:≤690N

Maximum static load: 430N

Accessories
Electronic lock
Handle lock
Cylinder lock

Cylinder lock
Plane lock

Plane lock
Rod control lock

Rod control lock
Panel lock

Panel lock
Toggle and hook

Toggle and hook
Handles

Handles
Door stop

Hinge

Seal gasket

Accessories
Electronic lock
Handle lock
Cylinder lock

Cylinder lock
Plane lock

Plane lock
Rod control lock

Rod control lock
Panel lock

Panel lock
Toggle and hook

Toggle and hook
Handles

Handles
Door stop

Hinge

Seal gasket



MS728



RL

Main material and finish: Sand-spraying and chrome-plated ZDC housing and insert, ZDC button or PA button, white zinc-plated steel cam


Application: Quick-open, easy assembling, H variable, Bend the cam to suit the different H

Default cam: S1D56Y00002

Performance parameter:


Handle load tension capability:≤500N

Maximum static load: 350N



180 degree cam rotation to realize LH or RH (only for cam without bend)

Specification	Model	ERP	
		Nanometer painted	Sand-blast chrome-painted
ZDC button, with insert	MS728-1	MS728Z2B000005	MS728Z3H000001
ZDC button, without insert	MS728-2	MS728Z2B000006	MS728Z3H000005
Plastic button, with insert	MS728-1H	MS728Z2B000003	MS728Z3H000002
Plastic button, without insert	MS728-2H	MS728Z2B000004	MS728Z3H000006



ERP	Painted (black) housing, handle	Nanometer painted housing, handle
	MS730Z2A200002	MS730Z2B200002



Main material and finish: ZDC housing, insert, and button, white zinc-plated ZDC cam

Application: Quick-open, easy assembling, front-end of lock tongue is suitable to special frame structure

Default cam: S1D56Y00002

Performance parameter:

Handle load tension capability:≤540N

Maximum static load: 400N



MS730

RL

Main material and finish: ZDC housing, insert, and button, white zinc-plated steel cam

Application: Quick-open, easy assembling, H variable, Bend the cam to suit the different H


Remark: Default key K200

Default cam: S1D56Y00002

Performance parameter:


Handle load tension capability:≤600N

Maximum static load: 350N



180 degree cam rotation to realize LH or RH (only for cam without bend)

ERP	Painted (black) housing, handle	Nanometer painted housing, handle
	MS730Z2A200001	MS730Z2B200018



ERP	MS732Z3A000001



MS732

RL

Main material and finish: Bright chrome-plated ZDC housing, handle and button, zinc-plated steel cam

Application: Quick-open design, easy installation. Bend the cam to suit the different H

Default cam: S1D56Y00002

Performance parameter:

Handle load tension capability:≤555N

Maximum static load: 350N

	Accessories	Electronic lock	Handle lock	Cylinder lock
--	-------------	-----------------	-------------	---------------

MS736



RL

Main material and finish: Nanometer painted ZDC housing and handle, ZDC insert, white zinc plated steel support and cam

Application: Quick-open,easy assembling, one-point locking or three-point locking function will be achieved with different cam mounted on

Remark: Default key k060

Default cam: 2893240002

Performance parameter:

Handle load tension capability:≤980N

Handle load torque capability:≤14N.m

Maximum static load: 270N

Plane lock

Rod control lock

Panel lock


Toggle and hook

Handles

Door stop

Hinge

Seal gasket






Remark: Change the assembling position of the position device and cam to adjust the stop height, thickness of position device is 1.5mm, change the fitting direction of position device to realize RH or LH application

ERP

MS736Z2B060001

Remark: The default cam is S2C2400



Remark: Change the fitting direction of position device and cam to realize RH or LH application

Specification	Model	ERP
With insert	MS738-1	MS738Z2B110009
Without insert	MS738-2	MS738Z2B000002

Remark: The default cam is S1A4500

MS738



Tighten
RL

Main material and finish: Nanometer painted ZDC housing, handle and button, ZDC insert, white zinc plated steel support and cam

Application: Quick-open,easy assembling. One-point locking or three-point locking function will be achieved with different cam mounted on

Remark: Default key k113

Default cam: S1A45Y0004

Performance parameter:

Handle load tension capability:≤250N

Handle load torque capability:≤14N.m

Maximum static load: 270N

Accessories	Electronic lock	Handle lock	Cylinder lock
-------------	-----------------	-------------	---------------

Rod control lock

Panel lock	Toggle and hook	Handles
------------	-----------------	---------

Door stop	Hinge	Seal gasket
-----------	-------	-------------

MS738-1A



Material: Zamak housing, handle, cylinder Q235 support, cam

Finish: Nanometer painted housing, handle, button, white zinc plated support cam

Structure :Quick-open, easy assembling. One-point locking and three-point locking function will be achieved with different cam mounted on.

Remark:The default key of it is K020



Default cam: S1B45Y00005

Performance parameter:

Handle load tension capability: $\leq 690\text{N}$

Handle load torque capability: $\leq 40\text{N.m}$

Maximum static load: 270N



Remark:Change the fitting position of the position device and cam can be adjusted the GH, the thickness of the position device is 1.5mm. Change the location of the position device can realize the LH or RH application

ERP

MS738Z2B020002

MS738-2A



Material: Zamak housing, handle, cylinder Q235 support, cam

Finish: Nanometer painted housing handle, white zinc plated support cam

Structure :Quick-open, easy assembling. One-point locking and three-point locking function will be achieved with different cam mounted on.

Remark:The default key of it is K020



Default cam: S1B45Y00005

Performance parameter:

Handle load tension capability: $\leq 510\text{N}$

Handle load torque capability: $\leq 40\text{N.m}$


Maximum static load: 270N



Remark:Change the fitting position of the position device and cam can be adjusted the GH, the thickness of the position device is 1.5mm. Change the location of the position device can realize the LH or RH application

ERP


MS738Z2B020001




MS818-2C

MS818-1C


MS818-1S




Default cam S1C7200




Default profile insert TC04-1




Optional profile insert TC04-2



Optional cam S2C2500
S2C2000




Optional profile insert
TC05-1/TC05-2



Optional cam S3C8800

Optional profile insert
TC06-1



Remark: Change the fitting position or angle of position device and cam to realize LH or RH application

Program	ERP	
	Black powder coated	Nanometer painted
MS818-1C	MS818Z1A040001	MS818A2B040001
MS818-2C	MS818A1A040003	MS818A2B040003
MS818-1S	MS818Z1A040003	MS818Z2B040003

MS818



Main material and finish: Black powder coated aluminium-alloy housing and ZDC handle, bright chrome plated ZDC profile insert, white zinc plated steel support and cam

Application: Quick-open,easy assembling, one-point locking or three-point locking function will be achieved with different cam mounted on

Remark : Default profile insert TC04-1, Default key K040

Default cam: S1C72Y00002

Performance parameter:

MS818-1S:

Handle load tension capability: $\leq 250\text{N}$

Handle load torque capability: $\leq 30\text{N.m}$

MS818-1C/2C:

Handle load tension capability: $\leq 430\text{N}$

Handle load torque capability: $\leq 25\text{N.m}$

Max static load :300N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

MS818-3B



Accessories	Electronic lock	Handle lock	Electronic lock	Accessories
Plane lock	RL	3PL		

Main material and finish: Nanometer painted housing, handle,bright chrome-plated ZDC profile insert,white zinc-plated steel support and cam

Application: Quick-open, easy assembling, change cam to have one-point or three point locking function

Remark: Default profile insertTC04-2, default key K040




Default cam: S3C72Y00002

Performance parameter:

Handle load tension capability:≤500N

Handle load torque capability:≤28N.m


Maximum static load: 300N



Remark: Change the fitting position or angle of position device and cam to suit LH or RH application

ERP MS818Z2B000002


Remark: Default cam S3C7200



ERP MS834-5-P with padlock MS834-5 without padlock

MS834Z1A043001 MS834Z1A043003

Remark : ERP excludes cam (optional 10*10) Optional cam S3C5000



Remark: Default cam S3B4510,H=20.5+10,default profile insert TC01. Cam cutout square 8mm, optional cam, three-point, two- point or one-point cam, see cam list on P007

ERP MS874S4BE03001

Remark: Default cam S3B4510

MS834-5



Main material and finish: Black powder coated ZDC housing and handle, bright chrome-plated ZDC profile insert, stainless steel support

Application: Open the handle upward, quarter-turn opening or closing, padlockable

Remark: Default key K043

Performance parameter:

Handle load tension capability:≤310N

Handle load torque capability:≤33N.m

Tips: Tighten the lock cover is helpful to protect the insert

Max static load :300N

MS874



RL **IP54** **3PL** **INOX AISI 3..**

Main material and finish: Stainless steel lock-body and cam, PA dish

Application: Open the handle upward, quarter-turn opening or closing

Remark: Default profile insert TC01

Default cam: 2882451002

Performance parameter:

Handle load tension capability:≤485N

Handle load torque capability:≤25N.m

Maximum static load: 300N

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod lock	Plane lock
Accessories	Electronic lock	Handle lock	Cylinder lock	Handle lock	Cylinder lock	Rod control lock	Plane lock

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------

MS839



RL **3PL**

Main material and finish: Pocked black powder coated handle and housing,bright chrome-plated profile insert,white zinc-plated steel support and cam

Application: Lead sealable, stop height is variable according to the adjusting nut on cam

Remark: Default TC01 profile insert, default key K140

Default Cam: 2888390001


Performance parameter:

Handle load tension capability:≤700N

Handle load torque capability:≤40N.m


Maximum static load: 300N

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------




Remark: 8*8 cam series for option


TC01(Default)




TC03-1(Optional)




TC01-2(Optional)




TC18(Optional)—P128



TC02-1(Optional)




Default cam



Specification	Model	ERP
ZDC handle and housing (Without padlock)	MS839-1	MS839Z1B031003
ZDC handle and housing (With padlock)	MS839-1-P	MS839Z1B140002
ZDC handle and PA housing (Without padlock)	MS839-1F	MS839N00140008
ZDC handle and PA housing (With padlock)	MS839-1F-P	MS839N00140002


Remark: Default cam S3B7400




ERP	MS839-5-1 Without padlock	MS839-5-1P With padlock
	MS839N00140007	MS839N00140010

Remark: The default cam is S3B4507 (Option 8*8cam)

TC01 (Default)



MS839-5



RL **IP54**

Main material and finish: PA housing, black powder coated ZDC

handle, white zinc-plated steel cam

Application: 360 degree handle rotation, padlockable,profile insert adjustable

Remark: Default profile insert TC01, default key K140

Performance parameter:

Handle load tension capability:≤630N

Handle load torque capability:≤38N.m

Maximum static load: 300N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	---------	-----------	-------	-------------

MS843




RL **IP54**

Main material and finish: Nanometer painted ZDC handle and housing, white zinc-plated steel support and cam
Application: Open the handle upward, with cam 90° rotation opening
Remark: Default key K080


Default cam: S3B6500

Performance parameter:

Handle load tension capability: ≤180N
Handle load torque capability: ≤14N.m
Maximum static load: 190N




Default cam S3B6500




Remark: Change the fitting position of the position device and cam to adjust the stop height, change the fitting direction to suit RH or LH application


Specification	With insert		Without insert	
	Model	ERP	Model	ERP
A=89 B=63	MS843-1	MS843Z2B080013	MS843-1A	MS843Z2B000011
A=107 B=80	MS843-2	MS843Z2B080016	MS843-2A	MS843Z2B000012
A=123 B=96	MS843-3	MS843Z2B080020	MS843-3A	MS843Z2B000005



MS860-1



MS860-2



Default cam S3B4500

Optional cam S1B6800X

Model	ERP	Material & Finish
MS860-1	MS860S4B000001	Stainless steel(Brushes polish)
MS860-2	MS860Z3G000001	Yellow nickel plated zinc alloy

MS860



Structure: The H dimension can be adjusted by nut, padlock available

Default cam: 2882450007(Stainless steel)
 2882450002(White zinc plated steel)


Performance parameter:

Handle load tension capability: ≤280N
Handle load torque capability: ≤42N.m
Maximum static load: 300N

Seal gasket	Hinge	Door stop	Handles	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



MS861



Main material and finish: Pocked black power coated ZDC housing and handle, white zinc-plated steel cam, stainless steel shaft

Application: Open the handle upward quarter-turn opening, adding electronic shielding part to have function of shielding

Remark: Default key K140



Default cam: S3C44Y13005(Right)
S3C44Y13002(Left)

Performance parameter:

Handle load tension capability: ≤570N

Handle load torque capability: ≤14N.m

Maximum static load: 300N



Main material and finish: ZDC housing , handle and shaft, steel support;


Application: Open the handle upward quarter-turn opening, position device direction to suit RH or LH application;

Remark: Default TC01 profile cylinder,K140 key. cam is optional,can be used for MS861-2

Performance parameter:
Handle load tension capability: ≤390N
Handle load torque capability: ≤12N.m
Maximum static load: 300N



MS861-2



Main material and finish: ZDC housing, handle and shaft, white zinc-plated steel cam

Application: Open the handle upward, quarter-turn rotation opening

Remark: Default K140 key



Default cam: 2882451002

Performance parameter:

Handle load tension capability: ≤390N

Handle load torque capability: ≤12N.m

Maximum static load: 300N



ERP	Pocked black powder coated housing and handle	Nanometer painted housing and handle
MS861Z1B140017	MS861Z2B140003	

Remark: Default cam S3B4510 (cut size8*8)

ERP MS861ZXX140001

MS861-2H



NEW

RL 3PL ▶ IP65

Main material and finish: ZDC housing , handle and shaft;

Application: Open the handle upward quarter-turn opening,

Remark: SUS304 screw, cam can be S1B series or S3B series

Performance parameter:

Handle load tension capability:≤390N

Handle load torque capability:≤12N.m

Maximum static load: 300N



MS861-2H Brass padlock



NEW

Main material and surface: Spraying essential oil after polishing on HPG59-1 lock shell,chrome plated steel lock hook;



Remark: S-shape profile cylinder, default key K72-3, Key alike only, with padlock.




ERP	Description
1118610001	with key
1118610002	without key

ERP


MS861ZXX000001



Use key to open the lock, without password



Enter password to open the lock, open lock with password instead of key, original password: "0,0,0"



Change the password (when it is correct), when knob indicates opening position, anti-clockwise rotation 15 degree to change the password

ERP MS861N00140001

Remark: Default cam S3B4510 (Optional cam 8*8)

MS861-2A



RL 3PL ▶ IP54

Main material and finish: Black PA housing, handle and knob, white zinc-plated steel cam and support

Application: Refer to instruction along with product

Remark: Default key K140

Default cam: 2882451017

Performance parameter:

Handle load tension capability:≤60N

Handle load torque capability:≤5N.m

Maximum static load: 300N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

MS861-3



Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------

RL **IP54**

Main material and finish: PA handle, housing, drive box

Application: Quarter-turn opening and close, position device direction to suit RH or LH application;

Remark: Default key K193


Default cam: S1B45Y00002

Performance parameter:

Handle load tension capability: ≤115N

Handle load torque capability: ≤10N.m





Maximum static load: 220N



ERP MS861N00193004

Remark: default cam S1B4500(optional cam 8*8)

Default key



ERP MS861Z1B140062

MS861-4



NEW

RL **3PL** **IP65**

Main material and finish: Black painting or silvery nanometer painting ZDC handle, housing, zinc plated steel cam and support;

Application: Quarter-turn opening and close, RH or LH application;

Remark: Default key K140

Default cam: S1B45Y00002

Performance parameter :

Handle tension capability: ≤350N

Handle torque capability: ≤25N.m

Life test: 5000 times open and close, the function is good

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

MS864-3



Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------

RL

Main material and finish: Black powder coated ZDC housing and handle, stainless steel shaft, white zinc-plated steel cam

Application: Open the handle upward, quarter-turn rotation opening, with function of locking, padlockable

Remark: Default profile insert TC06-1





Default cam: 2888643001

Performance parameter:

Handle load tension capability: ≤485N

Handle load torque capability: ≤25N.m

Maximum static load: 600N



MS864-3A



RL

Main material and finish: Black powder coated ZDC housing and handle, stainless steel shaft, white zinc-plated steel cam

Application: Open the handle upward, quarter-turn opening, with function of locking, padlockable

Remark: Default profile insert TC06-4

Default cam: S1C55Y00001


Performance parameter:

Handle load tension capability: ≤550N


Handle load torque capability: ≤45N.m

Maximum static load: 600N


TC04-1(Optional)




TC04-2(Optional)




TC06-2(Optional)



TC05-1(Optional)



TC06-1(Default)



Profile insert	A	B
TC06-2	17	Ø12
TC06-3	26.5	Ø14
Default TC06-4	12	Ø8x11

ERP

MS864Z1A290027

Remark: Default cam S3C5424

ERP

MS864Z1A290015

Remark: Default cam S1C5500

MS864-4




Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock

Cylinder lock

Handle lock

Electronic lock

Accessories



RL **IP64**

Main material and finish: Black painted ZDC housing and handle (high salt mist resistance)

Application: Quarter-turn opening or closing, position device direction to suit RH or LH application, padlockable

Remark: Default profile insert TC03-5

Default cam: 2888648002

Performance parameter:


Handle tension capability: ≤2500N

Handle torque capability: ≤21N.m

Remark: The tighten cap is good for protecting the cylinder

Maximum static load : 600N

Exploded sketch




Change the fitting direction
of the position device to
suit RH or LH application




ERP	MS864-4-3D with padlock	MS864-4-3D-P without padlock
	MS864Z2E142001	MS864Z2EE03003

Remark: Default key S3C58Y00 (Optional 10*10 cam)


Default profile insert




Default key



Default profile



Default Key



ERP	MS892Z1AE02001
Remark: ERP excludes Cam (Optional cam 10*10)	

MS892-1A

Accessories	Electronic lock	Handle lock	Cylinder lock

RL **IP64**

Main material and finish: Matt black powder coated ZDC housing and handle

Application: 90° rotation to open or close, position device direction to suit RH or LH application, padlockable

Performance parameter:

Handle tension capability: ≤690N

Handle torque capability: ≤45N.m

Remark: The tighten cap is good for protecting the cylinder


Maximum static load : 600N

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock

ROD CONTROL LOCK SERIES




MS731-1



	Black painted housing, handle	Nanometer painted housing, handle
ERP	MS731Z2A060001	MS731Z2B060001

Remark: Default cam S1A3500

MS731-2



	Black painted housing, handle	Nanometer painted housing, handle
ERP	MS731Z2A060003	MS731Z2B060003

Remark: Default cam S1A3900

MS731-1



Main material and finish: ZDC housing, handle, button and rod latch, white zinc-plated steel cam and rod

Application: 90 degree rotation to open or close

Remark: Default key K060

Performance parameter:

Handle load tension capability:≤350N


Handle load torque capability: $\leq 25\text{N}\cdot\text{m}$

Seal gasket	Hinge	Door stop	Handles	Handles	Door stop	Hinge	Seal gasket

MS731-3



MS731-3



MS731-4



Rod control lock

R **L** **IP40** **3PL**

Main material and finish: ZDC housing, handle, button and rod latch, white zinc-plated steel cam

Application: 90 degree rotation to open or close

Remark: Default Key K060

Performance parameter:


Handle load tension capability: ≤350N

Handle load torque capability: ≤25N.m

ERP	Black painted housing, handle	Nanometer painted housing, handle
	MS731Z2A060016	MS731Z2B060005

Remark: Default cam S1A3900


MS731-4



ERP	Black painted housing, handle	Nanometer painted housing, handle
	MS731Z2B060027	MS731Z2B060023

Remark: Default cam S1B4507 (Optional cam 8*8)

MS731-6



Specification	Model	ERP
LH	MS731-6-Z	MS731Z2B060007
RH	MS731-6-Y	MS731Z2B060008

Remark: Default cam S1A3810

MS731-6



R **L** **IP40** **3PL**

Main material and finish: Nanometer-painted ZDC housing, handle, button and support, white zinc-plated steel cam and rod latch, steel rod

Application: Insert 180 degree rotation to open, press the button, the handle bounce automatically, rotation handle to open or close the door plate

Remark: Default key K060

Performance parameter:

Handle load tension capability: ≤350N

Handle load torque capability: ≤25N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

MS820



R L IP40 3PL ▶

Main material and finish: Nanometer painted ZDC panel, dust-proof cap and insert, white zinc-plated steel cam and rod latch


Application: Quarter-turn rotation to open or close

Remark: Optional key K15-1



Performance parameter:

input torque: ≤9N.m

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------



Remark: Keep rod and rod latch in place while removing the cam and insert, rotating the rod latch in 180° to suit RH or LH application



Remark: Keep rod and rod latch in place while removing the cam and insert, rotating the rod latch in 180° to suit RH or LH application

MS820-1A



R L IP40 3PL ▶

Main material and finish: Nanometer painted ZDC insert and ABS panel, white zinc-plated steel cam and rod latch

Application: Quarter-turn rotation to open or close

Remark: Optional key K15-1

Performance parameter:

input torque: ≤3N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------


Specification	Model	ERP
Hooked	MS820-1	MS820Z2BT03001
Triangular 8mm	MS820-3	MS820Z2BT04001
Cross insert	MS820-4	MS820Z2BE02001

Remark: Default cam S1A3500

ERP MS820N2BT03001

Remark: Default cam S1A3500




Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories	MS821
												
							R	L	IP40	3PL		



Remark: Change rod and cam position to suit RH or LH application

ERP

MS821N00T01001



	Matt black powder coated	Nanometer
ERP	MS828Z1A100001	MS828Z2B100017

Remark: Default cam S1A3500

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------



main material and finish: Nanometer
painted ZDC housing, handle, and button,
ZDC support, white zinc-plated steel cam
and rod latch, steel rod

Application: Insert 180 degree rotation to open, press the button, the handle bounce automatically, handle turn combines with latching system to open or close

Remark: Default key K100

Performance parameter:

MS828-1F





Main material and finish: Plastic housing with metal part, Black painted ZDC handle, shaft, button, white zinc plated ZDC rod latch system, white zinc plated steel rod and cam

Remark: Default key K020

Default cam: S1A35Y00001


Performance parameter:

Handle load tension capability:≤250N
Handle load torque capability: ≤15N.m






MS828-1F advantage compare with MS828

- 1: Plastic and zinc base alloy inserts, with a certain degree of strength.
- 2: Locking part of the base front lock makes locking function must improve the reliability.
- 3: Design structure linked to the reserved zone, the user can choose two forms with padlock and without padlock.



Remark: MB1 series rod latch system



Remark: Default cam S1A3500

	MS828-1F Without padlock device	MS828-1F-P With padlock device
ERP	MS828N00100001	MS828N00200002

ERP MS828Z2B020008

MS828-8

RL

IP65

3PL ►

Main material and finish: Nanometer painted or black painted ZDC housing, handle, and button, white zinc-plated steel cam, press plate and rod latch,

Application: Insert 180° degree rotation to open, press the button, the handle bounce automatically, handle turn combines with rod latch system to open or close, padlock optional, LH and RH available.

Remark: Default key K10

Performance parameter:

Handle load tension capability: ≤250N

Handle load torque capability: ≤30N.m



Application: Insert 180° degree rotation to open, press the button, the handle bounce automatically, handle turn combines with rod latch system to open or close, padlock optional LH and RH available

Handle load tension capability:≤250N
Handle load torque capability:≤22N·m

MS828-9



NEW

RL **3PL**






Main material and finish: Nanometer painted ZDC housing, handle, serpentine lock, Q235 press plate, Carbon steel, white zinc-plated steel cam and rod latch, ZDC support, steel rod
Application: Cylinder 180 rotation to open, press the button, the handle bounce automatically, handle turn combines with rod latch system to open or close
Remark: Default key K72-3

Performance parameter:

Handle load tension capability: ≤340N

Handle load torque capability: ≤28N.m

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------



Remark: Change rod and cam position to suit RH or LH application

ERP

MS828Z2B720002

ERP

MS829Z1E060001

Remark: Default cam S1A3405

MS829



R **L** **IP40** **3PL**

Main material and finish: Yellow gray powder coated ZDC housing, black powder coated ZDC handle and button, white zinc plated steel cam and rod latch

Application: Handle quarter-turn combines with rod latch system to open or close

Remark: Default key K060

Performance parameter:

Handle load tension capability: ≤240N

Handle load torque capability: ≤20N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------



MS830




Finish: Yellow gray powder coated housing, black powder coated handle and shaft



MS830-3



Finish : Nanometer painted



Main material and finish: ZDC housing, handle, and dust-proof cap, white zincplated steel cam and rod-latch

Application: Handle quarter-turn combines with rod latch system to open or close

Remark: MS830 default key K580
MS830-3 default key K140


Performance parameter:

MS830:
Handle load tension capability: ≤225N
Handle load torque capability: ≤14N.m


MS830-3:
Handle load tension capability: ≤325N
Handle load torque capability: ≤20N.m

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

MS830





MS830-3



Remark: Change rod and cam position to suit RH or LH application

ERP	MS830	MS830-3
MS830Z1EE04001		MS830Z2B140003

Remark: Default cam S1A3500



Specification	Model	ERP
with padlock device,insert with self-reset function	MS830-6-2P	MS830Z2BE04031
without padlock device,insert with self-reset function	MS830-6-2	MS830Z2BE04030
with padlock device,insert without self-reset function	MS830-6-1P	MS830Z2BE04023
without padlock device,insert without self-reset function	MS830-6-1	MS830Z2BE04022

Remark: Default cam S1A34Y05001

MS830-6



Main material and finish: Nanometer-painted ZDC housing and dust cap, black painting ZDC handle and shaft, ZDC rod latch, steel rod, cam and connection
Remark: Default K580 key


Default cam: S1A34Y05001

Performance parameter:
Handle load tension capability: ≤315N
Handle load torque capability: ≤22N.m




Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod lock

The advantage of MS830-6 when compare with MS830

- Promote the reliability of latch function and theft-prevent function
- Handle can bounce after open the lock




Cam latch system Mb90




Remark: Default rod latch system, closing position, quarter-turn rotation, cam cutout square 8mm, optional cam series S1B, S2B, S3B, detailed cam list on P007
Default one-point cam S1B4507, H=19+7, length 45
Default three-point cam S3B4510, H=19+10

RH and LH application example




Keep cam and rod latch system in place while rotating the rod latch system in 180°


RH, open from right rotation with handle



RH, open from right rotation with handle




LH, open from left rotation with handle



Rotate shaft 90 degree, remove the cam and assemble it on the right side
LH, open from left rotation with handle

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock
Hinge	Door stop	Handles	Toggle and hook	Panel lock	Panel lock

**Mb0 Series
Mb2 Series**



Remark: Without rod latch system, use for seal door-outside, cam cutout 7mm, optional cam S1A cam series, see detailed cam list on P007. Default cam S1A3500, H=GH, length 35.



Keep rod and rod latch in place, remove the cam and insert, and rotate rod latch system in 180 degree to suit RH or LH application

Dm: Rod stroke

Ra: Rotation angle code

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Plane lock	Rod control lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket										


Mb1 Series



Optional Accessories:

See cam latch system Mb9 series on P174
Rod latch system Mb0 series on P175

Remark: Mb0 series transmission mechanism, the corresponding B size of 180



Main material and finish: Black painted ZDC housing ,handle and button,white zinc-plated steel cam and combines with rod latch system

Application: Handle quarter-turn combines with rod latch system to open or close

Remark: Default key K040

Default cam: S1A35Y00001 (Rod latch type)
S1B45Y07002 (Cam type)

Performance parameter:

Handle load tension capability: ≤280N

Handle load torque capability: ≤30N.m

Maximum static load: 270N (cam type)

Rod latch system	Dm	Ra	A	B	Specification
Mb01	15	90°	122	196	With cam
Mb02	15	90°	122	196	Without cam
Mb03	15	90°	138	196	With cam
Mb04	15	90°	138	196	Without cam
Mb21	15	90°	122	122	With cam
Mb24	23	135°	138	130	Without cam

Specification	Model	ERP
With button, optional rod latch system Mb01	MS831-1	MS831Z2A040001
With button, optional rod latch system Mb02	MS831-1-2	MS831Z2A040003
Without button, optional rod latch system Mb01	MS831-2	MS831Z2A040005
Without button, optional rod latch system Mb02	MS831-2-2	MS831Z2A040006
Without button	MS819-1	MS819Z2A040009
With button	MS819-2	MS819Z2A040003

MS832



MS832-1 MS832-2 MS832-1P

Accessories

Handle lock Electronic lock

Cylinder lock

Padlock

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

Push

Profile insert

Padlock

Handle

Cam control

Handle

Insert

Support

MS834-6



RL **IP55** **3PL**

Main material and finish: Black painted (high salt mist resistant) ZDC handle and housing, bright chrome-plated ZDC profile insert, stainless steel cam and rod

Application: Handle lift 45 degree
Handle 135° rotation combines with rod latch system to open or close, change gear and rod direction to suit RH or LH application



Remark: Default profile insert TC03-5A

Performance parameter:


Handle load tension capability: ≤395N

Handle load torque capability: ≤33N.m


Reminder: Tighten the locks protecting cover to protect the lock





Default TC03-5A



Default Key



	MS834-6-Z	MS834-6-Y
ERP	MS834Z2E000001	MS834Z2E000002



MS840-1

MS840-2



TC18 Insert (optional)--P122

Optional accessories:
See cam latch system Mb9 series on P174
Rod latch system Mb0 series on P175
TC01/TC02/TC03 profile insert on P027

Remark: PA housing or ZDC housing, default ZDC housing

Specification	Model	ERP
Optional rod latch system Mb01	MS840-1	MS840Z1B140001
Optional rod latch system Mb01, padlockable	MS840-1P	MS840Z1B140002
Optional rod latch system Mb02	MS840-1-2	MS840Z1B140019
Optional rod latch system Mb02, padlockable	MS840-1-2P	MS840Z1B140020
Cam latch system	MS840-2	MS840Z1B140064
Cam latch system, padlockable	MS840-2P	MS840Z1B140014

MS840



RL **IP54** **3PL**

Main material and finish: Pocked black powder coated ZDC housing and handle, ZDC profile insert, white zinc-plated steel cam and rod

Application: 90 degree handle rotation combines with rod latch to open or close

Remark: Default key K140

Default cam: S1A35Y00001(Rod latch type)
S1B45Y07005 (Cam type)

Performance parameter:


Handle load tension capability: ≤400N

Handle load torque capability: ≤35N.m

Maximum static load: 270N(cam type)

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

MS840-4



Main material and finish: Black powder coated ZDC housing, handle, zinc-plated steel cam

Application: 45 degree handle uplift rotation combines with cam to open or close, Open lock from left hand or right hand need change the set angle of limit part and cam


Character

Use magnet to open or close the lock. The advantage is the lock system is not exposed and the key combinations is more than other standard inserts. Open the lock, put the magnetic key into the groove of the handle, then put up the handle.


Performance parameter:

Handle load tension capability: ≤400N


Handle load torque capability: ≤35N.m



ERP MS840Z1B000006
Remark: Default cam S1A4500



MS840-5-1



MS840-5-2

Optional accessories:
See cam latch system Mb9 series on P174
Rod latch system Mb0 series on P175

MS840-5-1



Main material and finish: Black painted ZDC handle, housing, white zinc plated ZDC shaft, lock-tongue, steel cam, press plate and strip.

Application: Optional cam control system and rod control system

Remark: Optional key K140 and K720

Performance parameter:

Handle load tension capability: ≤330N

Handle load torque capability: ≤26N.m

Maximum static load: 270N(cam type)

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------

MS840-5-2

MS840-A



RL

Main material and finish: Black PA handle, housing and dust-proof cap, white zinc-plated steel cam and rod, bright chrome-plated ZDC profile insert

Application: Handle quarter-turn rotation combines with rod latch system to open or close

Remark: Default profile insert TC01, default key K140

Default cam: S1B45Y07002 (Cam type)


Performance parameter:

Handle load tension capability: ≤300N

Handle load torque capability: ≤33N.m

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------

Specification	Model	ERP
Rod latch system with TC series profile insert and dust-proof cap	MS840-1A	MS840N00140039
Cam latch system with TC series profile insert and dust-proof cap	MS840-2A	MS840N00140033




Optional Accessories:

See cam latch system Mb9 series on P174

Rod latch system Mb4 series on P192

TC01/TC02/TC03 profile insert on P027

Specification	Model	ERP
Rod latch system with insert	MS840-1B	MS840N00140025
Cam latch system with insert	MS840-2B	MS840N00140034



Optional Accessories:

See cam latch system Mb9 series on P174

Rod latch system Mb4 series on P192

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



RL

Main material and finish: Black PA housing, handle and dust-proof cap, white zinc-plated steel cam and rod, ZDC profile insert

Application: Handle quarter-turn combines with rod latch system to open or close

Remark: Default Key K140

Default cam: S1B45Y07002 (Cam type)

Performance parameter:

Handle load tension capability: ≤300N

Handle load torque capability: ≤33N.m

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories



RL **IP40** **3PL**

Main material and finish: Black PA handle, housing and dust-proof cap, white zinc-plated steel cam and rod, ZDC profile insert

Application: Handle quarter-turn combines with rod latch system to open or close

Remark: Default Key K140


Default cam: S1B45Y07002 (Cam type)

Performance parameter:

Handle load tension capability: ≤300N


Handle load torque capability: ≤33N.m

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------




MS840-1C

MS840-2C



MS840-D





Cut out

Optional Accessories:

See cam latch system Mb9 series on P174

Rod latch system Mb4 series on P192

Specification	Model	ERP
Rod latch system	MS840-1C	MS840N00140011
Cam latch system	MS840-2C	MS840N00140015



Cut out



RL **3PL**

Main material: Zamak housing, handle, insert ;Q235 support, cam, rod drive

Finish: Nanometer painted housing, handle, white zinc plated cam, rod drive

Structure : Open the lock by turning the insert 45 degree, handle pop-out, moving with drive system to open or close

Remark: Default TC03 profile insert

Performance parameter :

Handle load tension capability: ≤400N

Handle load torque capability: ≤35N.m

Max static load : 270N(Cam type)

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

MS846



MS846-1

MS846-2



Main material and finish: Pocked black powder coated ZDC handle and housing, ZDC profile insert, white zinc-plated steel cam and rod

Application: 90 degree handle rotation combines with rod latch to open or close

Remark: Default profile insert TC01, default key K140


Default cam: S1A35Y00001(Rod latch type)
S1B45Y07002(Cam type)

Performance parameter:

Handle load tension capability: ≤235N

Handle load torque capability: ≤40N.m

Maximum static load: 270N(cam type)




Optional accessories:

See cam latch system Mb9 series on P174
Rod latch system Mb0 series on P175
TC01/TC02/TC03 profile insert on P027

Remark: PA housing or ZDC housing ,default ZDC housing

Specification	Model	ERP
Optional rod latch system Mb01	MS846-1	MS846Z1B140001
Optional rod latch system Mb01, padlockable	MS846-1-P	MS846Z1B140002
Optional rod latch system Mb02	MS846-1-2	MS846Z1B140005
Optional rod latch system Mb02, padlockable	MS846-1-2P	MS846Z1B140007
Cam latch system	MS846-2	MS846Z1B140003
Cam latch system, padlockable	MS846-2-P	MS846Z1B140004



Optional accessories:

See cam latch system Mb9 series on P174
Rod latch system Mb0 series on P175
TC01/TC02/TC03 profile insert on P027

Remark : PA housing or ZDC housing, default ZDC housing

Specification	Model	ERP
Optional rod latch system Mb01	MS848-1	MS848Z1B140017
Optional rod latch system Mb02	MS848-1-2	MS848Z1B140004
Cam latch system	MS848-2	MS848Z1B140010

MS848



MS848-1

MS848-2



Main material and finish: Pocked black powder coated ZDC handle and housing, ZDC profile insert, white zinc-plated steel cam and rod

Application: 90 degree handle rotation combines with rod latch to open or close

Remark: Default profile insert TC01, default key K140

Default cam: S1A35Y00001(Rod latch type)
S1B45Y07002(Cam type)

Performance parameter:

Handle load tension capability: ≤520N

Handle load torque capability: ≤27N.m

Maximum static load: 270N(cam type)

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

MS848-1E



RL **IP65**

Main material: Black PA housing, Handle, dust-proof cap, zamak profile insert



Finish : Bright chrome plated insert, white zinc plated cam and rod drive

Remark : Optional profile insert
TC01,TC02,TC03 Default TC01 with K14

Performance parameter:

Handle load tension capability:≤170N

Handle load torque capability:≤20N.m




Cut out

Optional Accessories:
See cam latch system Mb9 series on P174
Rod latch system Mb4 series on P192


ERP

MS848N00140038



MS848-1B

MS848-2B



Cut out

Optional Accessories:
See cam latch system Mb9 series on P174
Rod latch system Mb2 series on P175

MS848-B



RL **IP54**

Main material and finish: Black PA handle, housing and dust-proof cap, white zinc-plated steel cam and rod, ZDC profile insert

Application: Handle quarter-turn combines with rod latch system to open or close

Remark: Default profile insert TC01, default Key K140

Default cam: S1B45Y07002 (Cam type)

Performance parameter:

Handle load tension capability:≤170N


Handle load torque capability:≤20N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

Specification	Model	ERP
Rod latch system	MS848-1B	MS848N00140002
Cam latch system	MS848-2B	MS848N00140018


Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------

Combination	Item No	
	Rod latch system	Cam latch system
①A	MS840-1A	MS840-2A
①B	MS840-1D	MS840-2D
②A	MS840-1B	MS840-2B
②B	MS840-1E	MS840-2E
③A	MS840-1F	MS840-2F
③B	MS840-1C	MS840-2C
④A	MS848-1B	MS848-2B
④B	MS848-1C	MS848-2C



- 1.Lock-body
- 2.Insert
- 3.Lock-body
- 4.Profile insert
- 5.Insert
- 6.Board
- 7.Rod latch system
- 8.PA dish
- 9.Rod latch system
- 10.Cam latch system
- 11.Cam latch system
- 12.Cam


Mb4 Series



Remark: Default rod latch system, closing position, 135 degree rotation angle, default optional cam S1B3500, cam cutout square 8mm. The rod latch system is used for the seal door-outside

Rod latch system	Dm	Ra	A	B	C	D	Specification
Mb43	23.5	135°	123.5	223.5	173.5	173.5	With cam
Mb44	23.5	135°	123.5	223.5	173.5	173.5	Without cam

Mb5 Series





Remark: Default rod latch system, closing position, 135 degree rotation angle, default optional cam S1B3500, cam cutout square 8mm. The rod latch system is used for the seal door-outside

Rod latch system	Dm	Ra	A	B	Specification
Mb51	23.5	135°	62.5	62.5	With cam
Mb52	23.5	135°	62.5	62.5	Without cam





Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

**Mb92-Y
Mb92-Z**



Remark: Default optional cam S3B4510

Mb94 Series



Support (Optional)

Specification	Model	ERP
Double bit	MS853-1-1	MS853Z1DT01001
Triangular	MS853-1-2	MS853Z1DT04001
Square 8mm	MS853-1-3	MS853Z1DT07001
Slot	MS853-1-4	MS853Z1DT10001
Default Key K04	MS853-2	MS853Z1D040001

MS853



IP40

Main material and finish: Blue gray powder coated ZDC handle, housing, ZDC support, white zinc-plated steel rod, PC dust-proof cap

Remark: Optional Key K15 series or K040

Performance parameter:

Handle load tension capability: ≤275N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

MS855-3





IP40

Main material and finish: Black ABS handle, housing, white zinc-plated ZDC slider, white zinc-plated support

Remark: Default Key K400


Performance parameter:

Handle load tension capability:≤150N






Model	Length(mm)	Lock catch appropriate quantity
LG-2D-250	250	1
LG-2D-375	375	1
LG-2D-500	500	1
LG-2D-625	625	2
LG-2D-750	750	2
LG-2D-875	875	2

Rod length=125 X n, n: Rod-Joint quantity, joint distance=125 ;



Catcher



Hook No	H	Z
KP1	19	15.5
KP2	20	16.5
KP3	22	18.5
KP4	25	21.5

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

MS855-5





MPL

Main material and finish: Painted RAL7030 ZDC housing and handle, ZDC slider and fix part, stainless steel rod




Remark: Default key K110

Performance parameter:

Handle load tension capability: ≤800N



Assembly drawing



MS861-2B



RL IP55

Main material and finish: PA housing and handle, white zinc plated ZDC rod latch, white zinc plated steel rod and screws

Remark: Handle with password

Default key K140

Performance parameter:

Handle load tension capability: ≤60N

Handle load torque capability: ≤5N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-------	-----------	---------	-----------------	------------	-----------------	---------	-----------	-------	-------------

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

MS861-2E



RL




Main material and finish: PA housing, Black powder coated ZDC handle, white zinc plated ZDC shaft and insert, white zinc plated steel rod latch and cam

Application: 135 degree handle rotation to open or close, padlock device for choose

Performance parameter:

Handle load tension capability: ≤290N

Handle load torque capability: ≤22N.m



ERP

MS861Z2A140001

Specification	Model	ERP
PA housing and handle	MS861-1	MS865N00140002
PA housing and pocked coated ZDC handle	MS861-1A	MS865N00140006

MS865



R

Main material and finish: Black PA housing, pocked black powder coated ZDC handle, white zinc plated steel rod


Application: Handle quarter-turn combines with rod latch system to open or close

Remark: Default Key K140

Performance parameter:

Handle load tension capability: ≤195N


Handle load torque capability: ≤10N.m




Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Mb95 rod latch system


Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories




View D




View E




View A



View B



View C



Remark: Generally rod prepared by user as per the frame instruction and lock stroke

ERP

MS867Z1E082001

MS867

IP40

Main material and finish: Yellow gray powder coated ZDC handle and housing, white zinc-plated ZDC rod

Application: Handle rotation to open or close rapidly, easy assembling


Remark: Default Key K082

Performance parameter:


Handle load tension capability: $\leq 490\text{N}$



Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



ERP MS867Z2A140001




MS875-1

MS875-2



Optional Accessories:

See cam latch system Mb9 series on P175
Rod latch system Mb4 series on P192



Double bit 4mm Triangular 8mm Square 8mm Square 7mm

Specification	Rod latch system		Cam latch system		Optional key
	Model	ERP	Model	ERP	
Double bit	MS875-1-1	MS875N00T02014	MS875-2-1	MS875N00T02013	K15-1A、K15-1F
Triangular 8mm	MS875-1-2	MS875N00T04001	MS875-2-2	MS875N00T04003	K15-3、K15-3F
Square 7mm	MS875-1-3	MS875N00T06001	MS875-2-3	MS875N00T06003	K15-6、K15-6F
Square 8mm	MS875-1-4	MS875N00T07001	MS875-2-4	MS875N00T07003	K15-4、K15-4F

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------

**MS875-1A
MS875-2A**



RL **IP54**

Main material and finish: Black PA panel, bright chrome-plated ZDC insert, white zinc-plated steel cam and rod


Application: Insert quarter-turn combines with rod latch system to open or close

Remark: Default Key K15 series


Default cam: S1B45Y07002 (Cam type)

Performance parameter:

Maximum Input torque: ≤10N.m



MS875-1A



MS875-2A

Optional Accessories:



See cam latch system Mb9 series on P174

Rod latch system Mb5 series on P192



Double bit 4mm Triangular 8mm Square 8mm Square 7mm

Specification	Rod latch system		Cam latch system		Optional key
	Model	ERP	Model	ERP	
Double bit	MS875-1A-1	MS875N00T03001	MS875-2A-1	MS875N00T02019	K15-1A, K15-1F
Triangular 8mm	MS875-1A-2	MS875N00T04002	MS875-2A-2	MS875N00T04008	K15-3, K15-3F
Square 7mm	MS875-1A-3	MS875N00T06002	MS875-2A-3	MS875N00T06004	K15-6, K15-6F
Square 8mm	MS875-1A-4	MS875N00T07002	MS875-2A-4	MS875N00T07004	K15-4, K15-4F



ERP MS875N00T01002

Remark: Default cam S1B3011D

MS875-3



RL **IP54**

Main material and finish: PA housing and panel, Zinc-plated steel cam and rod, chrome-plated ZDC insert

Application: Insert 90° rotation combines with rod latch system to open or close

Remark: Optional K15 series tool key

Performance parameter:

Maximum Input torque: ≤10N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

MS876



Main material and finish: Black PA housing, bright chrome plated ZDC handle, white zinc-plated steel rod

Application: Handle rotation combines with rod latch to open or close


Remark: Default key K140

Default cam: S1B45Y07002 (Cam type)


Performance parameter:

Handle load tension capability: ≤490N

Handle load torque capability: ≤26N.m






MS876-1



MS876-2


	MS876-1	MS876-2
ERP	MS876N00140014	MS876N00140010



Remark: Change the drive device position to realize LH or RH

Specification	Model	ERP
With dust-proof cap handle and TC series insert	MS882-1A	MS882N00140003
With simple insert handle	MS882-1B	MS882N00140006
With simple insert handle and buckle	MS882-1C	MS882N00140004
With sliding dust-proof cap and TC series insert	MS882-1D	MS882N00140005

MS882



Main material and finish: Black PA lock body, white zinc-plated steel rod

Remark: Default key K140





Performance parameter:

Handle load tension capability: ≤330N

Handle load torque capability: ≤30N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

PANEL LOCK SERIES



Default cam: S2C2500

MS850-1A



Main material and finish: Gray powder coated ALU housing, handle and cover, ZDC padlock device, zinc-plated steel shaft and keeper

Default cam: 2893250016

Performance parameter:

Handle load torque capability: ≤18N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	-------------	------------	-----------------	---------	-----------	-------	-------------






2PL

Main material and finish: Gray powder coated ALU housing, handle, padlock device, cover and shaft, zinc-plated steel cam and keeper

Default cam: 2893250016



Performance parameter:

Handle load torque capability: ≤25N.m




Default cam: S2C2500


Optional cam S2C2000



Cut out




Optional cup



Default cam S2C2500



WP003 water-tight cap (Optional)



Item	ERP	Specification	
		A	B
MS850-2	MS850A1D000007	54	69
MS850-2A	MS850A1D000008	44	59

ERP	MS856 Hole type	MS856-M Screw bolt type
	MS856S4A130001	MS856S4A130002

MS856



2PL

Main material and finish: Mirror polished stainless steel cup, bright chrome-plated ZDC handle, shaft tube and dust-proof cap, white zinc-plated ZDC bracket, steel cam and shaft

Remark: Default key K130

Default cam: 2891250002

Performance parameter:

Handle load torque capability: ≤24N.m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

Seal gasket

MS857



3PL

Main material and finish: Mirror polished stainless steel cup, cam and shaft tube, bright chrome-plated ZDC handle, shaft tube and dust-proof cap



Remark: Default key K130

Default cam: S3B65Y13001


Performance parameter:

Handle load torque capability: ≤14N.m


Cam loading capability: ≤510N



Cut out





Optional cup




Optional cam S1B1179D




Optional WP003 water-tight cap




Cut out



Optional cup



Default cam S1B7013D



Cut out



Optional WP003 insert water-tight cap

MS858



Main material and finish: Mirror polished stainless steel cup and cam, bright chrome-plated ZDC handle, shaft tube and dust-proof cap, white zinc-plated ZDC bracket and steel shaft

Remark: Default key K130

Default cam: S1B70Y13002

Performance parameter:

Handle load torque capability: ≤27N.m


Cam loading capability: ≤510N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------


ERP	MS857 Hole type MS857S4A13001	MS857-M Screw bolt type MS857S4A13003
-----	----------------------------------	--

ERP	MS858 Hole type MS858S4A13001	MS858-M Screw bolt type MS858S4A13002
-----	----------------------------------	--


Remark : ERP excludes Cam




MS866-2



	MS866-1	MS866-2
	MS866S4A082001	MS866S4A082002



Specification	Without insert		With insert	
	Model	ERP	Model	ERP
Steel	MS866-3A	MS866F1A000006	MS866-3	MS866F1A160001
SUS	MS866-3SA	MS866S4A000005	MS866-3S	MS866S4A160003



Specification	Model	ERP
With insert	MS866-4	MS866F1A330001
Without insert	MS866-4A	MS866F1A000001

The image shows a black, rectangular door handle assembly. It features a central lock mechanism with a keyhole. The handle is integrated into a larger, recessed frame. A small metal clip or fastener is visible at the bottom left corner of the handle frame.



Chain material and finish: Silk black steel
cup and handle, sand blast and nickel-
plated ZDC profile insert, zinc-plated steel
latch, support and riveting screw
Remark: Default key K230

Performance parameter:
Handle load tension capability: ≤200N
Ham loading capability: ≤550N

MS866-5



Seal gasket	Hinge	Door stop	Handles	Handles	Toggle and hook	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Plane lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	---------	-----------------	-----------------	------------	------------------	------------	---------------	------------	-------------	-----------------	-------------







Main material and finish: Silk black steel cup and handle, nickle-plated ZDC profile insert, zinc-plated steel latch, support and weld screw

Remark: Default key K082

Performance parameter:

Handle load tension capability: ≤145N

Cam loading capability: ≤800N




Latch 1



Latch 2

The dimension of Latch 1 and Latch 2 are the same, the welding direction is different



Cut out

MS866-5E



Main material and finish: Silk black steel cup, handle, chrome plated ZDC insert, stainless steel cover

Application: The drawing shows in locked position, turn the key and open insert, the handle pulls 20° up to open buckle by anti-loose structure, it can automatic reset.

Remark: There is catcher available, default one is without catcher. Default key is K49, key different available

Performance parameter:

Handle load tension capability: ≤145N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod lock

Panel lock

Toggle and hook

Handles


Door stop

Hinge

Seal gasket

Specification	Without insert		With insert	
	Model	ERP	Model	ERP
H=31.5	MS866-5	MS866F1A080001	MS866-5A	MS866F1A000003
H=44	MS866-5B	MS866F1A080002	MS866-5BA	MS866F1A000004
H=55	MS866-5C	MS866F1A080003	MS866-5CA	MS866F1A000005

Pull buckle




ERP

2138665001


ERP

MS866F1A490001

MS866-6



Main material and finish: Silk black steel cup, handle and ZDC profile insert, zinc-plated steel latch, support and weld screw
Remark: Default key K160



Remark: default product is with out keeper

Panel lock

Rod control lock

Plane lock


Cylinder lock

Handle lock

Electronic lock

Accessories

MS866-6



ERP	MS866-7 With insert	MS866-7A Without insert
	MS866S4A410001	MS866S4A000004

MS866-7



Main material and finish: Stainless steel cup, handle, latch and cam, bright chrome-plated profile insert

Remark: Default key K410


Performance parameter:
Handle load tension capability: ≤150N
Cam loading capability: ≤550N



Main material and finish: Stainless steel cup, handle
Finish: Mirror polished cup and handle


Performance parameter:
Handle load tension capability: ≤150N
Cam loading capability: ≤550N

Pull buckle



ERP

2138665001



ERP

MS866S4A410004

Seal gasket

Hinge

Door stop

Handles

Toggle and hook

Panel lock

Rod control lock

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket




MS866-8

							Accessories

Main material and finish: Wire-drawing polished stainless steel

Performance parameter:

Handle load tension capability: ≤50N
Cam loading capability: ≤200N



ERP MS866S4B000001



MS866-22


							Panel lock

Main material and finish: Mirror polished stainless steel cup and handle (steel in nanometer painting available), white zinc plated latch and support.

Remark: Default key K53



Performance parameter:

Handle load tension capability: ≤200N
Cam loading capability: ≤500N



MS866-22
MS866F2B530002

ERP MS866S4A530002



MS866-21
MS866F2B530001

ERP MS866S4A530001



MS866-21S

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Main material and finish: Stainless steel (or steel) cup, handle, white zinc plated latch and support

Remark: Default key K530

Performance parameter:

Handle load tension capability: ≤200N
Cam loading capability: ≤1000N

MS866-26



Plane lock | Cylinder lock | Handle lock | Electronic lock | Accessories

Main material: Stainless steel lock body and handle zamak cam, steel cover
Finish: Mirror polished lock body and handle White zinc plated cover and cam
Remark:Optional insert, Key K13

Performance parameter:
Handle load tension capability:≤180N
Cam loading capability: ≤1000N

Panel lock

MS866-27




Door stop | Handles | Toggle and hook


Main material: Stainless steel handle and lock body Zamak cam,steel cover
Finish: Mirror polished handle and lock body, white zinc plated steel cam
Remark:Optional insert, Key K13

Performance parameter:
Handle load tension capability:≤180N
Cam loading capability: ≤1000N

Seal gasket



Model	MS866-26	MS866-26A(Without cylinder)
ERP	MS866S4A130001	MS866S4A000007





MS866-28



Main material: Stainless steel handle and lock body zamak cam, steel cover
Finish: Mirror polished handle and lock body white zinc plated cam and cover
Remark: Optional insert, default key K13

Performance parameter:
Handle load tension capability:≤180N
Cam loading capability: ≤1000N



Model	MS866-28	MS866-28A(Without cylinder)
ERP	MS866S4A130002	MS866S4A000009

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

MS982-3



Seal gasket Hinge Door stop Handles Toggle and hook Panel lock Rod control lock Plane lock Cylinder lock Handle lock Electronic lock Accessories

MS982-3A



IP65

Material:ZDC housing and handle

Finish :Bright chrome plated

Structure :Pull and turn the handle 90 degree, along with the cam,Closing the door by hitting when the lock is on the close status

Performance parameter:

MS982-3

Handle load torque capability: ≤31N.m

Cam loading capability: ≤4000N

MS982-3A



Handle load torque capability: ≤39N.m

Cam loading capability: ≤2000N

Application example





MS982-3



ERP

MS982Z3A520003

MS982-3A



ERP

MS982Z3A520004


TOGGLE AND HOOK SERIES





Main material and finish: Zinc-plated steel body, rubber handle

Performance parameter:
Maximum static load: 1500N




ERP DK603F3D000001






Main material and finish: ZDC housing and keeper, stainless steel bracket
Remark: Key K080 for selection

Performance parameter:
Maximum static load: 610N



Specification	ERP	
	Black powder coated	Bright chrome-plated
DK604-1 With insert	DK604Z2A080002	DK604Z3A080001
DK604-2 Without insert	DK604Z2A000001	DK604Z3A000001




ERP DK603F3D000004



Main material and finish: white zinc-plated steel

Performance parameter:
Maximum static load: 3000N


Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------



Main material and finish: Mirror polished stainless steel

Performance parameter:

Maximum static load: 800N



ERP DK605S4A000004

DK609



Main material and finish: Black rubber handle, stainless steel keeper and bracket

Performance parameter:


Maximum static load: 45N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	------------------------	---------	-----------	-------	-------------

Main material and finish: Zinc-plated steel

Performance parameter:

Maximum static load: 150N




ERP DK609N00000001

DK609-2





Main material and finish: Black rubber handle, stainless steel support and catcher

Performance parameter:
Maximum static load: 65N



Catcher




ERP

DK609N00000006

ERP


DK610S00000001

DK610



Main material and finish: Electrolytic stainless steel


Performance parameter:
Maximum static load: 765N



ERP


DK610S00000001

DK611



Main material and finish: Stainless steel bracket and button, chrome plated steel bolt with plastic grip

Performance parameter:
Maximum static load: 500N



ERP

DK611S00000001

Seal gasket	Hinge	Door stop	Handles	Panel lock	Toggle and hook	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	------------	-----------------	------------------	------------	---------------	-------------	-----------------	-------------

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------



DK614



NEW

Main material and finish: AISI316

Performance parameter:



Maximum static load: 750N

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------



ERP

DK614S4C000001




ERP

DK616Z3D000001



DK615

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------





Main material and finish: spray(black light) ZDC housing, handle, keeper and stainless steel pin

Performance parameter:

Maximum static load: 910N

ERP	DK615-1 With insert	DK615-2 Without insert
	DK615Z1A030002	DK615Z1A000001



ERP

DK617S00000001



DK616



Main material and finish: White zinc plated ZDC housing, stainless steel lock button and spring, plastic seal



DK617



Main material: Grinding and polishing stainless steel

Performance parameter:
Maximum static load: 320N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock
-------------	-----------------	-------------	---------------	------------	----------

DK617-5




Main material: Stainless steel Grinding and polishing

Structure : Padlock version is available

Performance parameter:

Maximum static load: 750N

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Cylinder lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	---------------	------------	---------------	-------------	-----------------	-------------



ERP **DK617S9D4001**


DK618-6




Main material: Steel
Finish: 3+ zinc plated

Item shown on the picture is
DK618-6-Z

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Cylinder lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	---------------	------------	---------------	-------------	-----------------	-------------



Specification	Model	ERP
Left hand	DK618-6-Z	DK618F3D000005
Right hand	DK618-6-Y	DK618F3D000006




Specification	Model	ERP
Left hand	DK618-7-Z	DK618F3D000007
Right hand	DK618-7-Y	DK618F3D000008

DK618-7



Main material: Steel
Finish: 3+ zinc plated
Item shown on the picture is
DK618-7-Z

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Cylinder lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	---------------	------------	---------------	-------------	-----------------	-------------



Specification	Model	ERP
Left hand	DK618-8-Z	DK618F3D000009
Right hand	DK618-8-Y	DK618F3D000010

DK618-8




Main material: Steel
Finish: 3+ zinc plated
Item shown on the picture is
DK618-8-Z

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------


DK618-9



Main material: Steel
Finish: 3+ zinc plated
Item shown on the picture is DK618-9-Y



Specification	Model	ERP
Left hand	DK618-9-Z	DK618F3D000012
Right hand	DK618-9-Y	DK618F3D000011



ERP DK619S4C000001

DK619-9



Main material and finish: Stainless steel 304

Performance parameter:
Maximum static load: 140N


Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock
-------------	-----------------	-------------	---------------	------------	----------

DK619-2-1D




Main material and finish: Mirror polishing cover with plastic SUS304 body

Performance parameter:
Maximum static load: 180N



ERP DK619S4A000001



ERP DK623N00000001


DK623




Main material: PBT toggle, stainless steel screw

Performance parameter:
Maximum static load: 80N

Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
------------	-----------------	---------	-----------	-------	-------------




Keeper




ERP

DK624S9C000002




Main material and finish: Electrolytic stainless steel

Performance parameter:
Maximum static load: 800N



ER

DK627S4C000001



ER

DK631F3E000001



Main material and finish: Stainless steel
304

Performance parameter:
Maximum static load: 300N



Main material: Steel
Finish: 3+ zinc plated
Structure: with function of anti-loose,
adjustable hook length

Performance parameter:
Maximum static load: 300N





Main material and finish: White zinc plated steel housing, SUS304 bracket, PA lock tongue.

Performance parameter:
Maximum static load: 330N

Seal gasket	Hinge	Handles	Door stop	Panel lock	Toggle and hook	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	---------	-----------	------------	-----------------	------------------	------------	---------------	-------------	-----------------	-------------


DK633-1

DK633-1



ERP

DK633F3D000001



ERP

DK633 F3D000004



Main material: steel lock body, stainless steel pin

Finish: 3+ zinc plated 48

Performance parameter:
Maximum static load: 320N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	---------	-----------	-------	-------------



DK634



Main material and finish: White zinc-plated steel body


Performance parameter:
Maximum static load: 250N

DK633-2



ERP

DK633F3D000002



ERP

DK634F3D000001




DK635

Seal gasket	Hinge	Door stop	Handles	Panel lock	Toggle and hook	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	------------	-----------------	------------------	------------	---------------	-------------	-----------------	-------------

Main material and finish: 3+ zinc plated

Performance parameter:

Maximum static load: 1000N



ERP

DK635F3D000001




Main material and finish: Wire-drawing polishing stainless steel handle, white zinc-plated steel bracket

Performance parameter:

Maximum static load: 810N


Seal gasket	Hinge	Door stop	Handles	Panel lock	Toggle and hook	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	------------	-----------------	------------------	------------	---------------	-------------	-----------------	-------------



ERP

DK638S4B000001

DK636-1



specification

with insert(with key)


without insert

ERP

DK636Z9D630001

DK636Z00000001

DK636-2



ERP

DK636Z2A342001

DK636-1



Main material and finish: 3+ zinc plated steel toggle, passivated ZDC handle
Product applications as picure show

Performance parameter:

Item:DK636-1

Maximum static load: 1500N

Item:DK636-2


Maximum static load: 1000N

Application example



Seal gasket	Hinge	Door stop	Handles	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

DK637





Main material and finish: Nickel plated ZDC housing, button and lock tongue

Application: When the button presses the form 6.5, the lock tongue shrinks to 7

Performance parameter:

Maximum static load: 400N



DK639



Main material and finish: Trivalent white-zinc steel body

Performance parameter:
Maximum static load: 570N


Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Seal gasket	Hinge	Door stop	Handles	Panel lock	Toggle and hook	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

DK725



DK725-1
DK725-2




DK725-3B

Main material: ABS toggle or PA toggle


Performance parameter:

Maximum static load: 300N


DK725-1
DK725-2




DK725-3B



DK725-3C



Specification	Model	ERP	
		ABS Silver	ABS Black
T=1.5	DK725-1	DK725N00000001	DK725N00000002
T=2	DK725-2	DK725N00000003	DK725N00000004
T=1~2	DK725-3B	DK725N00000010	DK725N00000006
T=1~2	DK725-3C	DK725N00000011	DK725N00000007



DK725-5




Main material and finish: stainless steel housing module, hard chrome plated steel insert module

Application: RH or LH door has different toggle. It applies to car battery latch system. Release lever designed by user


Performance parameter:

Maximum static load: 500N

Insert the front of the toggle to the hole and press it



Make the door in the right position



Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

ERP DK725N00140001

DK725-7




Seal gasket
Hinge
Door stop
Toggle and hook
Panel lock
Plane lock
Cylinder lock
Handle lock
Electronic lock
Accessories

Main material and finish: black PA
Application: 90° clockwise rotate the key to open

Remark: Default black K148 key

Performance parameter:

Maximum static load: 245N



ERP

DK725N00148001

DK725-8



Seal gasket
Hinge
Door stop
Handles
Toggle and hook
Panel lock
Plane lock
Cylinder lock
Handle lock
Electronic lock
Accessories


Main material: ABS+PC housing, handle, PC board, insert, ABS latch, tongue, stainless steel screw

Finish: black Instructure Turn the insert to the left, pull the handle for open

Remark: default key K164

Performance parameter:

Maximum static load: 480N




ERP

DK725N00164001

HANDLES SERIES

LS501	LS503	LS504-1	LS504-2	LS504-3
LS505	LS506	LS507	LS508	LS509
LS510	LS511	LS513	LS515	LS514-1
LS514-2	LS514-3-4-5	LS516	LS516-2A	LS518
LS519	LS520	LS521	LS522	LS532




LS501



Main material and finish: Nanometer painted ZDC pull handle, lock hook and steel spring

Performance parameter:

Maximum static load: 600N



LS504-1



Performance parameter:
Maximum static load: 800N



Specification	Model	ERP
With insert	LS501-10	LS501Z2B110001
Without insert	LS501-20	LS501Z2B110002

Specification	Model	ERP
Stainless steel	LS504-1B	LS504S00000001
Steel (Bright chrome)	LS504-1	LS504F3A000001

LS503



Performance parameter:
Maximum static load: 1000N



LS504-2




Main material and finish: Oxidation aluminum alloy base and pull handle, rubber sleeve

Performance parameter:
Maximum static load: 840N

	Stainless steel	Bright chrome-plated steel
ERP	LS503S4A072001	LS503F3A072001

ERP	LS504A9A000001
-----	----------------


LS504-3



ERP


LS504F1A000001

LS505



ERP

LS505N00132001



LS506



Performance parameter:

Maximum static load: 1200N(L=90)

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

Handles

Door stop

Hinge

Seal gasket

Specification	A=M10 B=Ø9 C=57.5 D=Ø16 H=41.5 E=Ø11 Ts=1~2		A=M6 B=Ø6 C=45 D=Ø11 H=32 E=Ø7 Ts=1~5			
	Bright chrome-plated steel		Stainless steel			
	Model	ERP	Model	ERP	Model	ERP
L=55	LS506-55	LS506F3A550002	LS506-S55	LS506F4A550002	LS506-2-55	LS506F3A055001
L=60	LS506-60	LS506F3A600002	LS506-S60	LS506F4A600002	LS506-2-60	LS506F3A060001
L=70	LS506-70	LS506F3A700002	LS506-S70	LS506F4A700002	LS506-2-70	LS506F3A070001
L=84	LS506-84	LS506F3A840002	LS506-S84	LS506F4A840002	LS506-2-84	LS506F3A084001
L=90	LS506-90	LS506F3A090001	LS506-S90	LS506S4A090001	LS506-2-90	LS506F3A090002
L=100	LS506-100	LS506F3A100001	LS506-S100	LS506S4A100001	LS506-2-100	LS506F3A100008
L=102	LS506-102	LS506F3A102002	LS506-S102	LS506S4A102002	LS506-2-102	LS506F3A102001
L=119	LS506-119	LS506F3A119001	LS506-S119	LS506S4A119001	LS506-2-119	LS506F3A119004
L=122	LS506-122	LS506F3A122002	LS506-S122	LS506S4A122002	LS506-2-122	LS506F3A122001
L=135	LS506-135	LS506F3A135001	LS506-S135	LS506S4A135001	LS506-2-135	LS506F3A135005
L=149	LS506-149	LS506F3A149001	LS506-S149	LS506S4A149001	LS506-2-149	LS506F3A149002
L=155	LS506-155	LS506F3A155001	LS506-S155	LS506S4A155001	LS506-2-155	LS506F3A155002
L=160	LS506-160	LS506F3A160001	LS506-S160	LS506S4A160001	LS506-2-160	LS506F3A160002


LS507



Main material and finish: Silk black powder coated steel

Performance parameter:

Maximum static load: 1500N(item LS507-S75)



Cut out

Specification	Bright chrome-plated steel		Stainless steel	
	Model	ERP	Model	ERP
L=68	LS507-68	LS507F3A068001	LS507-S68	LS507S4A068001
L=75	LS507-75	LS507F3A075001	LS507-S75	LS507S4A075001
L=100	LS507-100	LS507F3A075001	LS507-S100	LS507S4A100001
L=150	LS507-150	LS507F3A150001	LS507-S150	LS507S4A150001


LS510



Material:ZDC


Performance parameter:

Maximum static load:1500N



Cut out

	chrome plated	Nanometer painted
ERP	LS510Z3A100001	LS510Z2B100001



Cut out

Specification	Bright chrome-plated steel		Stainless steel	
	Model	ERP	Model	ERP
L=55	LS508-55	LS508F3A055001	LS508-S55	LS508S4A055001
L=60	LS508-60	LS508F3A060001	LS508-S60	LS508S4A060001
L=70	LS508-70	LS508F3A070001	LS508-S70	LS508S4A070001
L=74	LS508-74	LS508F3A074001	LS508-S74	LS508S4A074001
L=84	LS508-84	LS508F3A084001	LS508-S84	LS508S4A084001
L=90	LS508-90	LS508F3A090001	LS508-S90	LS508S4A090001
L=102	LS508-102	LS508F3A102001	LS508-S102	LS508S4A102001
L=122	LS508-122	LS508F3A122001	LS508-S122	LS508S4A122001
L=138	LS508-138	LS508F3A138001	LS508-S138	LS508S4A138001

LS508



Main material: Stainless steel or steel

Performance parameter:

Maximum static load: 1200N(L=90)

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories	Accessories		



LS509



Main material and finish: Polished or bright chrome-plated stainless steel or steel

Performance parameter:

Maximum static load: 1000N (L=90)



LS511



Performance parameter:

Item: LS511-Z-120

Maximum static load: 1800N

Specification	Bright chrome-plated steel		Stainless steel	
	Model	ERP	Model	ERP
L=55	LS509-55	LS509F3A055001	LS509-S55	LS509S4A055001
L=60	LS509-60	LS509F3A060001	LS509-S60	LS509S4A060001
L=70	LS509-70	LS509F3A070001	LS509-S70	LS509S4A070001
L=74	LS509-74	LS509F3A074001	LS509-S74	LS509S4A074001
L=84	LS509-84	LS509F3A084001	LS509-S84	LS509S4A084001
L=90	LS509-90	LS509F3A090001	LS509-S90	LS509S4A090001
L=102	LS509-102	LS509F3A102001	LS509-S102	LS509S4A102001
L=122	LS509-122	LS509F3A122001	LS509-S122	LS509S4A122001
L=138	LS509-138	LS509F3A138001	LS509-S138	LS509S4A138001

Model	ERP	Bright chrome-plated steel		Stainless steel (mirror polished)		Bright chrome-plated ZDC		Specification				
		Model	ERP	Model	ERP	Model	ERP	L	d	H	d ₁	D
LS511-B55	LS511F3A055001	LS511-B55	LS511S4A055001					55	6	26	M4	Ø 4.5
LS511-B60	LS511F3A060001	LS511-B60	LS511S4A060001					60	6	26	M4	Ø 4.5
LS511-B70	LS511F3A070001	LS511-B70	LS511S4A070001					70	6	32	M4	Ø 4.5
LS511-B82	LS511F3A082001	LS511-B82	LS511S4A082001					82	6	26	M4	Ø 4.5
LS511-B90	LS511F3A090001	LS511-B90	LS511S4A090001					90	6	32	M4	Ø 4.5
LS511-B102	LS511F3A102001	LS511-B102	LS511S4A102001					102	6	32	M4	Ø 4.5
LS511-B122	LS511F3A122001	LS511-B122	LS511S4A122001					122	6	32	M4	Ø 4.5
LS511-B138	LS511F3A138001	LS511-B138	LS511S4A138001					138	6	32	M4	Ø 4.5
LS511-A75	LS511F3A075001	LS511-A75	LS511S4A075001					75	8	40	M5	Ø 6
LS511-A100	LS511F3A100001	LS511-A100	LS511S4A100001					100	8	32	M5	Ø 6
LS511-A150	LS511F3A150001	LS511-A150	LS511S4A150001					150	8	40	M5	Ø 6
LS511-90	LS511F3A090002	LS511-S90	LS511S4A090002					90	9	32	M5	Ø 6
LS511-100	LS511F3A100002	LS511-S100	LS511S4A100002					100	9	32	M5	Ø 6
LS511-119	LS511F3A119001	LS511-S119	LS511S4A119001					119	9	40	M5	Ø 6
LS511-135	LS511F3A135001	LS511-S135	LS511S4A135001					135	9	32	M5	Ø 6
LS511-149	LS511F3A149001	LS511-S149	LS511S4A149001					149	9	40	M5	Ø 6
LS511-155	LS511F3A155001	LS511-S155	LS511S4A155001					155	9	32	M5	Ø 6
LS511-160	LS511F3A160001	LS511-S160	LS511S4A160001					160	9	40	M5	Ø 6
				LS511-Z101	LS511Z3A101001	101	9	29	M5	Ø 6		
				LS511-Z120	LS511Z3A120001	120	10	37	M6	Ø 7		
				LS511-Z180	LS511Z3A180001	180	12	45	M5	Ø 7		

Handles	Door stop	Hinge	Seal gasket	Handles	Door stop	Hinge	Seal gasket						


LS513



Main material and finish: Rubber sheath, steel tube, black PA end pieces and center support

Performance parameter:

Maximum static load: 600N (L=300)



Specification		Model	ERP
L	A		
300	266	LS513-300	LS513N00300001
400	366	LS513-400	LS513N00400002
500	466	LS513-500	LS513N00500001
600	566	LS513-600	LS513N00600001
700	666	LS513-700	LS513N00700002
800	766	LS513-800	LS513N00800001
900	866	LS513-900	LS513N00900002
1000	966	LS513-1000	LS513N00000A02
2000	1966	LS513-2000	LS513N00000B01


LS515



Main material and finish: Black powder coated steel


Performance parameter:

Maximum static load: 800N



ERP LS515F1A102001

LS514-1




ERP LS514Z3A102001

LS514-2



ERP LS514Z2B104001

LS514-3-4-5



Model	ERP	Specification					
		A	B	C	D	L	E
LS514-3	LS514A2B100001	10.5	7	32	8	100	2-M6
LS514-4	LS514A2B125001	14.5	9.5	50	11	125	2-M6
LS514-5	LS514A2B130001	18.5	9.5	40	16	130	2-M6

LS514-1



Main material and finish: Bright chrome plated ZDC

LS514-2



Main material and finish: Nanometer painted ZDC

LS514-3-4-5



Main material and finish: Nanometer painted aluminium alloy

Performance parameter:

Maximum static load: 800N

LS516




Accessories
Handle lock
Electronic lock
Cylinder lock
Plane lock
Rod control lock


Main material and finish: Silk black powder coated aluminum alloy

Performance parameter:

Maximum static load: 2500N (L=100)



Specification	Model	ERP
L		
75	LS516-75	LS516A1A075001
100	LS516-100	LS516A1A100001
125	LS516-125	LS516A1A125001
150	LS516-150	LS516A1A150001
175	LS516-175	LS516A1A175001



ERP LS516A2A400001

LS516-2A




Hinges
Handles
Door stop
Hinge


Main material and finish: Silk black powder coated aluminum alloy

Performance parameter:

Maximum static load: 3000N



ERP LS516A1A164001



Model	ERP	Specification		
		A	B	C
LS518-1U	LS518Z2B030001	42.6	30	2 - M4
LS518-2U	LS518Z2B071001	86.7	71	2 - M5
LS518-3U	LS518Z2B116001	131.2	115.5	2 - M5
LS518-4U	LS518Z2B160001	176	160	3 - M5

LS516-2A-1D




Main material and finish: Black painted aluminum alloy

Performance parameter:

Maximum static load: 1000N

LS518



Main material and finish: Nanometer painted ZDC handle

Performance parameter:

Maximum static load: 1500N

Handles	Door stop	Hinge	Seal gasket	Handle lock	Cylinder lock	Plane lock	Rod control lock	Handle lock	Electronic lock	Accessories	LS519
 <p>Main material and finish: Mirror polished stainless steel handle</p> <p>Performance parameter: Maximum static load: 850N</p>	 <p>Main material and finish: Black ABS</p> <p>Performance parameter: Maximum static load: 980N</p>										




Main material and finish: Mirror polishing stainless steel handle


Performance parameter:

Performance parameters

Maximum static load: 850N



ERP LS519S4A105001



ERP LS521N00178001

LS521

Main material and finish: Black ABS

Performance parameter:
Maximum static load: 1050N

LS523

Main material and finish: Bright chrome plated ZDC

Performance parameter:
Maximum static load: 400N



Main material and finish: Black ABS

Performance parameter:


Maximum static load: 1050N




Main material and finish: Bright chrome plated ZDC

Performance parameter:

Performance parameters



ERP LS523Z3A126001



ERP LS520N00098001




LS522

Main material and finish: Black PA

Performance parameter:

Maximum static load: 800N


Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------------	------------	---------------	-------------	-----------------	-------------



ERP

LS522N00150001


LS522-2



ERP


LS522N00150002

LS522-3



ERP

LS522N00123001




Main material and finish: Bright chrome plated steel

Performance parameter:

Maximum static load: 2595N

ERP LS531F3A100001



Main material and finish: Grey PC

Performance parameter:

Maximum static load: 500N


ERP LS532N00000001

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	----------	------------	-----------------	---------	-----------	-------	-------------



LS537-3

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------	---------------	-------------	-----------------	-------------




ERP

LS537N00000004




LS539

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
-------------	-------	-----------	---------	-----------------	------------	------------	---------------	-------------	-----------------	-------------



ERP

LS539A4C086001



	LS546-Z LH	LS546-Y RH
ERP	LS546Z2A266001	LS546Z2A266002




Main material and finish: Black painted ZDC housing, PVC packed steel pipe
Application: unlock the hook by the swing handle, different hook installation position for the left and right handle


Performance parameter:
Maximum static load: 1000N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

DOOR STOP SERIES




Remark: change the fitting direction of the keeper to suit RH or LH application



Remark: change the fitting direction of the keeper to suit RH or LH application

Example of application



Specification	Model	ERP	Model	ERP
LH	TX80-1-Z	TX080F3A001	TX80-2-Z	TX080F3A005
RH	TX80-1-Y	TX080F3A002	TX80-2-Y	TX080F3A006




Main material and finish: Bright chrome plated steel body

Hinge	Door stop
Seal gasket	


TX90-1



Main material and finish: Bright chrome plated steel



Example of application




ERP	TX90-1-Z LH	TX90-1-Y RH
	TX090F3A001	TX090F3A002


TX90-3



Main material and finish: Chrome plated steel



ERP	TX090F3A011





TX90-2



Main material and finish: Bright chrome plated steel

ERP	TX90-2-Z LH	TX90-2-Y RH
	TX090F3A008	TX090F3A009



TX91




Main material: Stainless steel

ERP	TX91-1-Z LH	TX91-2-Y RH
	TX091S00002	TX091S00001



TX92-2

Main material: Stainless steel



ERP

TX092S00002



TX100-B



Handles

Door stop

Hinge

Seal gasket


Main material and finish: Bright chrome plated steel body, bright chrome plated steel body, locking screw and ZDC knob




ERP

TX100F3A001


TX101-1



TX101-2



Different states of telescopic cover stay



Remark: Extension rod retracts only when fully extended

Specification	Model	ERP
L=145	TX101-1	TX101F3D001
L=217	TX101-2	TX101F3D002

TX101-2

TX101-1



Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

Panel lock

Toggle and hook

Handles


Door stop

Hinge

Seal gasket

HINGE SERIES

Hinge calculation instructionsv



Hinge calculation formula:

No. of hinge=n, door width = A; door height = B; door weight = G; hinge installation distance = L

Axial force Fy analysis:

$$F_y = G * 1/n$$

That is, $F_{y1} + F_{y2} + F_{y3} = G$ $F_{y1} = F_{y2} = F_{y3} = G/n$

Radial force Fx analysis:

As pic shows, F_{x2} and center door weight G at the same height position,

This horizontal force is not applied to the center hinge $F = 0$;

So: $F_{x2}=0$

$$W = G * A/2 = L * F_x$$

$$F_x = F_{x1} = F_{x3}$$

$$F_{x1} = F_{x3} = G * A/2 L$$

Remark: while Selection, every hinge can support bearing door weight; in static conditions, the selection can be based on catalog data;
Above for the theoretical calculation formula;

CL103	CL104	CL105	CL106	CL108	CL109	CL111-2	CL115	CL116	CL117	CL119
CL121	CL123	CL124	CL125	CL126	CL127	CL128	CL132	CL133	CL135	CL137
CL138	CL139	CL142	CL145	CL148	CL150	CL152	CL152-2	CL154	CL156	CL158
CL158-2	CL163	CL167	CL173	CL178	CL201-1	CL202-1	CL203-1	CL203-2	CL203-4	CL204-1
CL204-3	CL204-3S	CL204-3F	CL205-1	CL206-1	CL207	CL208	CL210	CL209	CL211	CL212
CL213-1	CL214	CL215	CL218	CL219	CL220	CL221	CL222	CL223	CL225-3	CL225-5
CL226	CL226-1K	CL226-8	CL228	CL229-2A	CL230	CL231-1	CL232	CL233	CL234	CL235
CL237	CL237-3	CL238	CL240-1	CL244	CL246	CL247	CL248	CL249	CL250-1	CL250-6
CL251	CL253-1	CL253-2	CL253-5	CL253-6	CL253-9	CL253-10	CL254	CL257	CL260	CL261
CL263	CL264	CL266	CL268	CL269	CL272	CL273	CL274	CL275-1	CL276	CL280
CL281	CL282-1	CL283	CL289	CL290	CL293	CL295	CL296	CL297	CL331	CL332

The image contains four technical drawings:

- A top-left view of a cylindrical component with a central threaded rod and a spring. Dimensions shown are: height 16.6, diameter $\varnothing 5$, and a shoulder diameter M6.
- A top-right view of a similar component with a flared end. Dimensions shown are: outer diameter $\varnothing 4.1$, shoulder height 1.4, total height 15.5, and a base height of 8.2.
- A bottom-left view of a rectangular component with a central slot and a protrusion. Dimensions shown are: width 48, slot width 25.7, slot depth 3.2, and height 18.7.
- A bottom-right view of a curved pipe assembly. Dimensions shown are: overall height 21, inner radius 14.5, outer radius 8.5, and a countersunk hole of $\varnothing 5.2$ at 10x90°. A thickness Ts=2 is indicated.
- A separate drawing labeled "Door cutout" showing a U-shaped cutout with dimensions: height 17.5^{-0.5}, width 13^{+0.5}, and a shoulder angle of 13°.
- A bottom-right perspective view of a housing or bracket with a central vertical pipe and two horizontal supports.

The top left drawing shows a front view of a door handle assembly with dimensions: height 26, width 22, thickness 4, and two holes of diameter 0.4. The top right drawing is a 3D perspective view of the handle installed on a door. The bottom left drawing shows an exploded view of the handle's internal mechanism with dimensions: frame height 25, handle length 32, door thickness 2, and a lever arm length of >7. A 90° rotation arrow indicates the lever's range of motion. The bottom right drawing is a side view of the handle's internal cylinder with a diameter of 0.4 and a bore of 0.6.

ERP

CL105F3D001

The top drawing shows a cross-section of a locking mechanism with a central cylinder of diameter 0.4. It features a positioning pin on the left (LH) and a pull pin on the right (RH). The distance between the pins is 22, and the total height is 5.5. The right side shows two door panels labeled CL106-Z and CL106-Y. The bottom drawing is a detailed view of the cylinder's internal mechanism, showing a spring, a central rod, and a base plate with mounting holes. Key dimensions include a height of 5.2, a base width of 11, a base height of 18, a central rod height of 1.5, a central rod width of 60, a central rod thickness of 80, and a total base width of 96.

ERP

CL106Z3I001



CL108



Main material and finish: Black PA hinge, and nickel plated stainless steel pin


Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 800N

Axial load: 600N



ERP

CL108N00001



CL108-2

Main material: steel hinge

Finish: black powder coated


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 3000N

Axial load: 3000N



ERP

CL108F1A001



ERP

CL109-Z Left hinge

CL109-Y Right hinge

CL109Z1A002

CL109Z1A001



CL109



Main material and finish: Black powder coated ZDC hinge and stainless steel screw

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 2500N

Axial load: 2500N



CL109-2



Main material: ZDC hinge, stainless steel pin, PTFE gasket


Finish: black powder coated

Performance parameter:

Maximum static load

Radial load: 1800N

Axial load: 1600N



ERP

CL109Z1B001



Accessories



Electronic lock



Handle lock



Cylinder lock



Plane lock



Rod lock



Panel lock



Toggle and hook



Handles



Door stop



Hinge



Seal gasket



CL111


Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



Main material and finish: 3+ zinc plated ZDC hinge and stainless steel pin
Application: When the gap between door and frame is 3mm, opening angle 110°


Performance parameter:

Maximum static load
Radial load: 775N
Axial load: 1000N



ERP

CL111Z3D001



ERP

CL111F00004



CL111-3-1D



Main material and finish: steel hinge, stainless steel pin
Application: opening angle 180°
Finish: soak anti-rust oil

Performance parameter:

Maximum static load
Radial load: 450N
Axial load: 2000N



CL111-2


Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



Main material and finish: steel hinge, stainless steel pin
Application: opening angle 180°
Finish: soak anti-rust oil



Performance parameter:

Maximum static load
Radial load: 1500N
Axial load: 2000N



ERP

CL111F00001



CL114



Main material and finish: 3+ zinc plated steel hinge
Application: Opening angle 90°

Performance parameter:

Maximum static load
Radial load: 110N
Axial load: 105N


Hinge	Seal gasket

CL115



Main material and finish: Mirror polishing stainless steel hinge
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 530N
Axial load: 800N



ERP


CL115S4A001

CL116



Main material and finish: Black powder coated ZDC hinge and steel shaft
Application: Opening angle 180°


Performance parameter:
Maximum static load
Radial load: 1000N
Axial load: 450N



Door cutout

ERP

CL116Z1A001



ERP

CL117F3D001

CL117



Main material and finish: White zinc-plated steel hinge and shaft

Performance parameter:
Maximum static load
Radial load: 3000N
Axial load: 3000N

CL119



Main material and finish: Black powder coated ZDC hinge and nickle-plated steel shaft

Performance parameter:
Maximum static load
Radial load: 280N
Axial load: 930N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock


Toggle and hook

Handles

Door stop

Hinge

Seal gasket



ERP

CL119Z1B001



CL121




Main material and finish: Black powder coated ZDC hinge and 3+ zinc plated steel pin

Performance parameter:

Maximum static load


Radial load: 980N

Axial load: 1500N



ERP

CL121Z1A001



ERP

CL125F3D001



CL125



Main material and finish: White zinc-plated steel hinge and pin

Application: Opening angle 110°

Performance parameter:

Maximum static load

Radial load: 450N

Axial load: 850N



CL123




Main material and finish: Black powder coated aluminum alloy hinge and nickel-plated steel shaft

Performance parameter:

Maximum static load


Radial load: 1200N

Axial load: 1500N



ERP

CL123A1A001



ERP

CL126F3A001



CL126

Main material and finish: Bright chrome-plated ZDC hinge and nickle-plated steel shaft

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1290N

Axial load: 1600N





CL127-1
CL127-2





Main material and finish: Mirror polishing stainless steel hinge and pin
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 3145N



Axial load: 3000N



CL127-1

ERP




CL127S4A002



CL127-2

ERP

CL127S4A003



CL128



Main material and finish: 3+ zinc plated steel hinge and pin
Application: Opening angle 90°



Performance parameter:

Maximum static load

Radial load: 160N

Axial load: 140N

ERP CL128F3D001



CL128-2



Main material and finish: 3+ zinc plated steel hinge and pin

Performance parameter:

Maximum static load

Radial load: 375N

Axial load: 305N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

Seal gasket	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------	---------	-----------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

The image contains four technical drawings of door lock components:

- CL129F3D001:** A top-down view of a lock mechanism with dimensions: total width 85.7, height 72, thickness 5.4, internal slot width 60, and internal slot length 80. It features two mounting holes of diameter $\varnothing 4$.
- CL129F3D001:** A side view of the lock mechanism with a central shaft of diameter $\varnothing 5$ and a total height of 23.2.
- CL130F3D001:** A front view of the lock mechanism with a central shaft of diameter $\varnothing 5$, a total width of 65, and a central slot of width 30 and height 50.
- CL130F3D001:** A detailed view showing the lock's installation into a door frame. The door has a thickness of 23.8 and a hinge hole diameter of $\varnothing 6$. The lock is mounted on a frame with a thickness of 14. The lock body has a height of 20.2, a width of 14.5, and a depth of 13.5. The handle is located at a height of 13.4 from the bottom of the lock body. The handle is labeled "Door" and the frame is labeled "Frame".

Front View Dimensions:

- Total height: 90
- Width: 36
- Top hole diameter: Ø5
- Side holes: 4-Ø5.5

Side View Dimensions:

- Total width: 30
- Total height: 25.5
- Total depth: 35
- Bottom hole diameter: Ø3
- Top hole diameter: Ø17
- Side hole diameter: Ø10
- Side slot width: 18
- Side gap: 13
- Side height: 20.5
- Side width: 17
- Side angle: 120°

3D Perspective View:

ERP

CL132A4D001

Front View Dimensions:

- Total height: 59
- Total width: 25
- Side gap: 8
- Top gap: 2.5
- Bottom hole diameter: Ø6 (Split washer)
- Bottom base diameter: Ø8

Side View Dimensions:

- Total height: 43
- Total width: 8
- Top gap: 4.5

3D Perspective View:

ERP

CL133F3D001

CL132



Main material and finish: Sand-spraying aluminum alloy hinge, stainless steel pin
Application: Opening angle 120°


Performance parameter:

Maximum static load

Radial load: 800N

Axial load: 425N

CL133



Main material and finish: White zinc-plated steel hinge leaf and shaft
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1450N


Axial load: 2000N

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
	CL132-2										



Main material and finish: Electrolytic stainless steel hinge
Application: Opening angle 90°

Plane lock
Cylinder lock
Handle lock
Electronic lock
Accessories




ERP CL132S9C001

Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories




Main material and finish: Color zinc-plated ZDC hinge and pin
Application: Opening angle 115°

Performance parameter:
Maximum static load
Radial load: 1000N
Axial load: 720N




ERP CL133Z3C001


Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket




ERP CL135F2A001



ERP CL135F2A002



ERP CL135F2A003



ERP CL135F2A004




Main material and finish: Black painted steel hinge

Hinge	Seal gasket

	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock
CL137						

Main material and finish: White zinc-plated steel hinge and pin
Application: Opening angle 135°

Performance parameter:
Maximum static load
Radial load: 520N
Axial load: 375N




	CL137-Z Left hinge	CL137-Y Right hinge
ERP	CL137F3D001	CL137F3D002

	CL138-3-Z	CL138-3-Y
ERP	CL138F3D004	CL138F3D005

	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
CL138						

Main material and finish: 3+ zinc plated steel hinge and pin
Application: Opening angle 135°

Performance parameter:
Maximum static load
Radial load: 690N
Axial load: 630N



ERP	CL138F3D001
-----	-------------

	CL139
ERP	CL139F3D001

	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
CL139						


Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
	CL142										




INOX
AISI
3..

Main material and finish: Mirror polishing stainless steel hinge
Application: Opening angle 135°

Performance parameter:
Maximum static load
Radial load: 2170N
Axial load: 3000N



ERP CL142S4A001



ERP CL148N00001

Hinge	Seal gasket	Panel lock	Toggle and hook	Handles	Door stop




Main material and finish: White zinc-plated steel shaft, PA (black) hinge leaf
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 220N
Axial load: 450N




Main material and finish: 3+ zinc plated steel hinge and shaft

Performance parameter:
Maximum static load
Radial load: 495N
Axial load: 545N



ERP CL145F3D001



ERP CL150F3D001



CL152



Main material and finish: Electrolytic stainless steel hinge and pin


Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 620N

Axial load: 1170N



ERP

CL152S9C001



CL152-2



Main material and finish: Electrolytic stainless steel hinge and shaft


Application: Opening angle 180°

Performance parameter:

Maximum static load




Radial load: 620N

Axial load: 1170N




ERP


CL152S9C002



Frame cutout



Door cutout



CL154



Main material and finish: Blue-gray (RAL 7012) powder coated ZDC hinge and stainless steel shaft

Application: Opening angle 135°

Performance parameter:

Maximum static load

Radial load: 2500N

Axial load: 2200N


Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket
-------------	-----------------	-------------	---------------	------------	------------------	------------	-----------------	---------	-----------	-------	-------------

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

CL154-3



NEW



ERP

CL154Z1D002

Main material: ZDC hinge, stainless steel pin, steel board

Finish: RAL7012 powder coated


Application: Opening angle 130°

Performance parameter:

Maximum static load

Radial load: 2000N

Axial load: 2000N



ERP

CL156S4A001

CL156-2



Main material: stainless steel 304

Finish: mirror polishing

Application: Opening angle 90°

Type: exposed hinge

Performance parameter:



Maximum static load

Radial load: 350N

Axial load: 450N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

CL156



Main material and finish: Sand-spraying aluminum alloy hinge, stainless steel shaft


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 620N

Axial load: 365N



ERP

CL156A4D001



ERP

CL158F3D001

CL158



Main material and finish: White zinc-plated steel hinge leaf and shaft

Performance parameter:

Maximum static load

Radial load: 3000N

Axial load: 2500N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

CL158-2



Main material and finish: Wiredrawing stainless steel hinge leaf, stainless steel shaft



Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1500N

Axial load: 1200N



ERP CL158S4B001

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Panel lock	Toggle and hook	Handles	Door stop	Panel lock	Panel lock

CL158-3



Main material and finish: stainless steel(brushed polishing) hinge,steel pin


Application: Opening angle 180°

Performance parameter:



Maximum static load

Radial load: 1730N


Axial load: 2000N



ERP CL158S4B002



Model	ERP	specification				
		A	B	C	D	E
CL158-4	CL158S4B003	62	81.2	101	Φ7.2	Φ10.5
CL158-5	CL158S4B004	37	56.2	76	Φ6.6	Φ10



ERP CL163S4B001



Main material: stainless steel hinge and pin

Finish:brushed polishing

Application: reset hinge, opening angle 180°

Performance parameter:

Reset torque 2N.m



Main material and finish: Wiredrawing stainless steel hinge leaf and shaft

Performance parameter:

Maximum static load

Radial load: 1300N

Axial load: 1180N




CL167




Main material and finish: White zinc-plated steel hinge leaf, white zinc-plated aluminium alloy shaft
Application: Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 210N
Axial load: 320N



ERP

CL167F3D001



ERP

CL168S4A001




CL168




Main material and finish: White zinc-plated steel hinge leaf and shaft

Performance parameter:
Maximum static load
Radial load: 200N
Axial load: 330N



ERP

CL168F3D001



ERP

CL169Z3D001



CL168-2

NEW



Main material: stainless steel 304
Finish:mirror polishing
Application:Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 290N
Axial load: 540N



CL169



Main material and finish: White zinc-plated ZDC female hinge, steel male hinge and shaft

Performance parameter:
Maximum static load
Radial load: 700N
Axial load: 500N



Hinge

Seal gasket

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories





Main material and finish: Zinc-plated steel hinge and pin

Performance parameter:

Maximum static load


Radial load: 800N

Axial load: 600N



ERP

CL170F3D001



ERP

CL178F3D001



Main material: steel hinge and pin
Finish:zinc plated

Performance parameter:

Maximum static load

Radial load: 1280N

Axial load: 1170N




Main material and finish: Wiredrawing stainless steel hinge

Performance parameter:

Maximum static load


Radial load: 2000N

Axial load: 1500N



ERP

CL173S00001



ERP

CL179S4B001

Hinge	Seal gasket

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Rod control lock	Handle lock	Cylinder lock	Plane lock	Electronic lock	Accessories

CL180






Main material and finish: Magnetic force polishing SUS304 stainless steel hinge

Performance parameter:

Maximum static load


Radial load: 705N

Axial load: 400N



ERP

CL180SXX001



ERP

CL186S9C001

CL186



Main material and finish: Electrolysis stainless steel hinge leaf and shaft

Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 660N

Axial load: 800N

Hinge	Panel lock	Toggle and hook	Handles	Door stop	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Panel lock	Seal gasket

CL181





Main material and finish: White zinc plated steel hinge leaf and stainless steel shaft

Performance parameter:

Maximum static load


Radial load: 5000N

Axial load: 420N



ERP

CL181F3J001



ERP

CL188FXX001

CL188



Main material and finish: Phosphating 45# steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 3000N

Axial load: 3000N

Hinge	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

CL190



Accessories





Main material and finish: White zinc plated steel hinge

Performance parameter:

Maximum static load



Radial load: 365N

Axial load: 255N



ERP

CL190F3D001



ERP

CL195Z2A002

CL195-3



Main material and finish: Black painted ZDC hinge

Application: Opening angle 90°

Performance parameter:

Maximum static load

Radial load: 800N

Axial load: 650N

CL195






Panel lock







Main material and finish: Black POM hinge and steel shaft

Application: Opening angle 150°



ERP

CL195N00001



ERP

CL196N00001

CL196



Main material and finish: Black POM hinge

Remark: Special self tapping screw included

Performance parameter:

Maximum static load

Radial load: 80N

Axial load: 255N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Seal gasket

Hinge

Door stop

Handles

Toggle and hook

Panel lock

Plane lock

Rod control

lock

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

lock

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

lock

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

lock

Accessories



CL201-1






Main material and finish: ZDC hinge, steel pin, accessory

Performance parameter:


Maximum static load

Radial load: 800N

Axial load: 1500N



Remark: \geq size is 3.7, door's open angle is 90 degree.



ERP

CL200Z2C001



CL200-1

NEW

Main material and finish: Black painted ZDC hinge



Application: Opening angle 90°

Performance parameter:


Maximum static load

Radial load: 300N


Axial load: 250N



"U" shape accessory
ERP: 3452011001 (white zinc plating)




Claw shape accessory
ERP: 3452011002 (white zinc plating)



Pipe shape accessory
ERP: 3452011013 (white zinc plating)

Specification	CL201-1	CL201-1A	CL201-1B
Black powder coated	CL201Z2A002	CL201Z2A032	
Nanometer painted	CL201Z2B002	CL201Z2B017	
Blast sprayed	CL201Z4D002	CL201Z4D004	
SUS			CL201S4B001

Remark: Accessory is not included in above ERP number, but optional



	Black powder coated	Nanometer painted	Blast sprayed
ERP	CL201Z2A006	CL201Z2B004	CL201Z4D007

Remark: Accessory is not included in above ERP number, but optional.



CL201-2

Main material and finish: ZDC hinge, steel pin and accessories

Performance parameter:

Maximum static load

Radial load: 360N

Axial load: 460N



Pipe shape accessory
ERP: 3452013002
(White zinc plating)

"U" shape accessory
ERP: 3452011001 (white zinc plating)

Pipe shape accessory
ERP: 3452011013 (white zinc plating)

Claw shape accessory
ERP: 3452011002 (White zinc plating)

	Black powder coated	Nanometer painted	Blast sprayed
ERP	CL201Z2A011	CL201Z2B008	CL201Z4D009

Remark: Accessory is not included in above ERP number, but optional




CL201-6




Main material and finish: ZDC hinge, steel pin and accessories
Application: Opening degree 90°

Performance parameter:

Maximum static load
Radial load: 900N
Axial load: 980N



Accessory
ERP: 3452016002
(White zinc plating)



Remark: ≥size is 2.7, door's open angle is 90 degree.

	Nanometer painted	Blast sprayed
ERP	CL201Z2B001	CL201Z4D021

Remark: Accessory is not included in above ERP number, but optional.


CL201-9




Main material and finish: Blast sprayed ZDC hinge leaf and steel pin.
Application: Opening angle 120°

Performance parameter:

Maximum static load
Radial load: 500N
Axial load: 800N



Specification	With washer	Without washer
ERP	CL201Z4D064	CL201Z4D067



CL201-12




Main material and finish: Nanometer painted ZDC hinge leaf, steel pin
Application: Opening angle 100°

Performance parameter:

Maximum static load
Radial load: 900N
Axial load: 2000N

Specification	With SJ logo	Without SJ logo
ERP	CL201Z2B021	CL201Z2B022




CL202-1



Main material and finish: ZDC door-part, steel frame-part and pin
Application: Opening degree 180°

Performance parameter:

Maximum static load
Radial load: 280N
Axial load: 390N



Specification	Black Powder Coated	Nanometer painted
ERP	CL202Z1A001	CL202Z2B001



CL202-2



Main material and finish: ZDC door-part, steel frame-part, pin and screw

Application: Opening degree 180°


Performance parameter:

Maximum static load

Radial load: 560N

Axial load: 520N

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories



ERP	Matt black powder coated	Malachite green powder coated	Pocked black powder coated
	CL202Z1A002	CL202Z1F006	CL202Z1B001



CL203-2B



Main material and finish: ZDC hinge PA bushing

Application: Opening degree 180°


Performance parameter:

Maximum static load


Radial load: 600N

Axial load: 1500N

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories




ERP	Black powder coated	Bright chrome plated
	CL203Z1A007	CL203Z3A005




CL203-1

Offset hinge



CL203-2

Coaxial hinge



CL203-3


Symmetric hinge



CL203-1



CL203-2



Main material and finish: ZDC hinge PA bushing

Application: Opening degree 180°

Performance parameter:

Maximum static load

Model: CL203-1

Radial load: 490N Axial load: 570N

Model: CL203-2

Radial load: 650N Axial load: 1550N

Model: CL203-3

Radial load: 3300N Axial load: 880N

Specification	Model	ERP		
		Matt black powder coated	Pocked black powder coated	Nanometer painted
Coaxial hinge	CL203-2	CL203Z1A003	CL203Z1B004	CL203Z2B003
Offset left hinge	CL203-1-Z	CL203Z1A001	CL203Z1B001	CL203Z2B001
Offset right hinge	CL203-1-Y	CL203Z1A002	CL203Z1B002	CL203Z2B002
Symmetrical left hinge	CL203-3-Z	CL203Z1A008		CL203Z2B004
Symmetrical right hinge	CL203-3-Y	CL203Z1A009	CL203Z1B015	CL203Z2B005

Hinge	Seal gasket

CL203-4



Accessories Electronic lock Handle lock Electronic lock Accessories





Main material and finish: ZDC hinge
Application: Opening angle 180°

Performance parameter:



Maximum static load

Radial load: 270N




Axial load: 730N



RH



Specification	Model	ERP	
		Black powder coated	Nanometer painted
Left hand	CL203-4-Z	CL203Z2A001	CL203Z2B006
Right hand	CL203-4-Y	CL203Z2A002	CL203Z2B007



CL204-1



Main material and finish: ZDC hinge
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 980N

Axial load: 2800N

CL203-7



Accessories Electronic lock Handle lock Electronic lock Accessories







Main material and finish: Wiredrawing polishing stainless steel hinge
Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 1295N

Axial load: 2240N





ERP


CL203S4B001



CL204-2



CL204-3



**CL204-2
CL204-3**



Main material and finish: Steel hinge leaf and stainless steel cover
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1800N

Axial load: 2900N

ERP	CL204-2 Fixed with screw	CL204-2 Welding
	CL204S00001	CL204S9C001

Accessories Electronic lock Handle lock Cylinder lock

Electronic lock Handle lock Cylinder lock

Plane lock Cylinder lock

Plane lock Rod control

Panel lock Toggle and hook Handles

Handles Door stop

Hinge Seal gasket

Seal gasket



CL204-3C

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Plane lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Accessories



Main material and finish: Bright chrome-plated ZDC hinge





Application: Opening angle 180°

Performance parameter:

Maximum static load




Radial load: 1000N

Axial load: 1800N



ERP

CL204Z3A002



ERP

CL204Z3A007

CL204-3F

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



Main material and finish: Bright chrome-plated ZDC hinge

Application: Opening angle 180°

CL204-3D

Hinge	Handles	Panel lock	Toggle and hook	Door stop	Seal gasket



Main material and finish: Bright chrome-plated ZDC hinge





Application: Opening angle 180°

Performance parameter:

Maximum static load




Radial load: 2150N

Axial load: 2630N



ERP

CL204Z3A003



ERP

CL204S4A013

CL204-3K

Hinge	Handles	Door stop	Seal gasket

Main material and finish: Mirror polishing stainless steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 2000N

Axial load: 1530N

CL204-3S



Accessories


Electronic lock

Handle lock


Cylinder lock

Plane lock

Rod control lock



CL204-3S-2



Main material and finish: SUS304, wiredrawing polishing
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 1700N
Axial load: 2200N

CL204-4D



Panel lock


Toggle and hook

Handles


Door stop

Hinge

Seal gasket






CL204-3S-1







ERP	CL204S4B002	CL204S4B003
-----	-------------	-------------

Main material and finish: Bright chrome plated ZDC exposed hinge
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 1500N
Axial load: 2000N



ERP	CL204Z3A013
-----	-------------



CL204-7






Main material and finish: Mirror polishing SUS304 stainless steel hinge

Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 1500N
Axial load: 2000N

ERP	CL204S4A020
-----	-------------



CL205-1



Main material and finish: ZDC hinge
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 917N
Axial load: 710N

Specification	Model	ERP	
		Black powder coated	Pocked black powder coated
Left hand	CL205-1-Z	CL205Z1A001	CL205Z1B001
Right hand	CL205-1-Y	CL205Z1A002	CL205Z1B002

The image contains several technical drawings and 3D assembly diagrams:

- Top Left:** A cross-sectional view of a door handle component. Dimensions include: overall height 26, handle height 20, base thickness 6, gap Ts=2, handle width 3.5, handle thickness 3, base height 12.5, and base width 20. A note indicates a 180° rotation range.
- Top Right:** A side view of a handle assembly. Dimensions include: total width 25, handle diameter 2-Ø10, base height 2, base diameter Ø5.5, base thickness Ø4, and base width Ø5. A note indicates a 25 mm distance from the base to the center of the handle.
- Middle Left:** A 3D view of a "Door cutout" showing a rectangular slot with a height of 25, a thickness of 9.5, and two holes with a diameter of 2-Ø10.2.
- Middle Center:** A 3D view of a "LH" handle assembly.
- Middle Right:** A 3D view of a "RH" handle assembly.
- Bottom Left:** A cross-sectional view of a handle component with a central slot. Dimensions include: overall height 31, slot height 23, slot width 18, slot depth 8.5, and a 180° rotation range. Labels indicate an M8 screw at the top and an M10 nut at the bottom.
- Bottom Right:** A side view of a handle assembly. Dimensions include: total height 50, handle height 31, handle width 26, base width 42, and base thickness 56. A note indicates a 2-M8 hole.
- Bottom Center:** A 3D view of a handle assembly installed in a door panel.

	Pocketed black powder coated	Black painted	Bright chrome plated
ERP	CL206F1B001	CL206F2A001	CL206F3A008

CL206-2

Chain material and finish: ZDC hinge, steel pin

Application: Opening angle 180°

Performance parameter:

maximum static load

radial load: 1200N

axial load: 1000N

CL206-3

Chain material and finish: Bright chrome plated steel hinge and gasket

Application: Opening angle 180°


Performance parameter:

maximum static load

radial load: 2000N

axial load: 1500N

CL206-3B



Main material and finish: ZDC hinge
Application: Opening angle 180°






Performance parameter:

Maximum static load

Radial load: 2000N

Axial load: 1520N

Embedded screw recommended
tightening torque : 50N.m



CL206-12



NEW

Main material and finish: Wiredrawing
polishing SUS316 stainless steel hinge
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1500N

Axial load: 2000N

	Black painted	Bright chrome-plated
ERP	CL206Z2A002	CL206Z3A011

ERP	CL206S4B002
-----	-------------

CL206-4



Main material and finish: ZDC hinge,
steel pin







Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1200N

Axial load: 1000N



CL207



Main material and finish: White zinc-plated steel hinge

Application: Opening angle 90°

Performance parameter:

Maximum static load

Radial load: 170N

Axial load: 190N

	Black powder coated	Bright chrome-plated
ERP	CL206Z1A003	CL206Z3A012

ERP	CL207F3D001
-----	-------------

CL208



Main material and finish: ZDC hinge, steel support and screw


Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 240N

Axial load: 520N



ERP	Matt black powder coated	Nanometer painted	Bright chrome-plated
	CL208Z1A001	CL208Z2B001	CL208Z3A001

CL209-1C



Main material and finish: Nanometer painted ZDC hinge, stainless steel shaft and screw

Application: Opening angle 180°



Performance parameter:

Maximum static load

Radial load: 1800N

Axial load: 1350N

Embedded screw recommended tightening torque : 9N.m



ERP	CL209Z2B004
-----	-------------

CL209-1



CL209-2



Main material and finish: ZDC hinge and steel pin

Application: Opening angle 180°



Performance parameter:

Maximum static load



Radial load: 1500N

Axial load: 1800N

Embedded screw recommended tightening torque : 10N.m



CL209-1



CL209-2

Specification	ERP	
	CL209-1	CL209-2
Bright chrome-plated	CL209Z3A001	CL209Z3A002
Matt black powder coated	CL209Z1A001	CL209Z1A015
Pocked black powder coated	CL209Z1B001	CL209Z1B002
Nanometer painted	CL209Z2B001	CL209Z2B006




Main material and finish: ZDC hinge, steel pin, PA gasket set
Application: Opening angle 110°

Performance parameter:

Maximum static load
Radial load: 720N
Axial load: 830N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



	Matt black powder coated	Nanometer painted
ERP	CL210Z1A001	CL210Z2B001




Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°


Performance parameter:

Maximum static load
Radial load: 1500N
Axial load: 1800N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



Specification	A	Model	ERP
Suitable door thickness, Ts=1.5mm	4.6	CL211-1	CL211Z1A001
Suitable door thickness, Ts=2mm	5.1	CL211-2	CL211Z1A010




Specification	A	Model	ERP
Suitable door thickness, Ts=2mm	5.1	CL212-1	CL212Z1A001
Suitable door thickness, Ts=3mm	6.1	CL212-2	CL212Z1A003
Suitable door thickness, Ts=1.5mm	4.6	CL212-3	CL212Z1A004



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°

Performance parameter:

Maximum static load
Radial load: 1050N
Axial load: 980N



ERP	Specification	A
CL212Z1A007	Suitable door thickness, Ts=2mm	5.1
CL212Z1A008	Suitable door thickness, Ts=3mm	6.1
CL212Z1A009	Suitable door thickness, Ts=1.5mm	4.6



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°

Performance parameter:

Maximum static load
Radial load: 1050N
Axial load: 980N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

CL212-F



Accessories
Electronic lock
Handle lock
Cylinder lock
Plane lock

Rod control
lock

Panel lock





Toggle and
hook

Handles






Door stop

Hinge

Seal gasket




Specification	A	ERP
Suitable door thickness Ts=1.0mm	4.4	CL212N00001
Suitable door thickness Ts=1.5mm	5.1	CL212N00002



ERP CL213Z1A001

CL212-3A




Toggle and
hook


Handles

Door stop


Hinge



Frame cutout



Optional nylon pin






Part No.	L
PN001	57
PN002	78

Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 1050N
Axial load: 980N

ERP	Specification	A
CL212Z1A002	Suitable door thickness, Ts=2mm	5.1
CL212Z1A005	Suitable door thickness, Ts=3mm	6.1
CL212Z1A006	Suitable door thickness, Ts=1.5mm	4.6



ERP	Black powder coated	Pocked black powder coated
CL213Z1A003		CL213Z1B002

CL213-1



Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control

CL213-2



Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Main material and finish: ZDC hinge, brass gasket and steel pin
Application: Opening angle 180°





Performance parameter:
Maximum static load
Radial load: 575N
Axial load: 1030N

CL213-3



Main material and finish: ZDC hinge, PA shaft
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 670N
Axial load: 255N






	Black powder coated	Pocket black powder coated
ERP	CL213Z1A004	CL213Z1B003

CL213-6





Main material and finish: Black powder coated hinge, brass washer and steel pin
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 1225N
Axial load: 775N



ERP	CL213Z1A007
-----	-------------






ERP	CL213ZXX003
-----	-------------

CL213-7



Main material and finish: Powder coated ZDC half-concealed hinge
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 680N
Axial load: 1225N



CL213-9



Main material and finish: Orange-peel (RAL7035) powder coated ZDC hinge leaf and stainless steel pin

Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 320N
Axial load: 350N

Hinge	Handles	Toggle and hook	Panel lock	Door stop	Seal gasket
-------	---------	-----------------	------------	-----------	-------------

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock
-------------	-----------------	-------------	---------------	------------	----------

CL214



Main material and finish: ZDC hinge and steel pin



Application: Opening angle 180°

Performance parameter:




Maximum static load

Radial load: 1125N

Axial load: 1490N



Specification	ERP	
	CL214-1	CL214-2
Bright chrome-plated	CL214Z3A001	CL214Z3A002
Matt black powder coated	CL214Z1A001	CL214Z1A003
Pocked black powder coated	CL214Z1B001	CL214Z1B002
Nanometer painted	CL214Z2B001	CL214Z2B002



Frame cutout

CL216



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 570N

Axial load: 480N

CL215



Main material and finish: White zinc plated steel hinge, PA washer




Application: Opening angle 180°

Performance parameter:




Maximum static load

Radial load: 750N


Axial load: 850N



ERP CL215F3D001



Door cutout



Frame cutout

CL217



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 550N

Axial load: 470N

Seal gasket

Hinge

Handle

Panel lock

Toggle and hook

Door stop

Plane lock

Cylinder lock

Handle lock

Electronic lock

Accessories

Seal gasket

Hinge

Handles

Door stop

Toggle and hook

Panel lock

Rod control

Plane lock

Cylinder lock

Handle lock

Electronic lock

Accessories

CL218



Main material and finish: White zinc-plated steel hinge


Application: Opening angle 90°

Performance parameter:


Maximum static load

Radial load: 570N


Axial load: 780N



CL218-1



CL218-2



CL218-3

ERP


CL218F3D001

ERP



CL218F3D002

ERP

CL218F3D003



O-ring seals onto the screw holes will be provided if required



CL219



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin

Application: Opening angle 180°

Performance parameter:
Maximum static load

Model: CL219-1

Radial load: 1000N

Axial load: 1200N

Model: CL219-2

Radial load: 600N

Axial load: 460N

Model: CL219-3

Radial load: 700N

Axial load: 800N

ERP	Specification													
	Structure	A	B	C	D	E	F	G	H	J	K	L	M	
CL219Z1A001	Non-damping	8	20	M5	35	45	60	50	18	Ø8	11	14	18	
CL219Z1A005	Non-damping	4	13	M4	22	22	30	22	13	Ø5	8	10	9	
CL219Z1A007	Non-damping	4	18.5	M4	27.5	22	30	22	13	Ø5	8	10	14.5	

Hinge	Handles	Door stop	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket										

Hinge	Seal gasket

CL220



Main material and finish: Gray chrome-plated ZDC hinge, nickel-plated steel pin


Performance parameter:

Maximum static load

Radial load: 290N

Axial load: 160N

CL220



ERP

CL220Z3B001

CL222



Main material and finish: ZDC hinge, nickel-plated steel pin, PA bushing

Application: Opening angle 180°

Performance parameter:


Maximum static load

Radial load: 1675N

Axial load: 2000N

ERP


Black powder coated
Pocked black powder coated
Bright chrome-plated
Nanometer painted



ERP

CL222Z1A001
CL222Z1B001
CL222Z3A001
CL222Z2B002

CL221



Main material and finish: Nanometer painted ZDC hinge


Performance parameter:

Maximum static load

Radial load: 55N

Axial load: 75N

CL221



ERP

Specification
LH applicable
RH applicable

ERP

CL223F3D001

CL223



Main material and finish: White zinc plated steel hinge leaf

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 390N

Axial load: 1260N

Hinge

Panel lock
Toggle and hook
Handles
Door stop

Hinge

Seal gasket

ERP

CL223F3D001

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

CL225



Main material and finish: White zinc plated steel hinge leaf

Performance parameter:
Maximum static load

Model: CL225-1/1A

Radial load: 150N



Axial load: 200N

Model: CL225-2

Radial load: 100N


Axial load: 130N

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket										





Remark: Accessory (optional) This accessory is used as an alternative to the hinge with pin, usually fitted at the bottom of the door as load-bearing fixing door

LH		RL		Specification
Model	ERP	Model	ERP	
CL225-1-Z	CL225F3D001	CL225-1-Y	CL225F3D004	Standard type: white zinc plated steel hinge. A means hinge with two mounting holes, S means grinding vibration polishing stainless steel hinge.
CL225-1-S-Z	CL225S0001	CL225-1-S-Y	CL225S0002	
CL225-1A-Z	CL225F3D008	CL225-1A-Y	CL225F3D007	
CL225-1A-S-Z	CL225S0010	CL225-1A-S-Y	CL225S0011	
CL225-2-Z	CL225F3D011	CL225-2-Y	CL225F3D012	White zinc plated steel hinge with two mounting holes



ERP	LH	RH
CL225F3D022	CL225F3D019	

Exploded drawing



ERP	CL225N00001

CL225-3



Main material and finish: White zinc plated steel hinge leaf

Performance parameter:

Maximum static load

Radial load: 150N

Axial load: 250N

CL225-5



Main material and finish: Black PA hosing, white zinc-plated ZDC latch, stainless steel spring

Application: Telescopic 8mm

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket										

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket										

CL225-7



CL225-7-Y


Main material and finish: White zinc plated steel hinge leaf

Performance parameter:

Maximum static load

Radial load: 525N

Axial load: 125N



	CL225-7-Z LH	CL225-7-Y RH
ERP	CL225F3J001	CL225F3J002

CL226-4A



Main material and finish: Black powder coated ZDC hinge,nickel-plated steel pin

Application: Opening degree 180°



Performance parameter:

Maximum static load






Radial load: 1120N

Axial load: 1200N

Embedded screw recommended tightening torque : 12N.m



Model	ERP	Specification							Remark	
		A	B	C	D	E	F	G		
CL226-4-1	CL226Z1A019	90	60	36	18	44	8	8	15	Ø8.4 Countersunk hole,ZDC
CL226-4A-1	CL226Z1A020	90	60	36	18	44	8	8	15	M8 Screw embedded, ZDC
CL226-4-2	CL226Z1A021	63	50	30	15	28	6	6	11.5	Ø6.3 Countersunk hole, stainless steel
CL226-4A-2	CL226Z1A022	63	50	30	15	28	6	6	11.5	M6 Screw embedded, ZDC



CL226



CL226-1



CL226-2



CL226-3



CL226-2A

Model	ERP	Specification							Remark
		A	B	C	D	E	F	G	
CL226-1	CL226Z1A001	36	60	16.5	8.4	8	15	8	Countersunk hole,ZDC
CL226-1A	CL226Z1A006	36	60	16.5	8.4	8	15	8	Screw embedded, ZDC
CL226-1B	CL226S9C001	36	60	16.5	8.4	8	15	8	Countersunk hole,stainless steel
CL226-2	CL226Z1A009	30	50	12.5	6.3	6	11.5	6	Countersunk hole,ZDC
CL226-2A	CL226Z1A010	30	50	Refer to detailed drawing		6	11.5	6	Screw embedded, ZDC
CL226-2C	CL226Z1A011	30	50	Refer to detailed drawing		6	11.5	6	Step hole,ZDC
CL226-2S	CL226N00001	30	50	12.5	6.3	6	11.5	6	Countersunk hole,PA
CL226-2B	CL226S4B001	30	50	12.5	6.3	6	11.5	6	Countersunk hole,stainless steel
CL226-3	CL226Z1A015	25	40	10.2	5.3	5	9	4	Countersunk hole,ZDC
CL226-3A	CL226Z1A017	25	40	10.2	5.3	5	9	4	Screw embedded, ZDC

Main material and finish: Black powder coated ZDC hinge,nickel-plated steel pin
Application: Opening angle 180°

Performance parameter:

Maximum static load

Model: CL226-1

Radial load: 1500N Axial load: 1800N

Model: CL226-2

Radial load: 1200N Axial load: 1300N

Model: CL226-3

Radial load: 1000N Axial load: 1200N

Model: CL226-2A

Radial load: 1200N Axial load: 1300N

Embedded screw recommended tightening torque : 10N.m

Hinge

Seal gasket

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod lock

Panel lock

Toggle and hook

Handles

Door stop

Door stop

Handles

Panel lock

Toggle and hook

Plane lock

Rod lock

Panel lock

Toggle and hook


Handles

Door stop

Seal gasket



CL226-5A



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°


Performance parameter:

Maximum static load

Radial load: 1120N

Axial load: 1200N


Embedded screw recommended tightening torque : 12N.m



	CL226-5A-Z LH	CL226-5A-Y RH
ERP	CL226Z1A024	CL226Z1A025



CL226-6A



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°


Performance parameter:

Maximum static load


Radial load: 520N

Axial load: 210N

Embedded screw recommended tightening torque : 9N.m




ERP	CL226Z1A026
-----	-------------



Model	ERP	Specification								Remark
		A	B	C	D	E	F	G	H	
CL226-7-1	CL226Z1A028	56	76	30	50	6	11.5	6		Ø6.3 Countersunk hole, ZDC
CL226-7A-1	CL226Z1A029	56	76	30	50	6	11.5	6	12.5	M6 Screw embedded, ZDC
CL226-7-2	CL226Z1A034	88	120	36	60	8	15	8		Ø6.8 Countersunk hole, ZDC
CL226-7A-2	CL226Z1A030	88	120	36	60	8	15	8	16.5	M8 Screw embedded, ZDC

ERP	CL226F2B001
-----	-------------



CL226-7
CL226-7A



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1120N

Axial load: 1200N

Embedded screw recommended tightening torque : 12N.m



CL226-8



Main material and finish: Nanometer painted steel hinge leaf, shaft
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 3000N

Axial load: 3000N





**CL229-2A
CL229-2B**

Main material and finish: Electrolysis stainless steel hinge


Application: Opening angle 90°

Performance parameter:

Maximum static load

Radial load: 425N

Axial load: 225N



Model	ERP	Specification	
		A	B
CL229-2A-Z	CL229S9C001	50.5	64
CL229-2A-Y	CL229S9C003	50.5	64
CL229-2B-Z	CL229S9C002	56.5	68
CL229-2B-Y	CL229S9C004	56.5	68



CL230-3



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 940N

Axial load: 720N





Remark: Nylon pin optional, details refer to CL230


ERP	CL230Z1A026
-----	-------------




CL230




ERP	CL230S4B001
-----	-------------



Door cutout



Nylon pin (Optional)



Part No.	L
PN001	57
PN002	78

Model	ERP	Specification		
		Ts	A	B
CL230-1	CL230Z1A001	Ts=1.5	4.6	15
CL230-2	CL230Z1A013	Ts=2	5.1	15
CL230-1A	CL230Z1A004	Ts=1.5	4.6	17
CL230-2A	CL230Z1A016	Ts=2	5.1	17
CL230-1B	CL230Z1A007	Ts=1.5	4.6	19
CL230-2B	CL230Z1A019	Ts=2	5.1	19



CL230



Main material and finish: Wire-drawing polishing stainless steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 900N

Axial load: 700N

Hinge	Seal gasket
-------	-------------

Seal gasket




Main material and finish: Bright chrome plated ZDC hinge and steel shaft
Application: Opening angle 180°



Performance parameter:
Maximum static load
Radial load: 940N
Axial load: 720N

	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Seal gasket

CL232



ERP CL230Z3A019



ERP CL232Z3H001

CL232



Main material and finish: Sand-spraying and bright chrome-plated ZDC female hinge, white zinc-plated steel male hinge, nickel plated steel pin
Application: Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 420N
Axial load: 1050N

	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Seal gasket

CL231




Main material and finish: Bright chrome plated ZDC hinge, nickel-plated steel pin, brass gasket


Application: Opening angle 180°

Performance parameter:
Maximum static load
Model: CL231-1
Radial load: 330N **Axial load:** 760N

Model: CL231-2
Radial load: 575N **Axial load:** 125N



Model	ERP	Specification						
		A	B	C	D	E	F	G
CL231-1	CL231Z3A001	68	80	Ø8	Ø4.2	14.5	11.5	Ø6
CL231-2	CL231Z3A004	48	60	Ø9.4	Ø4.5	13	9.5	Ø5



ERP CL233S9C001

CL233



Main material and finish: Electrolysis or polishing stainless steel hinge
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 3000N
Axial load: 3000N

	Hinge	Seal gasket

CL233-2



Main material and finish: Black powder coated ZDC hinge, steel pin


Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 1000N

Axial load: 1200N



ERP

CL233Z1A001

CL234



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin




Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 1150N

Axial load: 700N



ERP

CL236Z2A001



ERP

CL236Z2B001

CL235



Main material and finish: Pocked black powder coated ZDC hinge, stainless steel screw


Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 165N

Axial load: 980N



ERP

CL235Z1B001

CL236



Main material and finish: Black painted ZDC hinge, white zinc-plated steel pin

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1250N

Axial load: 600N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

CL237





Accessories

Cylinder lock

Plane lock

Rod control lock



Main material and finish: Sand-spraying and nickel-plated ZDC female hinge, white zinc-plated steel male hinge, nickel plated steel pin

Application: Opening angle 90°



Performance parameter:

Maximum static load

Radial load: 1295N


Axial load: 290N

ERP	Sand-spraying and bright chrome-plated CL237Z3H001	Sand-spraying and nickel-plated CL237Z3I001
-----	---	--



ERP CL237Z00001

CL237-3



Main material and finish: ZDC hinge and stainless steel shaft

Application: Opening angle 122°

Performance parameter:

Maximum static load

Radial load: 560N

Axial load: 840N

CL237-2




Handles

Toggle and hook

Panel lock

Hinge

Seal gasket



Main material and finish: Griege painted (high salt mist resistant) female hinge, electrolysis male hinge and 316 stainless steel shaft

Application: Maximum opening angle 100°

Remark: Female hinge fixed with M4 screw (not provide), male hinge fixed with riveting or welding of cabinet door


Performance parameter:

Maximum static load

Radial load: 750N

Axial load: 365N

ERP CL237S2G001



ERP CL237Z1A001

CL237-4



Main material and finish: Black powder coated ZDC hinge leaf, stainless steel pin and silicone washer

Application: Opening angle 110°

Performance parameter:

Maximum static load

Radial load: 1180N


Axial load: 1540N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock
Hinge	Toggle and hook	Handles	Door stop	Panel lock	Seal gasket

Panel lock
Toggle and hook
Handles
Door stop

Hinge
Seal gasket

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket										
CL238										
CL238-1										
CL238-2										
CL238-3										
										
Main material and finish: Electrolysis stainless steel hinge Application: Opening angle 180°										
Performance parameter: Maximum static load Radial load: 520N Axial load: 600N										




ERP CL238S9C001

ERP CL238S9C002

ERP CL238S9C003

Model	ERP	Specification
CL240-1	CL240A9A001	With knurl end shaft
CL240-1D	CL240A9A002	With screw end shaft
CL240-2	CL240A9A003	With knurl end shaft
CL240-2D	CL240A9A004	With screw end shaft



Main material and finish: Oxidation aluminum alloy hinge, stainless steel shaft,nickel-plated steel pin
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 500N
Axial load: 600N


Hinge	Seal gasket

CL244



Main material and finish: White zinc plated steel hinge and pin
Application: Opening angle 120°


Performance parameter:
Maximum static load
Radial load: 270N
Axial load: 305N



ERP


CL244F3D001

CL246



Main material and finish: Sand-spraying and bright chrome-plated ZDC hinge, white zinc-plated steel pin
Application: Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 1000N
Axial load: 820N



ERP

CL246Z3H001


Model	ERP	Specification
CL248-1	CL248F3D001	White zinc plated steel
CL248-S	CL248S9C001	Electrolysis SUS316 hinge

CL247



Main material and finish: Black powder coated ZDC hinge, white zinc-plated steel pin
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 780N
Axial load: 490N



ERP

CL247Z1A001


CL248



Main material and finish: White zinc plated steel and pin

Application: Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 280N
Axial load: 250N



Main material and finish: White zinc plated steel and pin

Application: Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 280N
Axial load: 250N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Hinge	Door stop	Handles	Panel lock	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

CL249



Main material and finish: Steel or stainless steel hinge




Application: Opening angle 180°

Performance parameter:


Maximum static load

Radial load: 1200N

Axial load: 1300N




CL250-3



CL250-4

Seal gasket	Hinge	Handle	Toggle and hook	Panel lock	Door stop	Handles	Panel lock	Toggle and hook	Handles	Door stop	Hinge

**CL250-1
CL250-2**




Main material and finish: White zinc plated steel hinge and pin

Performance parameter:


Maximum static load

Radial load: 310N



Axial load: 480N



CL250-1



CL250-2



Model	ERP	Specification
CL250-1	CL250F3D001	White zinc plated steel
CL250-1B	CL250S00004	Grinding vibration polishing stainless steel
CL250-2	CL250F3D002	White zinc plated steel
CL250-2B	CL250S00003	Grinding vibration polishing stainless steel

Hinge	Seal gasket

CL251



Main material and finish: Sand-spraying and bright chrome-plated ZDC hinge, stainless shaft pin and cover


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 1200N

Axial load: 910N



ERP

CL251Z3H001



ERP

CL252S00001

CL252



Main material and finish: Stainless steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 520N

Axial load: 800N

CL251-3



Main material and finish: Bright chrome plated ZDC exposed hinge Wire-drawing polishing


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 1000N

Axial load: 1500N



ERP

CL251S4B001



ERP

CL253S4A001

CL253-1



Main material and finish: Mirror polishing stainless steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 745N

Axial load: 1090N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control
Hinge					Seal gasket

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Panel lock
Seal gasket					

	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket											

CL253-2
CL253-3



Main material and finish: Mirror polishing stainless steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load


Model: CL253-2

Radial load: 1000N **Axial load:** 1200N


Model: CL253-3

Radial load: 1500N **Axial load:** 1800N

CL253-2



CL253-3



Model	ERP	Specification
CL253-2	CL253S4A002	Stainless steel
CL253-2-A	CL253F3D012	Carbon steel
CL253-3	CL253S4A003	Stainless steel

ERP

CL253S4A003

CL253-4



Main material and finish: Mirror polishing stainless steel hinge


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 516N

Axial load: 665N



ERP

CL253S4A004



ERP

CL253S4A011

CL253-4A



Main material and finish: Mirror polishing stainless steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 380N

Axial load: 810N

CL253-5



Main material and finish: White zinc-plated steel hinge

Application: Opening angle 180°


Performance parameter:

Maximum static load

Radial load: 840N

Axial load: 1380N

	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
Seal gasket											



ERP

CL253F3D001


CL253-6



Main material and finish: Mirror polishing stainless steel hinge Magnetic Shock
Application: Opening angle 180°

Performance parameter:

Maximum static load
Radial load: 550N
Axial load: 650N



ERP

CL253S4A005


CL253-7



Main material and finish: Mirror polishing stainless steel hinge
Application: Opening angle 180°

Performance parameter:


Maximum static load
Radial load: 590N
Axial load: 635N



ERP

RH
CL253S4A006

LH
CL253S4A007



ERP

CL253-9-Z RH
CL253S4A008

CL253-9-Y LH
CL253S4A009

CL253-9



Main material and finish: Stainless steel hinge leaf and shaft
Application: Opening angle 180°

Performance parameter:

Maximum static load
Radial load: 305N
Axial load: 470N

CL253-10



Main material and finish: Mirror stainless steel hinge and stainless steel shaft
Application: Opening angle 180°

Performance parameter:

Maximum static load
Radial load: 76N
Axial load: 161N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories
	CL253-13										



Main material and finish: Aluminum alloy hinge leaf, shaft


Application: Opening angle 180°

Performance parameter:


Maximum static load

Radial load: 180N

Axial load: 530N



ERP CL253A00001



ERP CL253S4A037

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket



Main material and finish: SUS304 mirror plastic board 304 stainless steel
Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 340N

Axial load: 600N




Main material and finish: Aluminum alloy hinge, POM shaft

Application: The hinge is damping hinge with bolt adjustable damping force



ERP CL253S9C004



ERP CL253A9A001



CL253-25

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Main material and finish: Mirror polishing stainless steel SS304


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 340N

Axial load: 600N



ERP

CL253S4A049



ERP

CL253F1A002



CL253-26

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

Main material and finish: Mirror polishing stainless steel SS304


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 780N

Axial load: 840N



ERP

CL253S4A040



ERP

CL253F3D013



Main material and finish: Black powder coated carbon steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 500N

Axial load: 700N



Main material and finish: 3+ zinc plated carbon steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 990N

Axial load: 990N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock

Hinge	Seal gasket



CL253-30

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

Main material and finish: Mirror polishing stainless steel SS304


Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 310N

Axial load: 480N



ERP

CL253S4A054



CL253-31

Seal gasket	Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

Main material and finish: Mirror polishing stainless steel SS304


Application: Opening angle 180°

Performance parameter:

Maximum static load


Radial load: 650N

Axial load: 550N



ERP

CL253S00008



ERP

CL253S4A057



Main material and finish: Mirror polishing stainless steel SS304 exposed hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 610N

Axial load: 510N



Main material and finish: Mirror polishing stainless steel SS304 exposed hinge


Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 450N

Axial load: 400N



ERP

CL253S4A056

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod lock	Panel lock	Toggle and hook	Handles	Door stop	Hinge	Seal gasket

CL255





Main material and finish: Black powder coated hinge, nickel plated steel pin
Application: Opening angle 180°

Performance parameter:




Maximum static load

Model: CL255-1/2/3

Radial load: 935N **Axial load:** 915N



Door cutout



ERP

CL254Z1A001

CL254



Main material and finish: Black powder coated ZDC hinge, nickel plated steel pin
Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1000N

Axial load: 800N

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles


Door stop

Hinge






Seal gasket

Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

Seal gasket



Nylon pin (Optional)



ERP

CL257F3D001

CL257



Main material and finish: White zinc-plated steel hinge and pin, PA spacer sleeve

Application: Opening angle 110°

Performance parameter:

Maximum static load

Radial load: 885N

Axial load: 525N



Main material and finish: 3+ zinc plated carbon steel hinge





Application: opening angle 105°

Performance parameter:

Max Static load

Radial load: 130N

Axial Load: 220N



CL261



Main material and finish: White zinc-plated steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 340N

Axial load: 200N

Specification	LH	RH
ERP	CL257F3D009	CL257F3D008

ERP	CL261F3D001
-----	-------------



Main material and finish: White zinc-plated steel hinge




Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 350N

Axial load: 205N



Main material and finish: Electrolysis stainless steel SS304 exposed hinge

Application: Opening angle 180°

Performance parameter:




Maximum static load

Radial load: 600N

Axial load: 400N

ERP	CL260F3D001
-----	-------------

ERP	CL261S9C002
-----	-------------

	Accessories	Electronic lock	Handle lock	Cylinder lock	Electronic lock	Handle lock	Cylinder lock	Accessories
CL262								

Main material and finish: White zinc-plated steel hinge

Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 430N

Axial load: 650N

CL263



Main material and finish: White zinc-plated steel hinge

Performance parameter:



Maximum static load




Radial load: 1295N

Axial load: /

ERP

CL262F3D001



	Accessories	Electronic lock	Handle lock	Cylinder lock	Electronic lock	Handle lock	Cylinder lock	Accessories
CL264								

Main material and finish: Black powder coated ZDC hinge, stainless steel gasket, nickel plated steel pin

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1050N

Axial load: 980N

CL266




Main material and finish: White zinc-plated steel hinge



Performance parameter:


Maximum static load

Radial load: 260N

Axial load: 340N


	Hinge	Panel lock	Toggle and hook	Handles	Door stop	Seal gasket
CL263						

	Hinge	Panel lock	Toggle and hook	Handles	Door stop	Seal gasket
CL266						

	ERP	CL262F3D001
		


ERP

CL262F3D001

	ERP	CL264Z1A001
		

ERP

CL264Z1A001

	ERP	CL266F3D001
		

ERP

CL266F3D001

CL268



INOX
AISI 3..


Main material and finish: Stainless steel or steel hinge

Performance parameter:



Maximum static load

Radial load: 260N

Axial load: 450N



Model	ERP	H	Material
CL268-1	CL268S00001	23.9	Stainless steel
CL268-2	CL268S00002	20.5	Stainless steel
CL268-3	CL268S00003	17.5	Stainless steel
CL268-1A	CL268F3D001	23.9	Steel
CL268-2A	CL268F3D002	20.5	Steel
CL268-3A	CL268F3D003	17.5	Steel



CL270



Main material and finish: White zinc-plated steel hinge

Performance parameter:

Maximum static load

Radial load: 2000N

Axial load: 2000N

CL269



INOX



Main material and finish: White zinc-plated steel hinge

Performance parameter:

Maximum static load

Radial load: 610N

Axial load: 800N



CL270-4-1D



Main material and finish: 3+ zinc plated carbon steel exposed hinge and shaft

Application: opening angle 180°

Performance parameter:

Maximum static load

Radial load: 250N

Axial load: 150N

ERP

CL269F3D001

ERP

CL270F00004

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Toggle and hook

Panel lock

Handles

Door stop

Hinge

Seal gasket

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket




CL272



Main material and finish: Black PA hinge, steel screw, PC shaft
Application: Opening angle 160°

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock
-------------	-----------------	-------------	---------------	------------	------------------



ERP

CL272N00001




CL272-2




Main material and finish: POM black male and female hinge transparent PC shaft, and Stainless steel adjustable screw and nut.
Application: Maximum rotating angle 165°

Hinge	Handles	Toggle and hook	Panel lock
-------	---------	-----------------	------------



ERP

CL272N00002



ERP

CL273F3D001



CL273



Main material and finish: White zinc-plated steel hinge
Application: Opening angle 90°~120°

Performance parameter:
Maximum static load
Radial load: 260N
Axial load: 340N




CL274



Main material and finish: White zinc-plated steel hinge
Application: Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 180N
Axial load: 310N



ERP

CL274F3D001

Hinge	Seal gasket
-------	-------------



CL275-1

Accessories
Handle lock
Electronic lock
Cylinder lock
Plane lock
Rod control lock



Main material and finish: White zinc-plated steel hinge





Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 120N

Axial load: 310N



ERP CL275F3D010

ERP CL275F3D002



CL275-2

Door stop
Handles
Toggle and hook
Panel lock



Main material and finish: White zinc-plated steel hinge





Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 120N

Axial load: 310N



ERP CL276Z3D001

ERP CL275F3D003



CL275-4



Main material and finish: 3+ zinc plated carbon steel hinge

Application: Opening angle 120°

Performance parameter:


Maximum static load

Radial load: 410N

Axial load: 91N



CL276



Main material and finish: White zinc-plated ZDC female hinge

Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 480N

Axial load: 690N



Hinge	Door stop	Handles	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories	CL280
Seal gasket											
											

The technical drawing illustrates two components, CL280-1-Z and CL280-1-Y, used in conjunction. The top part, CL280-1-Z, is a horizontal plate with a central circular hole of diameter $\phi 10$. A vertical slot of height 3 is located to the right of the hole. Below this, a cross-sectional view shows a central vertical column with a height of 72 and a base width of 52. Four holes of diameter $\phi 8.1$ are arranged in a 2x2 pattern on the left side of the base. To the right of the central column, there is a vertical slot of height 72 and a base width of 52. Three holes of diameter $\phi 4.2$ are arranged in a 3x1 pattern along the bottom edge of this section. The bottom part, CL280-1-Y, is a rectangular plate with a central vertical column. It features four holes of diameter $\phi 8.1$ arranged in a 2x2 pattern on its left side. On its right side, there is a vertical slot of height 72 and a base width of 52, containing three holes of diameter $\phi 4.2$ arranged in a 3x1 pattern along its bottom edge.

	CL281-A-Z LH	CL281-A-Y RH
ERP	CL281S4A001	CL281S4A003

The figure consists of three parts: a front view diagram, a side view diagram, and a 3D perspective view.

Front View Diagram:

- Overall width: 37
- Width from handle center to vertical wall: 27
- Width from handle center to horizontal wall: 32
- Height from floor to handle center: 17
- Minimum gap from handle to adjacent wall: ≥ 3
- Radius of handle arc: 120°
- Vertical clearance between handle and horizontal wall: 2.5
- Vertical clearance between handle and floor: 3.5

Side View Diagram:

- Total height: 38
- Shaft height: 30
- Shaft diameter: $\phi 8$
- Shaft shoulder diameter: $\phi 5$
- Shaft shoulder height: 15
- Shaft shoulder to handle center: 16
- Shaft shoulder to handle base: 6.5
- Handle base height: 8
- Handle base diameter: $\phi 11$
- Handle base to floor: 25
- Handle base to handle center: 43

3D Perspective View: Shows the handle installed in a door panel, illustrating its physical form and how it fits into the door frame.

The technical drawing illustrates a door hinge assembly with the following dimensions:

- Top View Dimensions:**
 - Width of the hinge body: 135 mm
 - Height of the hinge body: 110 mm
 - Thickness of the hinge body: 30 mm
 - Width of the positioning pin: 2-Ø 6 mm
 - Height of the positioning pin: 40 mm
 - Width of the main body: 60 mm
 - Distance from the center of the positioning pin to the center of the top screw holes: 55 mm
 - Distance from the center of the bottom screw holes to the center of the top screw holes: 50 mm
 - Width of the top screw holes: 4-Ø 9 mm
 - Angle of the top screw holes: Ø 19x90°
 - Length of the adjustable shaft: 27.5 mm
 - Total height of the hinge: 6.5 mm
 - Vertical clearance for the adjustable shaft: +1 mm
 - Vertical clearance for the main body: +1 mm
 - Angular adjustment range: 180°
- Side View and Perspective:** An exploded perspective diagram shows the hinge's internal components: the main body, the adjustable shaft, and the positioning pins.

CL281

CL281-1-Y CL281-1-Z

INOX
AISI
3..

Main material and finish: Stainless steel hinge

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1280N

CL282-1-Y
CL282-1-Z

Main material and finish: Pocked black powder coated ZDC female part, stainless steel shaft

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1800N

Axial load: 1500N

Hinge	Door stop	Handles	Panel lock	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories


CL282-2-Y
CL282-2-Z



Main material and finishing: Pocked black powder coated ZDC female hinge, stainless steel shaft
Application: Opening angle 180°

Performance parameter:

Maximum static load
Radial load: 1500N
Axial load: 1300N




ERP	CL282-2-Z LH	CL282-2-Y RH
	CL282Z1B003	CL282Z1B004



INOX
AISI 3..

Main material and finish: Stainless steel hinge and pin
Application: Opening angle 140°

Performance parameter:
Maximum static load
Radial load: 500N
Axial load: 980N



ERP	CL283S00003


Hinge	Door stop	Handles	Panel lock	Toggle and hook	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

CL283-1
CL283-2




Main material and finish: stainless steel hinge and shaft
Application: Opening angle 120°


Performance parameter:
Maximum static load
Radial load: 500N
Axial load: 980N



CL283-1



CL283-2



ERP	CL283-1	CL283-2
	CL283S00001	CL283S00002

Hinge	Door stop	Handles	Panel lock	Rod control lock	Plane lock	Cylinder lock	Handle lock	Electronic lock	Accessories

Seal gasket



CL283-8

NEW



Main material and finish: Zinc nickel alloy steel hinge

Application: Opening angle 130°


Performance parameter:

Maximum static load

Radial load: 240N


Axial load: 330N

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Rod control lock	Handle lock	Cylinder lock	Plane lock	Accessories



ERP

CL283F3D006



ERP

CL289Z2A001



Main material and finish: Black painted ZDC female part

Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 1500N

Axial load: 1435N

Embedded screw recommended tightening torque: 10N. m

Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock



Main material and finish: Painted aluminium alloy

Application: Opening angle 180°


Performance parameter:

Maximum static load

Radial load: 1000N


Axial load: 1000N

Hinge	Handles	Panel lock	Toggle and hook	Door stop	Seal gasket



ERP

CL288S00001



ERP

CL289A2B001

Hinge	Seal gasket

	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Rod control lock	Accessories
CL290								



INOX
AISI
3...

Main material and finish: Stainless steel hinge



Application: Opening angle 110°

Performance parameter:

Maximum static load


Radial load: 140N

Axial load: 310N



ERP CL290S00001

	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Rod control lock	Accessories
CL293								



Main material and finish: Sand-spraying and nickle-plated casting steel hinge


Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 3000N

Axial load: 3000N



ERP CL293F3I001

	Hinge	Toggle and hook	Panel lock	Handles	Door stop	Hinge	Seal gasket
CL292							



Main material and finish: Sand-spraying and chrome-plated ZDC hinge, carbon steel pin


Application: Opening angle 180°

Performance parameter:

Maximum static load

Radial load: 95N

Axial load: 105N



ERP CL292Z3H001

	Hinge	Toggle and hook	Panel lock	Handles	Door stop	Hinge	Seal gasket
CL294							



INOX
AISI
3...

Main material and finish: Stainless steel hinge


Application: Opening angle 120°

Performance parameter:

Maximum static load

Radial load: 2000N

Axial load: 1500N



ERP CL294S00001

	Accessories	Electronic lock	Handle lock	Cylinder lock	Plane lock	Rod control lock	Rod control lock	Accessories
CL295								

CL295





Accessories
Electronic lock
Handle lock
Cylinder lock
Plane lock
Rod control lock



Main material and finish: Black PA hinge, white zinc plated steel pin
Application: Opening angle 180°

Performance parameter:
Maximum static load
Radial load: 1180N
Axial load: 1515N



ERP CL295N00001

CL296





Door stop
Handles
Toggle and hook
Panel lock




Main material and finish: White zinc-plated steel hinge
Application: Opening angle 120°

Performance parameter:
Maximum static load
Radial load: 200N
Axial load: 160N



ERP CL296F3D001




ERP CL297F00001

CL297



Main material and finish: Antirust oil soaked steel hinge
Application: Opening angle 155°

Performance parameter:
Maximum static load
Radial load: 1500N
Axial load: 1800N



ERP CL297F00002

CL297-2



Main material and finish: Antirust oil soaked steel hinge leaf, stainless steel pin
Application: Opening angle 150°

Performance parameter:
Maximum static load
Radial load: 900N
Axial load: 2000N

Accessories
Electronic lock
Handle lock
Cylinder lock

Plane lock
Rod control lock

Panel lock
Toggle and hook
Handles
Door stop

Hinge
Seal gasket



Main material and finish: Nanometer painted ZDC hinge and nickel plated steel pin


Application: Opening angle 90°

Performance parameter:

Maximum static load

Radial load: 260N

Axial load: 330N



	Nanometer painted	Black powder coated
ERP	CL331Z2B001	CL331Z1A001



Main material and finish: Black powder coated ZDC hinge and nicked plated steel pin


Application: Opening angle 90°

Performance parameter:



















Maximum static load











































Radial load: 295N























































Axial load: 625N



	Nanometer painted	Black powder coated
ERP	CL332Z2B001	CL332Z1A001



	MFT-017	MFT-018	MFT-019	MFT-020	MFT-036	MFT-037	MFT-038	MFT-039	Accessories
Cylinder lock									Electronic lock
Handle lock									Handle lock
Electronic lock									Cylinder lock
Accessories									
Plane lock									Plane lock
Toggle and hook									Rod control lock
Panel lock									Panel lock
Rod control lock									Toggle and hook
Handles									Handles
Door stop									Door stop
Hinge									Hinge
Seal gasket									Seal gasket

		Accessories							
		Electronic lock				Handle lock			
		Cylinder lock		Plane lock		Rod control lock		Toggle and hook	
Seal gasket	Hinge	Door stop	Handles	Door stop	Handles	Door stop	Handles	Door stop	Hinge
MFT-051	MFT-054	MFT-055	MFT-056	Tee Pipe	FJ019-3	FJ019-2	FJ019-1D		
									
									
MFT-058	MFT-059	MFT-060	MFT-065						
									
									
MFT-067	MFT-068	MFT-069	MFT-070						
									
									
									
									
									
									
									
									
					<img alt="Technical drawing of FB0155" data-bbox="575 4200				

Index

Model	Page	Model	Page	Model	Page	Model	Page	Model	Page	Model	Page	Model	Page	Model	Page		
Electronic Series		Cabinet Series														Hinge Series	
DS864-8-7A	032	MS301-1	041	MS715	078	MS744	084	MS813-4	107	MS840-B	184	MS866-21S	222	CL103	281		
DS899	034	MS302-1	041	MS717-1	127	MS744-3	085	MS813-5B	109	MS840-C	185	MS866-22	221	CL104	281		
DS899-1A	036	MS302-2	041	MS717-2	127	MS745-1/2	085	MS813-B	108	MS840-6P	186	MS866-26	223	CL105	282		
DS912	038	MS304	042	MS718	128	MS745-4	086	MS815-1	109	MS842	053	MS866-27	223	CL106	282		
DS913	039	MS306	042	MS718-2	128	MS746-2	086	MS815-2	110	MS843	147	MS866-28	224	CL108	283		
		MS307	043	MS718-3	129	MS748	087	MS815-3	110	MS844	121	MS866-29	225	CL108-2	283		
		MS308-2	043	MS718-3C	129	MS748-3/3A	087	MS816-1/1A	111	MS845-1/3	121	MS867	202	CL109	284		
		MS315-4	044	MS718-4C	130	MS748-3B	088	MS816-1E-1/2	112	MS845-5	122	MS867-8	203	CL109-2	284		
		MS317	045	MS719	130	MS748-4	088	MS816-2	113	MS845-7B	122	MS868	055	CL111	285		
		MS317-1A	046	MS719-1C	131	MS753	089	MS816-3S-1/2	114	MS846	187	MS870-2	226	CL111-2	285		
		MS320	047	MS719-1U	131	MS754	090	MS816-4B	115	MS848	188	MS874	144	CL111-3-1D	286		
		MS322-2	046	MS720	134	MS755	091	MS816-4D-4/5	115	MS848-1E	189	MS875-1/2	204	CL114	286		
		MS323	048	MS721	078	MS756	091	MS817	116	MS848-B	190	MS875-1A/2A	205	CL115	287		
		MS324	048	MS722	079	MS758	092	MS818	142	MS850-1A	210	MS875-3	206	CL116	287		
		MS324-2	049	MS723	132	MS758-2	092	MS818-3B	143	MS850-2/2A	211	MS876	207	CL117	288		
		MS324-3	049	MS723-2	133	MS760	093	MS819	176	MS853	194	MS882	208	CL119	288		
		MS330	060	MS723-3	133	MS761	093	MS820	163	MS855-3	195	MS887-1	055	CL121	289		
		MS353	050	MS726-1	134	MS762	094	MS820-1A	164	MS855-5	197	MS887-2	056	CL123	289		
		MS703	124	MS726-1A	135	MS769-1	095	MS821	165	MS856	212	MS887-3	057	CL125	290		
		MS704-1	061	MS726-2	135	MS769-2	095	MS822	118	MS857	213	MS887-4	058	CL126	290		
		MS704-1A	061	MS726-3	136	MS769-3	094	MS823-1	117	MS858	214	MS892-1A	158	CL127-1/2	291		
		MS704-2	060	MS727	136	MS772	096	MS823-1A	117	MS859	054	MS982-3	227	CL128	292		
		MS705	064	MS728	137	MS773	096	MS824	118	MS860	148	MS982-3A	227	CL128-2	292		
		MS705-1W-2D	069	MS729-1	079	MS773-3	097	MS825	119	MS861	149	MS983	225	CL129	293		
		MS705-K	068	MS729-2	079	MS773-4	097	MS826	119	MS861-2	149			CL130-2	293		
		MS705-Q	068	MS729-3	079	MS773-5	098	MS826-7D	120	MS861-2A	152			CL132	294		
		MS705-3A	070	MS730	137	MS775-2	098	MS826-8D	120	MS861-2B	198			CL132-2	295		
		MS705-3C	069	MS730-1A	138	MS779	099	MS828	166	MS861-2E	199			CL133	294		
		MS705-3C-4	071	MS731-1	160	MS784	099	MS828-1F	167	MS861-2G	150			CL133-2	295		
		MS705-3D	071	MS731-2	160	MS786	100	MS828-8	168	MS861-2H	151			CL135	296		
		MS705-3E	072	MS731-3	161	MS801-1	101	MS828-9	169	MS861-3	153			CL137	297		
		MS705-3J	072	MS731-4	161	MS801-2	100	MS829	170	MS861-4	154			CL138	297		
		MS705-3U	073	MS731-6	162	MS802	102	MS830	171	MS864-3	155			CL138-3	298		
		MS705-8G	073	MS732	138	MS803	102	MS830-3	171	MS864-3A	155			CL139	298		
		MS705-24G	074	MS733	080	MS804	103	MS830-6	172	MS864-4	157			CL142	299		
		MS705-27	074	MS734	080	MS805	103	MS831	176	MS865	200			CL145	299		
		MS706	075	MS735	081	MS806	104	MS832	177	MS866-1	215			CL148	300		
		MS707	124	MS735-2	081	MS807-1	051	MS833	177	MS866-2	215			CL150	300		
		MS708	125	MS735-4	082	MS807-2	051	MS834	178	MS866-3	216			CL152	301		
		MS710	125	MS736	139	MS807-3	051	MS834-5	144	MS866-4	216			CL152-2	301		
		MS712	126	MS737	139	MS809	104	MS834-6	179	MS866-5	217			CL154	302		
		MS713	126	MS738	140	MS811-1/2	105	MS839	145	MS866-5E	218			CL154-3	303		
		MS713-Q	126	MS738-1A	141	MS811-3	105	MS839-5	146	MS866-6	219			CL156	303		
		MS714-1	076	MS738-2A	141	MS811-4	105	MS840	180	MS866-7	220			CL156-2	304		
		MS714-2	076	MS741	083	MS812-1	106	MS840-4	181	MS866-7-1P	220			CL158	304		
		MS714-3	077	MS742	083	MS812-2	107	MS840-5	182	MS866-8	221			CL158-2	305		
		MS714-4	077	MS743	084	MS813	108	MS840-A	183	MS866-21	222			CL158-3	305		

Index

Model	Page	Model	Page	Model	Page	Model	Page	Model	Page	Model	Page	Model	Page	Page	Model	Page
Hinge Series																
CL158-4/5	306	CL206-3B	331	CL233-2	357	CL261	382	DKS	229	LS501	255	TX80-1	274			
CL163	306	CL206-4	331	CL234	357	CL261-2	382	DK601	229	LS503	255	TX80-2	274			
CL167	307	CL206-12	332	CL235	358	CL262	383	DK602	230	LS504-1	256	TX90-1	275			
CL168	307	CL207	332	CL236	358	CL263	383	DK603	231	LS504-2	256	TX90-2	276			
CL168-2	308	CL208	333	CL237	359	CL264	384	DK603-3	232	LS504-3	257	TX90-3	275			
CL169	308	CL209-1C	333	CL237-2	359	CL266	384	DK604	231	LS505	257	TX91	276			
CL170	309	CL209-1/2	334	CL237-3	360	CL268	385	DK605	233	LS506	258	TX92-2	277			
CL173	309	CL210	335	CL237-4	360	CL269	385	DK606	233	LS507	259	TX100-B	277			
CL178	310	CL211	335	CL238	361	CL270	386	DK609	234	LS508	260	TX101-1	278			
CL179	310	CL212	336	CL240-1/2	362	CL270-4-1D	386	DK609-2	235	LS509	261	TX101-2	278			
CL180	311	CL212-1B	336	CL244	363	CL272	387	DK610	236	LS510	259					
CL181	311	CL212-3A	337	CL246	363	CL272-2	387	DK611	236	LS511	262					
CL186	312	CL212-F	337	CL247	364	CL273	388	DK614	237	LS513	263					
CL188	312	CL213-1	338	CL248	364	CL274	388	DK615	237	LS514-1/2/3	264					
CL190	313	CL213-2	338	CL249	365	CL275-1	389	DK616	238	LS515	263					
CL195	313	CL213-3	339	CL250-1/2	365	CL275-2	389	DK617	238	LS516	265					
CL195-3	314	CL213-6	339	CL250-3/4	366	CL275-4	390	DK617-5	239	LS516-2A	265					
CL196	314	CL213-7	340	CL250-6	366	CL276	390	DK618-6	239	LS516-2A-1D	266					
CL200-1	316	CL213-9	340	CL251	367	CL280	391	DK618-7	240	LS518	266					
CL201-1	315	CL214	341	CL251-3	367	CL280-2	391	DK618-8	240	LS519	267					
CL201-2	316	CL215	341	CL252	368	CL281	392	DK618-9	241	LS520	267					
CL201-3	317	CL216	342	CL253-1	368	CL282-1	392	DK619-2-1D	241	LS521	268					
CL201-4	317	CL217	342	CL253-2/3	369	CL282-2	393	DK619-9	242	LS522	269					
CL201-5	318	CL218	343	CL253-4	369	CL283-1/2	394	DK623	242	LS523	268					
CL201-6	319	CL219	344	CL253-4A	370	CL283-4	393	DK624	243	LS531	270					
CL201-9	319	CL220	345	CL253-5	370	CL283-8	395	DK627	244	LS532	270					
CL201-12	320	CL221	345	CL253-6	371	CL288	395	DK631-2	244	LS537-3	271					
CL202-1	320	CL222	346	CL253-7	371	CL289	396	DK633-1	245	LS539	271					
CL202-2	321	CL223	346	CL253-9	372	CL289-2	396	DK633-3	246	LS546-Y	272					
CL203-2B	321	CL225	347	CL253-10	372	CL290	397	DK634	246							
CL203-1/2/3	322	CL225-3	348	CL253-13	373	CL292	397	DK635	247							
CL203-4	323	CL225-5	348	CL253-16	373	CL293	398	DK636-1/2	248							
CL203-7	323	CL225-7	349	CL253-20	374	CL294	398	DK637	249							
CL204-1	324	CL226	350	CL253-23	374	CL295	399	DK639	250							
CL204-2/3	324	CL226-4A	349	CL253-25	375	CL296	399	DK725	251							
CL204-3C	325	CL226-5A	351	CL253-26	375	CL297	400	DK725-5	252							
CL204-3D	325	CL226-6A	351	CL253-27	376	CL297-2	400	DK725-7	253							
CL204-3F	326	CL226-7	352	CL253-28	376	CL331	401	DK725-8	253							
CL204-3K	326	CL226-8	352	CL253-30	377	CL332	401									
CL204-3S	327	CL229-2A/2B	353	CL253-31	377											
CL204-4D	327	CL230	353	CL253-32-1	378											
CL204-7	328	CL230-3	354	CL253-32-2	378											
CL205-1	328	CL230-4	354	CL254	380											
CL205-2	329	CL230-3-1D	355	CL255	379											
CL206-1	329	CL231	355	CL257	380											
CL206-2	330	CL232	356	CL257-2	381											
CL206-3	330	CL233	356	CL260	381											

Index

Toggle and hook Series

Handle Series

Door stop Series

Accessories

Tee pipe

Seal gasket series ...

New product list

Electronic lock	Cabinet lock	Toggle	Hinge	Hinge
DS912 DS913	MS315-4	DK614	CL109-2	CL213-9
	MS705-27	DK619-9	CL111-2	CL237-4
	MS773-5	DK627	CL111-3-1D	CL251-3
	MS861-2G	DK633-3	CL154-3	CL257-2
	MS861-2H		CL168-2	CL275-4
	MS861-4		CL195-3	CL283-8
	MS828-8		CL200-1	CL297-2
	MS828-9		CL201-9	
	MS840-6P		CL201-12	
	MS867-8		CL206-12	

Sample Tips

The performance and application specification of our products are only for reference. If the application conditions of the chosen products and the matching products can not be confirmed, then they should be tested under the practical situation and environment. Thereby it can be confirmed whether the products are suitable for the users and whether they satisfy the users in the application. The application conditions will be changed in different applicable occasions and by different installed methods, so the sample only introduces the products' general performance and application. The standard size is only for the users to confirm the products' external size and provide them proper installed methods. Any mistake or drawback of those data in practical application, we highly welcome your feedback information.

Order of regular standard items will be handled and dispatched faster than those of irregulars and nonstandard ones.

All of your cabinet locks, hinges, door stops and other regular products are RH application. Drawings of this catalog may not share single unified scale.

Remark:

Remark: